

Specification Sheet

Part Number: 156-00589



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

2-Piece Cable Tie & Edge Clip, 8.0" Long, EC5A, 1–3 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg

Article Number	156-00589
----------------	-----------

Type	T50REC5A
------	----------

Color	Black (BK)
-------	------------

Quantity Per	bag
--------------	-----

Product Description	HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.
---------------------	--

Short Description	2-Piece Cable Tie & Edge Clip, 8.0" Long, EC5A, 1–3 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg
-------------------	--

Global Part Name	T50REC5A-PA66UV/PA66HIRHSUV-BK
-------------------------	--------------------------------

Minimum Tensile Strength (Imperial)	50.0
--	------

Minimum Tensile Strength (Metric)	225
--	-----

Length L (Imperial)	8.0
----------------------------	-----

Length L (Metric)	202.0
--------------------------	-------

Fixation Method	EdgeClip, sideways, assembled, 2 piece
------------------------	--

Identification Plate Position	none
--------------------------------------	------

Variant	Inside Serrated
----------------	-----------------

Width W (Imperial)	0.18
---------------------------	------

Width W (Metric)	4.6
-------------------------	-----

Bundle Diameter Min (Imperial)	0.20
---------------------------------------	------

Bundle Diameter Min (Metric)	5.0
-------------------------------------	-----

Bundle Diameter Max (Imperial)	2.0
---------------------------------------	-----

Bundle Diameter Max (Metric)	50.0
-------------------------------------	------

Thickness T (Imperial)	0.05
-------------------------------	------

Thickness T (Metric)	1.2
-----------------------------	-----

Height H (Imperial)	0.61
Height H (Metric)	15.5
Panel Thickness Min (Imperial)	0.04
Panel Thickness Max (Imperial)	0.12
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	3.0
Material	Polyamide 6.6 UV-stabilized (PA66UV) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66UV PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 UV-resistant (PA66UV)
Flammability	UL 94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C) -40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100

Customs Number

3926909988

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)