

## Specification Sheet

Part Number: 151-01169

Designed for use with MCT18 - MCT30 cable ties to provide stability when securing bundles.

Simple to install with a screw or rivet.

Metal content dispersed throughout mount ensures identification by metal detectors and X-ray machines.

Industry standard blue color assists with visual detection and reduces the risk of contamination.



Metal Cnt Cable Tie Screw Mnt, .75" x .75", .14" Max Tie Width, .12" Hole Dia, PA66MP, Blue, 100/pkg

**Article Number** 151-01169

**Type** MCMB3

**Color** Blue (BU)

**Quantity Per** bag

**Product Description** The MCMB3 mounts are for use with HellermannTyton MCT18 - MCT30 Series cable ties to provide stability when securing bundles. The Metal Content Mount is specifically designed for the food, beverage and pharmaceutical processing industries to meet the safety standards set by the Hazardous Analysis of Critical Control Point (HACCP). The mount is nylon-based with metal content dispersed throughout allowing for the part to be identified by metal detectors or X-ray inspections, reducing the risk of contamination.

<b>Short Description</b>	Metal Cnt Cable Tie Screw Mnt, .75" x .75", .14" Max Tie Width, .12" Hole Dia, PA66MP, Blue, 100/pkg
<b>Global Part Name</b>	MCMB3-PA66MP-BU
<b>Length L (Imperial)</b>	0.75
<b>Length L (Metric)</b>	19.0
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	0.75
<b>Width W (Metric)</b>	19.0
<b>Cable Ties</b>	MCT18 - MCT30
<b>Height H (Imperial)</b>	0.17
<b>Height H (Metric)</b>	4.3
<b>Cable Tie Width Max (Imperial)</b>	0.14
<b>Cable Tie Width Max (Metric)</b>	3.5
<b>Mounting Hole Diameter D (Imperial)</b>	0.12
<b>Mounting Hole Diameter D (Metric)</b>	3.1 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.12

**Mounting Hole Diameter D Max (Imperial)** 0.12

**Mounting Hole Diameter D Max (Metric)** 3.1

**Mounting Hole Centers (Imperial)** 0.52

**Material** Polyamide 6.6, with metal particles (PA66MP)

**Material Shortcut** PA66MP

**Flammability** UL 94 HB

**Halogen Free** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909988

