

Specification Sheet

Part Number: 157-00083



Design gives quick and easy assembly by hand without the need for tools.

Mount can be used in a wide variety of applications where 5mm weld studs or 5mm ISO bolts.

Design provides low insertion force and high extraction force.

Standoff Stud Mount Tie, 6.0 mm studs, 6.0" Long, PA66HS, Black, 1000/pkg

Article Number	157-00083
----------------	-----------

Type	T50SSBS6OT-E
------	--------------

Color	Black (BK)
-------	------------

Quantity Per	bag
--------------	-----

Product Description	The Standoff Stud Mount tie applies easily to weld studs and secures bundles away from fixing holes. These are used primarily in the automotive industry, but can be used in a variety of applications.
---------------------	---

Short Description	Standoff Stud Mount Tie, 6.0 mm studs, 6.0" Long, PA66HS, Black, 1000/pkg
-------------------	---

Global Part Name	T50SSBS6OT-E-PA66HS-BK
------------------	------------------------

Minimum Tensile Strength (Imperial)	45.0
Minimum Tensile Strength (Metric)	200
Length L (Imperial)	6.0
Length L (Metric)	160
Fixation Method	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.16
Bundle Diameter Min (Metric)	1.0
Bundle Diameter Max (Imperial)	1.4
Bundle Diameter Max (Metric)	35.0
Stud Diameter (Metric)	6.0 mm
Stud Diamater (Imperial)	0.24

Material	Polyamide 6.6 heat stabilized (PA66HS)
-----------------	--

Material Shortcut	PA66HS
--------------------------	--------

Operating Temperature	-40°F to +221°F (-40°C to +105°C)
------------------------------	-----------------------------------

Reach Compliant (Article 33)	Yes
-------------------------------------	-----

ROHS Compliant	Yes
-----------------------	-----

Package Quantity (Imperial)	1000
------------------------------------	------

Package Quantity (Metric)	1000
----------------------------------	------

Customs Number	3926909988
-----------------------	------------