

Specification Sheet

Part Number: 156-02711



One-piece ratchet closure allows for easy installation during pre- or final assembly
Easy release feature simplifies quick adjustments and maintenance
Impact modified, heat and UV stabilized PA66 provides long-term durability, indoors and out
High-performing oval fir trees ensure anti-rotational routing in existing or stamped oval or rectangular holes with no additional hardware required

Article Number 156-02711

Type IRCBFTOVAL

Color Black (BK)

Quantity Per bag

Product Description

The Inline Ratchet P-Clamp family offers versatility when managing wires, cables and hoses. Built-in attachments include round and oval fir trees and adhesive mounts, so no additional hardware is needed for securing to a hole or panel. The robust design and durable materials make it ideal for heavy duty applications, both indoors and out. The adjustable clamp can be closed by hand to the desired diameter. The release feature allows easy and nondestructive removal of cables simply by using a flat-head screwdriver. In this way, the clamp can be reused or serviced without removing it from the mounting surface.

Short Description

Inline Ratchet Clamp, 0.50" - 0.77" Bundle Dia, FT7X12, PA66HIRHSUV, Black, 25/bag

Global Part Name

IRCBFTOVAL-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 100.0

Minimum Tensile Strength (Metric) 445.0

Length L (Imperial) 1.37

Length L (Metric) 34.8

Fixation Method Fir Tree for oval holes

Width W (Imperial) 1.37

Width W (Metric) 34.9

Bundle Diameter Min (Imperial) 0.50

Bundle Diameter Min (Metric) 12.70

Bundle Diameter Max (Imperial)	0.77
Bundle Diameter Max (Metric)	19.56
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.27
Panel Thickness Min (Metric)	0.60
Panel Thickness Max (Metric)	6.75
Mounting Hole Diameter D (Imperial)	0.28 x 0.47
Mounting Hole Diameter D (Metric)	7.0 x 12.0 mm
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
UL Listed (US and Canada)	Yes

Package Quantity (Imperial) 25

Package Quantity (Metric) 25

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)