



P/N	MATERIAL	FLAMMABILITY RATING TEST METHOD IEC 60695-2-11
94544-7008	PA 6.6 NATURAL	IEC 60335 - 1 REV. 4 GWT 750 °C

PACKAGING:
 Loose in plastic bag, inside carton box.
 Plastic bags are sealed and contain water for part moisturizing (according to AS-45499-001 norm).
 Customer shall moisturize parts (according to AS-45499-001 norm) in case partial bags are re-sealed at their site.

S.P.Q.: 800 pz.

Std.Descr.: HOUSING DUAL ROW WITH LOCK 8 CKT*

EC NO: Z2018-0006 DRWN: L.SANTESS2017/07/31 CHKD: L.SANTESS2017/08/03 APPR: P.ZANGIROLO2017/08/03	DESCRIPTION REV B3	QUALITY SYMBOLS ▽ - 0 ▽ - 0		GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH		SCALE 2:1	DESIGN UNITS METRIC	FIRST ANGLE PROJECTION	REVISE ON CAD ONLY	
		4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± 0.10 ± --- 1 PLACE ± 0.2 ± ---	ANGULAR ± 2 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DIMENSION STYLE MM ONLY		TITLE HOUSING 8 CKT DOPPIA FILA CON S.LOCK E AGGANCIO		MOLEX INCORPORATED MATERIAL NO. 94544-7008 DOCUMENT NO. SD-94544-001 SHEET NO. 1 OF 1
		DRAWN BY DATE FGOTTARD 2001-12-20		CHECKED BY DATE MTESTAGU 2001-12-20		APPROVED BY DATE GZUIN 2001-12-20		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
		A2								