

## Specification Sheet

Part Number: 155-46302



Oval mount design pushes on easy by hand without the need for tools. Design provides low insertion and high extraction force.

1-Pc Cable Tie/Oval Stud Mount, Designed for 6.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg

<b>Article Number</b>	155-46302
<b>Type</b>	T50SOSSB6HE
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	bag
<b>Product Description</b>	Oval Shaped Stud Mount's special design allows for a .20" (5.5 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The mount allows it to be installed onto a weld stud without the use of any tools.
<b>Short Description</b>	1-Pc Cable Tie/Oval Stud Mount, Designed for 6.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg
<b>Global Part Name</b>	T50SOSSB6HE-PA66HS-BK

<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	170
<b>Length L (Imperial)</b>	6.0
<b>Length L (Metric)</b>	160.0
<b>Fixation Method</b>	Weld Stud Fixing
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Outside Serrated
<b>Width W (Imperial)</b>	0.19
<b>Width W (Metric)</b>	4.7
<b>Bundle Diameter Min (Imperial)</b>	0.04
<b>Bundle Diameter Min (Metric)</b>	1.0
<b>Bundle Diameter Max (Imperial)</b>	1.4
<b>Bundle Diameter Max (Metric)</b>	35.0
<b>Thickness T (Imperial)</b>	0.05

<b>Thickness T (Metric)</b>	1.35
<b>Stud Length Min (Metric)</b>	16.0
<b>Stud Diameter (Metric)</b>	6.0 mm
<b>Stud Diameter (Imperial)</b>	0.24
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL 94 V-2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988

