

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0010181034

Status:

Active

Overview:

Standard .093" Pin and Socket Connectors

Description:

2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 1 Female Terminal, 2 Male Terminals

Documents:

3D Model

3D Model (PDF)

Drawing (PDF)

Packaging Specification PK-3099-002-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

LR19980

UL

E29179

General

Product Family

PCB Headers

Series

3099

Application

Power, Wire-to-Board

Comments

Solder Type|Round Pin/Socket

Overview

Standard .093" Pin and Socket Connectors

Product Name

Standard .093"

UPC

800754984362

Physical

Breakaway

No

Circuits (Loaded)

3

Circuits (maximum)

3

Color - Resin

Black

Durability (mating cycles max)

25

Flammability

94V-2

Glow-Wire Capable

No

Lock to Mating Part

Yes

Material - Metal

Brass, Phosphor Bronze

Material - Plating Mating

Tin

Material - Plating Termination

Tin

Material - Resin

Polyester

Net Weight

1.322/g

Number of Rows

1

Orientation

Vertical

PC Tail Length

4.32mm

PCB Locator

Yes

PCB Retention

None

PCB Thickness - Recommended

1.60mm

Packaging Type

Bag

Pitch - Mating Interface

5.03mm

Plating min - Mating

1.270µm, 5.080µm

Plating min - Termination

1.270µm, 5.080µm

Polarized to Mating Part

Yes

Polarized to PCB

Yes

Shrouded

Fully

Stackable

No

Surface Mount Compatible (SMC)

No


Temperature Range - Operating

-40° to +105°C

Termination Interface: Style

Through Hole

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per -
D(2021)10043-DC (17
Jan 2022)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

Green Image

ELV

Not Relevant

RoHS Phthalates

Not Contained

Search Parts in this Series

3099 Series

Mates With

[1490](#) Receptacle, [1292](#) Receptacle,
[1396](#) Receptacle, [1375](#) Receptacle, [1360](#)
Receptacle, [1261](#) Receptacle

Current - Maximum per Contact	5.0A
Voltage - Maximum	250V

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-3099-002-001
Sales Drawing	SDA-3099-X3XX-001

This document was generated on 02/23/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION