

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1552400013](#)
Status: **Active**
Overview: [Flamar Standard and Custom Cables for Industrial Automation](#)
Description: Flamar Sensor Cable, TPE Jacket, Unshielded, 4 Circuits, 0.34mm² / 22 AWG, 5.40mm (.213") Diameter, 600.0m (1968.50') Length, Black

Documents:

[Product Specification 1552400001-P1E \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Brochure \(PDF\)](#)

Agency Certification

CSA LL107556
UL E470965

General

Product Family Cable
Series [155240](#)
Comments 3 reels of 200.0m each
Crimp Quality Equipment Yes
Geographic Area Global
Overview [Flamar Standard and Custom Cables for Industrial Automation](#)

Product Name Flamar, Signal and Control
UPC 889056452724

Physical

Bending Radius - Minimum > 10xOD
Cable Length 600.0m
Circuits (Loaded) 4
Color - Cable Jacket Black
Insulation PVC
Material - Outer Jacket TPE
Net Weight 0.040/kg
Outer Jacket Diameter 5.40mm
Packaging Type Reel
Temperature Range - Operating -40° to +105°C
Wire Size AWG 22
Wire Size mm² 0.34
Wire/Cable Type UL Listed PLTC

Electrical


Current - Maximum per Contact Contact Molex
Voltage - Maximum 300V

Material Info

Engineering Number 3X200M

Reference - Drawing Numbers

Product Specification 1552400001-P1E



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2020)9139-DC (19
Jan 2021)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit [Contact US](#)

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

[155240](#) Series

Use With

Nano-Change (M8) [120091](#) , Micro-Change (M12) [120071](#) , Ultra-Lock (M12) [120085](#)