

IEC Appliance Inlet C20 with Circuit Breaker TA45



Screw-on version from front or rear side  
Rocker non-illuminated  
white



Snap-in mounting from front side  
Rocker illuminated  
orange

C20



70° C

#### Description

- Panel mount :  
Screw-on version from front or rear side, snap-in version front side
- 2 Functions :  
Appliance Inlet Protection class I , circuit breaker type TA45 2-pole
- Quick connect terminals 6.3 x 0.8 mm

See below:

#### Approvals and Compliances

#### Characteristics

- All single elements are already wired
- Unwired versions available on request
- Circuit Breaker non-illuminated or illuminated
- Suitable for use in equipment according to IEC/UL 62368-1

#### Other versions on request

- Unwired versions
- Variant with notch for V-Lock mating Cordsets

#### References

Alternative: version with line filter [EF12](#)

#### Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Approvals](#), [Distributor-Stock-Check](#), [Accessories](#), [Detailed request for product](#)

Newly available variants corresponding to V-Lock mating cordset. The connector is equipped with a notch intended for use with the latching cordset. The cord latching system prevents against accidental removal of the cordset.

#### Technical Data

Ratings IEC	16A / 250VAC; 50Hz
Ratings UL/CSA	20A / 250VAC; 60Hz
Dielectric Strength	> 1.5 kVAC between L-N > 3 kVAC between L/N-PE (1 min/50Hz)
Allowable Operation Temperature	-10 °C to 55 °C
IP-Protection	front side IP40 acc. to IEC 60529
Protection against electric shock	Suitable for appliances with protection class I acc. to IEC 61140
Terminal	Quick connect terminals 6.3 x 0.8 mm
Panel Thickness S	Screw: max 8mm Mounting screw torque max 0.5 Nm Snap-in: 1.5/2.5 mm
Material: Housing	Thermoplastic, black, UL 94V-0

Appliance inlet/-outlet	C20 acc. to IEC 60320-1, UL 60320-1, CSA C22.2 no. 60320-1 (for cold conditions) pin-temperature 70 °C, 16A, Protection Class I
Circuit Breakers	Acc. IEC/EN 60934, UL 1077, CSA 22.2 no. 235 2-pole rocker switch, illuminated or non-illuminated. Optional with undervoltage- or remote trip release Short circuit capacity Icn: at $I_n < 3A/240VAC$ : $10 \times I_n$ at $I_n \geq 3A/240VAC$ : 300A

#### Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

## Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: EF11

Approval Logo	Certificates	Certification Body	Description
	VDE Approvals	VDE	Certificate Number: 40001029
	UL Approvals	UL	UL File Number: E96454

## Product standards

Product standards that are referenced

Organization	Design	Standard	Description
	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
	Designed according to	UL 60320-1	Standard for Attachment Plugs and Receptacles
	Designed according to	CSA C22.2 no. 60320-1	General Use Receptacles, Attachment Plugs, and Similar Wiring Devices

## Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
	Designed for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements

## Compliances


The product complies with following Guide Lines

Identification	Details	Initiator	Description
	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.
		SCHURTER AG	V-Lock system are based on a matching plug-dose combination. The connector is equipped with a notch intended for use with the latching cordset. The cord latching system prevents against accidental removal of the cordset.

**Dimensions [mm]**  
 Screw-on mounting




\*\* --- Version TA45 with undervoltage release  
 Snap-in mounting



\*\*--- Version TA45 with undervoltage release

## Diagrams





## Effect of ambient temperature

The units are calibrated for an ambient temperature of +23°C. To determine the rated current for a lower or higher ambient temperature, use a correction factor (typical value) from the table below:


Ambient Temperature [°C]	Correction factor
-10	0.89
-5	0.91
0	0.92
+23	1.00
+30	1.03
+40	1.08
+55	1.16

Example: Rated current = 5 A, Environmental temperature = 40 °C, --> Correction factor = 1.08, Resulting current = 5.5 A --> Round to next higher rated current: 6 A

## Time-Current-Curves

Tripping Characteristics  $I_n < 3$  ATripping Characteristics  $I_n \geq 3 \dots < 18$  A

Tripping Characteristics  $I_n \geq 18 \text{ A}$



## Configuration code TA45

Type	Configuration code TA45									
EF11-A B T W F 1 5 0 C 0 - 0 0 0 - 1 1 1 - 0 0 0										




- Circuit Breaker of Equipment
- 2-pole, rocker actuated
- Quick connect terminal

Other types on request

## Without release: code C0

## Undervoltage release



## Remote trip release

Code	Rated voltage $U_n$
•	240 V AC
•	230 V AC
•	120 V AC

## Rated current circuit breaker of equipment


$I_n$	Code	$I_n$	Code	$I_n$	Code	$I_n$	Code
10,0	100	13,0	130	16,0	160	19,0	190
11,0	110	14,0	140	17,0	170	20,0	200
12,0	120	15,0	150	18,0	180		

Other rated currents on request

## Rocker legend

Surface	Illustration	Colour of print
F embossed	— O	
H printed	ON OFF	white
K printed	ON OFF	black
L printed	— O	white
M printed	— O	black
P printed	I O	white
R printed	I O	black

Position of the rocker legend e.g F




## Colours

Switch front		Rocker	
W black		white	—
B black		black	—
6 black		—	orange transp.

## Diagram

Thermal overload protection




Without illumination

With illumination 220...240 V  
110...120 V

ABT	ABD
A12 A14	A32 A34

Configuration code (Order example)



**Optional Variants**

0 without V-Lock notch  
9 with V-Lock notch

**Colour**

0 black

**Mounting**

0 Screw mounting  
2 Snap-in mounting s = 1.5  
3 Snap-in mounting s = 2.0  
4 Snap-in mounting s = 2.5

**Terminal PE**

1 Quick-connect terminals 6.3x0.8mm

**Terminal N**

1 Quick-connect terminals 6.3x0.8mm, without connection to TA45  
3 connection to TA45 non insulated

**Terminal L**

1 Quick-connect terminals 6.3x0.8mm, without connection to TA45  
3 connection to TA45 non insulated

## Variants

Rated Current [A]	Rocker colour	Circuit Breakers		Connectors					Internally wired	Order Number
		Illumination	Add-on modules	Mounting	Panel Thickness [mm]	Protection Class	V-Lock			
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.0022.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.0035.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.0035.0012.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.0470.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.0572.0012.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.0699.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.0885.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.1089.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.1089.0013.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.1682.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.1894.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.2078.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.2196.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.2196.0013.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.2405.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.2561.0010.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.2561.0012.01	
16	-	non-illuminated or illuminated	Optional with under-voltage- or remote trip release	Screw	-	I	●	●	EF11.3197.0010.01	


Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

## Packaging unit

16 Pcs

## Accessories

### Description



**Assorted Covers**  
 Rear Cover

0859.0109



**RC320**  
 Rear Cover for Power Entry Module



**Cord retaining kits**  
 Cord retaining strain relief

Flat head, H

4700.0008

## Mating Outlets/Connectors

### Category / Description

#### Connector Overview complete



4795, Mounting: Power Cord, Cable Connector: IEC C19

4795

4790, Mounting: Power Cord, Screw Connector: IEC C19

4790

0104U, Mounting: Power Supply Cord, Screw clamps Connector: IEC C19

0104U

#### Power Supply Cord Overview complete



Cord Sets 10 A, North America, 3.0 m, Connector IEC C13, SJT 3x18 AWG, Transparent

4300.0920

Cord Sets 16 A, Europlug, 2.5 m, Connector IEC C19, H05VV-F3G1.5, black

6004.0395

Cord Sets 16 A, Interconnection, 1.0 m, Connector IEC C19, H05VV-F3G1.5, black

6020.0392

Cord Sets 16 A, Interconnection, 2.0 m, Connector IEC C19, H05VV-F3G1.5, black

6020.0394

Cord Sets 16 A, North America, 2.5 m, Connector IEC C19, SJT 3x14 AWG, black

6009.5195

## Mating Outlets/Connectors shuttered

#### Power Cord Overview complete



VAC19KS, Overview, V-Lock cord retaining, diverse Connector IEC C19, diverse, black

VAC19KS