


PME295/P295, Film, Metallized Paper, Safety, 3300 pF, 20%, 440 VAC (Y1) (ENECA), 480 VAC (UL, cUL), 1500 VDC, 115°C, Lead Spacing = 15mm



Dimensions	
L	18mm MAX
H	14.5mm MAX
T	7.5mm MAX
S	15mm +/-0.4mm
LL	30mm +5mm
F	0.8mm +/-0.05mm
G	0.5mm NOM

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	400

General Information	
<b>Series:</b>	PME295/P295
<b>Dielectric:</b>	Metallized Paper
<b>Style:</b>	Radial
<b>Features:</b>	EMI Safety
<b>RoHS:</b>	Yes
<b>Lead:</b>	Wire Leads
<b>Safety Class:</b>	Y1
<b>Qualifications:</b>	ENECA, UL, cUL, CQC
<b>AEC-Q200:</b>	No
<b>THB Performance:</b>	No
<b>Component Weight:</b>	2.7 g
<b>Miscellaneous:</b>	SRF= 27 MHz.

Specifications	
<b>Capacitance:</b>	3300 pF
<b>Capacitance Tolerance:</b>	20%
<b>Voltage AC:</b>	440 VAC (Y1) (ENECA), 480 VAC (UL, cUL)
<b>Voltage DC:</b>	1500 VDC
<b>Temperature Range:</b>	-40/+115°C
<b>Rated Temperature:</b>	115°C
<b>Dissipation Factor:</b>	1.3% 1kHz
<b>Insulation Resistance:</b>	12 GOhms
<b>Max dV/dt:</b>	2000 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.