

SPECIFICATIONS

MODEL	FSP059-7S2AC8	FSP147-7S5AC8	FSP235-7S8AC18
	XLR, FUANGEE5525		
OUTPUT			
Output Voltage (Typ.) Note.1	29.4 V	29.4 V	29.4 V
Continuous Output Current (Typ.)	2.0 A	5.0 A	8.0 A
Rated Power	59 W	147 W	235 W
LED Indicator	Charging(CC) : RED	Floating charging(CV) : GREEN	
INPUT			
AC inlet	IEC320-C8		IEC320-C18
Voltage Range	90 ~ 264 Vac		
Frequency Range	47~63Hz		
Power Factor(Typ.)	NA	PF>0.95/115VAC, PF>0.9/230VAC at full load	PF>0.95/115VAC, PF>0.9/230VAC at full load
Efficiency(Typ.)	87%	90%	90%
Leakage Current(max.)	0.25mA / 254VAC		
PROTECTION			
Overload	95%~105% rated output power Protection type: Constant current limiting recovers automatically after fault condition is removed		
Short Circuit	Protection type: Hiccup mode, recovers automatically after fault condition is removed		
Over Voltage	Protection type: Shut down o/p voltage, AC reset to recover		
Over Temperature	110°C±10°C detect on inside ambient temperature Protection type: Shut down o/p voltage, AC reset to recover		
SAFETY & EMC			
Safety Standards	UL1012/CSA107.1, IEC60335-1/2-29		
Withstand Voltage	I/P-O/P : 3KVAC		
Isolation Resistance	I/P-O/P : 100M Ohms / 500VDC /25°C/70%RH		
EMC Emission	Compliance to EN55014-1, FCC PART 15/ CISPR14-1, EN/EN61000-3-2,3		
EMC Immunity	Compliance to EN61000-4-2,3,4,5,6,11		
ENVIRONMENTAL			
Operating Temperature	0~40°C		
Operating Humidity	20%~90% RH non-condensing		
Storage Temp.,Humidity	-40~+85%, 10~95% RH		
Vibration	Operating Temperature		
MECHANICAL			
Outline	Fully enclosed plastic case		
Dimensions	128 x 67 x 32 mm	177 x 86 x 32 mm	177 x 86 x 32 mm
Weight(Typ.)	300 g	560 g	680 g
Cooling	Free Air Convection		

NOTES:

1. Modification for charger specification may be required for different battery specification. Please contact battery vendor and FSP for details.
2. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.

CHARGING CURVE