



Quality Products. Service Excellence.

Hole Plugs *HP Series*



Features

- Designed to seal unused pushbutton holes, conduit openings and knockout holes against dust, oil and water.
- Standard Pushbutton size is 30.5mm; Mini Pushbutton size is 22.5mm
- **Steel Hole Plug**
 - Available in 12 sizes.
 - Finished in 2 color options - ANSI 61 gray or RAL7035 Light Gray
 - Oil resistant gasket.
 - Secured with an 10-24 x 0.55" threaded stud and plated wing nut.
- **Stainless Steel Hole Plugs**
 - Available in 8 sizes.
 - Finished in brushed natural 304 stainless steel finish.
 - Oil resistant gasket.
 - Secured with an 10-24 x 0.55" threaded stud and plated wing nut.

Steel

| ANSI 61 Gray | RAL7035 Lt Gray | | | |
|-----------------|--------------------|-------------------------|----------------------|------------------|
| Part No. | Part No. | Description | Max Hole Diameter | Plug Diameter |
| HP22 | HP22LG | 22mm Mini Pushbutton | 0.88 | 1.22 |
| HP50 | HP50LG | .5" Conduit | 0.88 | 1.38 |
| HP75 | HP75LG | .75" Conduit | 1.06 | 1.56 |
| HPB | HPBLG | Std. Pushbutton | 1.25 | 1.75 |
| HP100 | HP100LG | 1" Conduit | 1.38 | 1.88 |
| HP125 | HP125LG | 1.25" Conduit | 1.69 | 2.19 |
| HP150 | HP150LG | 1.5" Conduit | 2.00 | 2.50 |
| HP200 | HP200LG | 2" Conduit | 2.50 | 3.00 |
| HP250 | HP250LG | 2.5" Conduit | 3.00 | 3.50 |
| HP300 | HP300LG | 3" Conduit | 3.62 | 4.12 |
| HP350 | HP350LG | 3.5" Conduit | 4.12 | 4.62 |
| HP400 | HP400LG | 4" Conduit | 4.62 | 5.12 |

Stainless Steel

| Part No. | Description | Max Hole Diameter | Plug Diameter |
|----------|-----------------|-------------------|---------------|
| HP22SS | 22mm Pushbutton | 0.88 | 1.22 |
| HP50SS | .5" Conduit | 0.88 | 1.38 |
| HP75SS | .75" Conduit | 1.06 | 1.56 |
| HPBSS | Std. Pushbutton | 1.25 | 1.75 |
| HP100SS | 1" Conduit | 1.38 | 1.88 |
| HP125SS | 1.25" Conduit | 1.69 | 2.19 |
| HP150SS | 1.5" Conduit | 2.00 | 2.50 |
| HP200SS | 2" Conduit | 2.50 | 3.00 |

© 2022. Hammond Manufacturing Ltd. All rights reserved.