

## Specification Sheet

Part Number: T120R0HSK2



Heat stabilized heavy-duty cable ties provide excellent resistance to high heat exposures.

Head design provides high tensile strength with very low insertion force.

Bent tail ensures a quick and simple installation.

High-Temp Cable Tie, 15" Long, UL Rated, 120lb Tensile Strength, PA66HS, Black, 50/pkg

|                |           |
|----------------|-----------|
| Article Number | 111-12061 |
|----------------|-----------|

|      |       |
|------|-------|
| Type | T120R |
|------|-------|

|       |            |
|-------|------------|
| Color | Black (BK) |
|-------|------------|

|              |     |
|--------------|-----|
| Quantity Per | bag |
|--------------|-----|

|                     |                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                        |
|-------------------|----------------------------------------------------------------------------------------|
| Short Description | High-Temp Cable Tie, 15" Long, UL Rated, 120lb Tensile Strength, PA66HS, Black, 50/pkg |
|-------------------|----------------------------------------------------------------------------------------|

|                         |                 |
|-------------------------|-----------------|
| <b>Global Part Name</b> | T120R-PA66HS-BK |
|-------------------------|-----------------|

|                                            |       |
|--------------------------------------------|-------|
| <b>Minimum Tensile Strength (Imperial)</b> | 120.0 |
|--------------------------------------------|-------|

|                                          |       |
|------------------------------------------|-------|
| <b>Minimum Tensile Strength (Metric)</b> | 535.0 |
|------------------------------------------|-------|

|                            |      |
|----------------------------|------|
| <b>Length L (Imperial)</b> | 15.0 |
|----------------------------|------|

|                          |       |
|--------------------------|-------|
| <b>Length L (Metric)</b> | 387.0 |
|--------------------------|-------|

|                                      |      |
|--------------------------------------|------|
| <b>Identification Plate Position</b> | none |
|--------------------------------------|------|

|                           |    |
|---------------------------|----|
| <b>Releasable Closure</b> | No |
|---------------------------|----|

|                    |              |
|--------------------|--------------|
| <b>Tie Closure</b> | plastic pawl |
|--------------------|--------------|

|                |                 |
|----------------|-----------------|
| <b>Variant</b> | Inside Serrated |
|----------------|-----------------|

|                           |      |
|---------------------------|------|
| <b>Width W (Imperial)</b> | 0.30 |
|---------------------------|------|

|                         |     |
|-------------------------|-----|
| <b>Width W (Metric)</b> | 7.6 |
|-------------------------|-----|

|                                       |      |
|---------------------------------------|------|
| <b>Bundle Diameter Min (Imperial)</b> | 0.20 |
|---------------------------------------|------|

|                                     |     |
|-------------------------------------|-----|
| <b>Bundle Diameter Min (Metric)</b> | 5.0 |
|-------------------------------------|-----|

|                                       |      |
|---------------------------------------|------|
| <b>Bundle Diameter Max (Imperial)</b> | 4.13 |
|---------------------------------------|------|

|                                     |       |
|-------------------------------------|-------|
| <b>Bundle Diameter Max (Metric)</b> | 105.0 |
|-------------------------------------|-------|

|                                      |                                        |
|--------------------------------------|----------------------------------------|
| <b>Material</b>                      | Polyamide 6.6 heat stabilized (PA66HS) |
| <b>Material Shortcut</b>             | PA66HS                                 |
| <b>Flammability</b>                  | UL 94 V-2                              |
| <b>Halogen Free</b>                  | Yes                                    |
| <b>Operating Temperature</b>         | -40°F to +257°F (-40°C to +125°C)      |
| <b>ROHS Compliant</b>                | Yes                                    |
| <b>Certification/Specification</b>   | UL-ZODZ2.E64139 VG U48/04103           |
| <b>UL Recognized (US)</b>            | Yes                                    |
| <b>UL Listed (US and Canada)</b>     | Yes                                    |
| <b>UL Recognized (US and Canada)</b> | Yes                                    |
| <b>UL Listed (US)</b>                | Yes                                    |
| <b>Package Quantity (Imperial)</b>   | 50                                     |
| <b>Package Quantity (Metric)</b>     | 50                                     |
| <b>Customs Number</b>                | 3926909988                             |

