

Specification Sheet

Part Number: T30XL0C2



Engineered and manufactured for maximum performance and quality. Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Bent tail allows for simpler insertion.

Cable Tie, 14" Long, UL Rated, 30lb Tensile Strength, PA66, Black, 100/pkg

Article Number	111-02901
Type	T30XL
Color	Black (BK)
Quantity Per	bag
Product Description	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Cable Tie, 14" Long, UL Rated, 30lb Tensile Strength, PA66, Black, 100/pkg

Global Part Name	T30XL-PA66-BK
-------------------------	---------------

Minimum Tensile Strength (Imperial)	30.0
--	------

Minimum Tensile Strength (Metric)	135.0
--	-------

Length L (Imperial)	14.0
----------------------------	------

Length L (Metric)	365.0
--------------------------	-------

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	No
---------------------------	----

Tie Closure	plastic pawl
--------------------	--------------

Variant	Inside Serrated
----------------	-----------------

Width W (Imperial)	0.14
---------------------------	------

Width W (Metric)	3.6
-------------------------	-----

Bundle Diameter Min (Imperial)	0.06
---------------------------------------	------

Bundle Diameter Min (Metric)	1.5
-------------------------------------	-----

Bundle Diameter Max (Imperial)	4.13
---------------------------------------	------

Bundle Diameter Max (Metric)	105.0
-------------------------------------	-------

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
UL Recognized (US)	Yes
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

