

Specification Sheet

Part Number: REZ300.NB3P



The unique, patented head design enables the tie to be inserted through a standard style head for permanent locking or can be twisted into the pinch-releasable style head for easy opening at a later time. The quick pinch-release mechanism can be released by one hand even when the tie is under tension.

Releasable Cable Tie, 12" Long, 30 lb Tensile Strength, PA66, Black, 100/pkg

Article Number	115-40300
Type	REZ300
Color	Black (BK)
Quantity Per	bag
Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Releasable Cable Tie, 12" Long, 30 lb Tensile Strength, PA66, Black, 100/pkg

Global Part Name	REZ300-PA66-BK
-------------------------	----------------

Minimum Tensile Strength (Imperial)	30.0
--	------

Minimum Tensile Strength (Metric)	135
--	-----

Length L (Imperial)	12.0
----------------------------	------

Length L (Metric)	305
--------------------------	-----

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	Yes
---------------------------	-----

Tie Closure	plastic pawl
--------------------	--------------

Variant	Inside Serrated
----------------	-----------------

Width W (Imperial)	0.19
---------------------------	------

Width W (Metric)	4.7
-------------------------	-----

Bundle Diameter Min (Imperial)	0.63
---------------------------------------	------

Bundle Diameter Min (Metric)	16.0
-------------------------------------	------

Bundle Diameter Max (Imperial)	3.2
---------------------------------------	-----

Bundle Diameter Max (Metric)	80.0
-------------------------------------	------

Thickness T (Imperial)	0.055
-------------------------------	-------

Thickness T (Metric)	1.4
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988