




Quality Products. Service Excellence.

Vertical Rack Cable Manager with Door **RB-VCM Series**

For use with Open Frame Racks



RACK BASICS®



Vertical cable managers facilitate cable organization for a single or multiple rack installation. The RB-VCM is cost-effective and includes a number of unique features to save you installation time.

Features

- Manager body and door are constructed of 16-gauge steel.
- All-steel construction with side and rear cut-outs for cable pass-through.
- Includes cable mounting lances for hook and loop cable organization.
- Mounts to either side of the open-frame rack (includes mounting hardware).
- The attached hinged door opens to one side and secures closed with two (2) small strips of the magnet.
- Horizontal stabilizers easily swing away for cable installation and swing back for structural support.
- Separated space easily allows for cables to be added or removed without fishing the cable.
- Manager and door finished in textured RAL9005 black powder paint finish.
- TAA-compliant for GSA Schedule purchases.
- RoHS and REACH compliant.
- Manufactured in North America.

Compatibility

- Designed specifically for the RB-2P but also compatible with:
- DRZ477
- DNRR**HDW Series
- DC4R Series
- RB-2PA Series

Looking for a Finger Manager?

- Single-Sided Vertical Finger Manager - **FRCM Series**
- Double-Sided Vertical Finger Manager - **VFM Series**

Part of the Rack Basics® line of economy rack solutions.

Accessories

- Vertical Cable Manager Extensions
- Hook and Loop Roll



Part No.	Overall Dimensions (Inches)			Mounting Dimensions		Door Included	Similar Size Part No.
	Height	Width	Depth	Units	Rack Units		
RB-VCM24	47.00	6.00	5.00	42.00	24	Yes	
RB-VCM44	82.00	6.00	5.00	77.00	44	Yes	RRCM44UD
RB-VCM48	89.00	6.00	5.00	85.00	48	Yes	RRCM48UD

Estimated Cable Fill Capacities

Part No.	Description	Opening Quantity	Recommended Cable Fill (50% Fill Ratio)		Maximum Cable Fill (100% Fill Ratio)	
			Cat 6	Cat 6a	Cat 6	Cat 6a
RB-VCM44	Channel Opening	1	149	103	297	207
	Side Opening	2 x 19 = 38	31	21	61	42
	Rear Pass Through	10	28	19	55	38
RB-VCM48	Channel Opening	1	149	103	297	207
	Side Opening	2 x 21 = 42	31	21	61	42
	Rear Pass Through	11	28	19	55	38

Data subject to change without notice

