


Dual 1 Form A/B, C Solid-State Relay



FEATURES

- Current limit protection
- Isolation test voltage 3750 V_{RMS}
- Typical R_{ON} 10 Ω
- Load voltage 200 V
- Load current 200 mA
- High surge capability
- Clean bounce free switching
- Low power consumption
- SMD lead available on tape and reel
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

APPLICATIONS

- General telecom switching
 - On / off hook control
 - Ring delay
 - Dial pulse
 - Ground start
 - Ground fault protection
- Instrumentation
- Industrial controls

LINKS TO ADDITIONAL RESOURCES



DESCRIPTION

The LH1512 relays contain normally open and normally closed switches that can be used independently as a 1 form A and 1 form B relay, or when used together, as a 1 form C relay. The relays are constructed as a mult.-chip hybrid device. Actuation control is via an infrared LED. The output switch is a combination of a photodiode array with MOSFET switches and control circuitry.

AGENCY APPROVALS

- [UL](#)
- [VDE](#)
- [CQC](#)
- [FIMKO](#)

| ORDERING INFORMATION | |
|--|---|
| <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; padding: 2px;">L</div> <div style="border: 1px solid black; padding: 2px;">H</div> <div style="border: 1px solid black; padding: 2px;">1</div> <div style="border: 1px solid black; padding: 2px;">5</div> <div style="border: 1px solid black; padding: 2px;">1</div> <div style="border: 1px solid black; padding: 2px;">2</div> <div style="border: 1px solid black; padding: 2px;">B</div> <div style="border: 1px solid black; padding: 2px;">#</div> <div style="border: 1px solid black; padding: 2px;">#</div> <div style="border: 1px solid black; padding: 2px;">T</div> <div style="border: 1px solid black; padding: 2px;">R</div> </div> <p style="text-align: center;"> PART NUMBER ELECTR. VARIATION PACKAGE CONFIG. TAPE AND REEL </p> | <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <small>DIP</small> <small>7.62 mm</small> </div> <div style="text-align: center;"> <small>SMD</small> <small>> 0.1 mm</small> </div> </div> |
| PACKAGE | UL, CSA, FIMKO |
| SMD-8, tubes | LH1512BAC |
| SMD-8, tape and reel | LH1512BACTR |
| DIP-8, tubes | LH1512BB |



| ABSOLUTE MAXIMUM RATINGS (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|--|--|-------------------|-------------|------------------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| INPUT | | | | |
| LED continuous forward current | | I _F | 50 | mA |
| LED reverse voltage | I _R ≤ 10 μA | V _R | 5 | V |
| OUTPUT | | | | |
| DC or peak AC load voltage | I _L ≤ 50 μA | V _L | 200 | V |
| Continuous DC load current (form C operation) | | I _L | 200 | mA |
| Peak load current, form A | t = 100 ms | I _P | (2) | |
| Peak load current (single shot), form B | | I _P | 400 | mA |
| SSR | | | | |
| Ambient operating temperature range | | T _{amb} | -40 to +85 | °C |
| Storage temperature range | | T _{stg} | -40 to +125 | °C |
| Pin soldering temperature (3) | t = 10 s max. | T _{sld} | 260 | °C |
| Input to output isolation test voltage | t = 1 s, I _{ISO} = 10 μA max. | V _{ISO} | 3750 | V _{RMS} |
| Pole-to-pole isolation voltage (S1 to S2) (1) (dry air, dust free, at sea level) | | | 1600 | V |
| Output power dissipation (continuous) | | P _{diss} | 600 | mW |

Notes

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability
- (1) Breakdown occurs between the output pins external to the package
- (2) Refer to current limit performance application note for a discussion on relay operation during transient currents
- (3) Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP)

| ELECTRICAL CHARACTERISTICS (T _{amb} = 25 °C, unless otherwise specified) | | | | | | | |
|---|--|-------------------|------|------|------|------|--|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT | |
| INPUT | | | | | | | |
| LED forward current switch turn-on (NO) | I _L = 100 mA, t = 10 ms | I _{Fon} | - | 0.6 | 2 | mA | |
| LED forward current switch turn-off (NO) | V _L = ± 150 V | I _{Foff} | 0.2 | 0.5 | - | mA | |
| LED forward current switch turn-on (NC) | I _L = 100 mA, t = 10 ms | I _{Fon} | 0.2 | 0.9 | - | mA | |
| LED forward current switch turn-off (NC) | V _L = ± 150 V | I _{Foff} | - | 1 | 2 | mA | |
| LED forward voltage | I _F = 10 mA | V _F | 1.15 | 1.26 | 1.45 | V | |
| OUTPUT | | | | | | | |
| On-resistance: (NO, NC) | I _F = 5 mA (NO), I _F = 0 (NC), I _L = 50 mA (NC) | R _{ON} | - | 10 | 15 | Ω | |
| Off-resistance: (NO) | I _F = 0 mA, V _L = ± 100 V | R _{OFF} | 0.35 | 5000 | - | GΩ | |
| Off-resistance: (NC) | I _F = 5 mA, V _L = ± 100 V | R _{OFF} | 0.1 | 1.4 | - | GΩ | |
| Current limit: (NO) | I _F = 5 mA, t = 5 ms, V _L = ± 5 V | I _{LMT} | 270 | 360 | 460 | mA | |
| Off-state leakage current: (NO) | I _F = 0 mA, V _L = ± 100 V | I _O | - | 0.02 | 1000 | nA | |
| Off-state leakage current: (NC) | I _F = 5 mA, V _L = ± 100 V | I _O | - | 0.07 | 1 | μA | |
| Off-state leakage current: (NO, NC) | I _F = 0 mA (NO), I _F = 5 mA, V _L = ± 200 V | I _O | - | | 1 | μA | |
| Output capacitance: (NO) | I _F = 0 mA, V _L = 50 V | C _O | - | 60 | - | pF | |
| Output capacitance: (NC) | I _F = 5 mA, V _L = 50 V | C _O | - | 60 | - | pF | |
| TRANSFER | | | | | | | |
| Capacitance (input to output) | V _{ISO} = 1 V | C _{IO} | - | 3 | - | pF | |

Note

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements

| SWITCHING CHARACTERISTICS (T _{amb} = 25 °C, unless otherwise specified) | | | | | | | |
|--|--|------------------|------|------|------|------|--|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT | |
| Turn-on time (NO) | I _F = 10 mA, I _L = 50 mA | t _{on} | - | 1.4 | 3 | ms | |
| Turn-on time (NC) | I _F = 10 mA, I _L = 50 mA | t _{on} | - | 1.2 | 3 | ms | |
| Turn-off time (NO) | I _F = 10 mA, I _L = 50 mA | t _{off} | - | 0.7 | 3 | ms | |
| Turn-off time (NC) | I _F = 10 mA, I _L = 50 mA | t _{off} | - | 2 | 3 | ms | |



TYPICAL CHARACTERISTICS (T_{amb} = 25 °C, unless otherwise specified)




Fig. 1 - Maximum Load Current vs. Ambient Temperature




Fig. 4 - Typical Leakage vs. Temperature (Measured across Pin 5 and 6 or 7 and 8)




Fig. 2 - Form A Typical Load Current vs. Temperature




Fig. 5 - Form B Typical Load Current vs. Temperature




Fig. 3 - Form A Typical Load Current vs. Load Voltage




Fig. 6 - Typical LED Forward Voltage Drop vs. Temperature




Fig. 7 - Form A Typical Blocking Voltage vs. Temperature




Fig. 10 - Form B Typical Blocking Voltage vs. Temperature




Fig. 8 - Form A Typical Turn-On vs. Temperature




Fig. 11 - Form B Typical Turn-On vs. Temperature




Fig. 9 - Form A Typical Turn-Off vs. Temperature




Fig. 12 - Form B Typical Turn-Off vs. Temperature




Fig. 13 - Form A Typical Turn-On vs. LED Forward Current




Fig. 16 - Form B Typical Turn-On vs. LED Forward Current




Fig. 14 - Form A Typical Turn-Off vs. LED Forward Current




Fig. 17 - Form B Typical Turn-Off vs. LED Forward Current




Fig. 15 - Form A Typical On-Resistance vs. Temperature






Fig. 18 - Form B Typical On-Resistance vs. Temperature



ilh1512bb_19

Temperature (°C)


Fig. 19 - Form A Typical I_F for Switch Operation vs. Temperature



ilh1512bb_21

Temperature (°C)


Fig. 21 - Form B Typical I_F for Switch Operation vs. Temperature



ilh1512bb_20

Temperature (°C)

Fig. 20 - Form A Typical I_F for Switch Dropout vs. Temperature



ilh1512bb_22


Temperature (°C)

Fig. 22 - Form B Typical I_F for Switch Dropout vs. Temperature




PACKAGE DIMENSIONS in millimeters


DIP



SMD




PACKAGE MARKING (example)



Note


- Tape and reel suffix (TR) is not part of the package marking

SOLDER PROFILES



948626

Fig. 23 - Wave Soldering Double Wave Profile According to J-STD-020 for DIP Devices



19841

Fig. 24 - Lead (Pb)-free Reflow Solder Profile According to J-STD-020 for SMD Devices

HANDLING AND STORAGE CONDITIONS

ESD level: HBM class 2

Floor life: unlimited

Conditions: $T_{amb} < 30\text{ °C}$, RH < 85 %

Moisture sensitivity level 1, according to J-STD-020



Footprint and Schematic Information for LH1512BAC, LH1512BACTR, LH1512BB

The footprint and schematic symbols for the following parts can be accessed using the associated links. They are available in Eagle, Altium, KiCad, OrCAD / Allegro, Pulsonix, and PADS.

Note that the 3D models for these parts can be found on the Vishay product page.

| PART NUMBER | FOOTPRINT / SCHEMATIC |
|-------------|--|
| LH1512BAC | www.snapeda.com/parts/LH1512BAC/Vishay/view-part |
| LH1512BACTR | www.snapeda.com/parts/LH1512BACTR/Vishay/view-part |
| LH1512BB | www.snapeda.com/parts/LH1512BB/Vishay/view-part |

For technical issues and product support, please contact optocoupleranswers@vishay.com.

DIP



SMD



i179034_2



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.