AD-383u7 NEL

Overview

Frequency Band UHF 860 - 960 MHz

Chip NXP UCODE 7

Antenna Dimensions 30 x 50 mm / 1.18 x 1.97 in

International Standard ISO/IEC 18000-63 Type C

Industry Segments Apparel Logistics

Applications
Supply Chain Management
Home Essentials
Brand Protection

RoHs EU Directive 2011/65/EU and 2015/863 Compliant



Superior read range on a wide range of dielectrics

AD-383u7 NEL from Avery Dennison is a high performing inlay suitable for a wide variety of RFID tagging applications. The product features the UCODE 7 chip by NXP.

The Gen2 UHF RFID inlay perfectly integrates with a wide variety of RFID tagging applications, including supply chain, inventory & logistics, apparel and home essentials.

AD-383u7 is equipped with the UCODE 7 IC from NXP, featuring 128-bit of EPC memory and 96-bit TID memory, pre-encoded for multi-vendor chip (MCS) based serialization. The product is also available in wide-edge leading format. Delivery formats include Dry Inlay, Wet Inlay and Pressure Sensitive Label.

Like all RFID products from Avery Dennison, AD-383u7 NEL inlays are manufactured according to the industry's highest quality standards, as confirmed by the RFID Lab at Auburn University: The inspection body awarded Avery Dennison its first comprehensive and significant ARC accreditation for quality.



Technical features

Chip	NXP UCODE 7			
EPC and User Memory	128-bit and n/a			
TID Memory	96-bit / 48-bit unique serial numbe	96-bit / 48-bit unique serial number		
Product Code	RF600459	RF600460		
Delivery Format	Dry inlay	Wet inlay		
Die-cut Dimension	-	34 x 54 mm / 1.34 x 2.13 in		
Inlay Substrate	PET			
Total Thickness	10 - 12 mils / 261 - 312 microns	12 - 14 mils / 300 - 350 microns		
Standard Pitch	63.5 mm / 2.5 in			
Web Width	38 mm / 2 in			
Core Size	76 mm / 3 in			
Quantity / Reel	15000 pcs / reel	7500 pcs / reel		
Operating	-40 °C to 85 °C			
Temperature	-40 °F to 185 °F			
On-Metal	Non metal			
Certificate	ARC			


Contact information

rfid.averydennison.com/contact

North America: +1-866-903-7343 (toll free US)

International: +1-678-617-2359

RoHS



 $\textbf{Warranty:} \ \mathsf{Please} \ \mathsf{refer} \ \mathsf{to} \ \mathsf{Avery} \ \mathsf{Dennison} \ \mathsf{standard} \ \mathsf{terms} \ \mathsf{and} \ \mathsf{conditions:} \ \textbf{rfid.averydennison.com/terms} \ \mathsf{andconditions:} \ \mathsf{rfid.averydennison.com/terms} \ \mathsf{andconditions:} \ \mathsf{rfid.averydennison.com/terms} \ \mathsf{andconditions:} \ \mathsf{rfid.averydennison.com/terms} \ \mathsf{andconditions:} \ \mathsf{averydennison.com/terms} \ \mathsf{averydennison.com/terms } \ \mathsf{averydennison.com/terms} \ \mathsf{averydennison.com/terms } \ \mathsf{avery$

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.





AD-383u7 WEL

Overview

Frequency Band UHF 860 - 960 MHz

Chip NXP UCODE 7

Antenna Dimensions 50 x 30 mm / 1.97 x 1.18 in

International Standard ISO/IEC 18000-63 Type C

Industry Segments Apparel Logistics

Applications
Supply Chain Management
Home Essentials
Brand Protection

RoHs EU Directive 2011/65/EU and 2015/863 Compliant



Superior read range on a wide range of dielectrics

AD-383u7 from Avery Dennison is a high performing inlay suitable for a wide variety of RFID tagging applications. The product features the UCODE 7 chip by NXP.

The Gen2 UHF RFID inlay perfectly integrates with a wide variety of RFID tagging applications, including supply chain, inventory & logistics, apparel and home essentials.

AD-383u7 is equipped with the UCODE 7 IC from NXP, featuring 128-bit of EPC memory and 96-bit TID memory, pre-encoded for multi-vendor chip (MCS) based serialization. The product is also available in a narrow-edge leading format. Delivery formats include Dry Inlay, Wet Inlay and Pressure Sensitive Label.

Like all RFID products from Avery Dennison, AD-383u7 inlays are manufactured according to the industry's highest quality standards, as confirmed by the RFID Lab at Auburn University: The inspection body awarded Avery Dennison its first comprehensive and significant ARC accreditation for quality.



Technical features

Chip	NXP UCODE 7		
EPC and User Memory	128-bit and n/a		
TID Memory	96-bit		
Product Code	RF600527	RF600465	RF100350
Delivery Format	Dry inlay	Wet inlay	Label / sticker
Die-cut Dimension	-	54 x 34 mm / 2.13 x 1.34 in	57 x 38 mm / 2.25 x 1.50 in
Inlay Substrate	PET		
Face Sheet	-	-	Π2C (FASSON®) Bright White
Total Thickness	9 - 11 mils / 229 - 279 microns	10 - 12 mils / 254 - 305 microns	15 - 17 mils / 389 - 439 microns
Standard Pitch	38.1 mm / 1.5 in	38.1 mm / 1.5 in	50.8 mm / 2 in
Web Width	54 mm / 2 in	58 mm / 2 in	61.2 mm / 2 in
Core Size	76 mm / 3 in		
Quantity / Reel	15000 pcs/reel	10000 pcs / reel	2489 pcs / reel
Operating	-40 °C to 85 °C		
Temperature	-40 °F to 185 °F		
On-Metal	Non metal		
Certificate	ARC		


Contact information

rfid.averydennison.com/contact

North America: +1-866-903-7343 (toll free US)

International: +1-678-617-2359

RoHS



 $\textbf{Warranty:} \ \mathsf{Please} \ \mathsf{refer} \ \mathsf{to} \ \mathsf{Avery} \ \mathsf{Dennison} \ \mathsf{standard} \ \mathsf{terms} \ \mathsf{and} \ \mathsf{conditions:} \ \textbf{rfid.averydennison.com/terms} \ \mathsf{andconditions:} \ \mathsf{rfid.averydennison.com/terms} \ \mathsf{andconditions:} \ \mathsf{rfid.averydennison.com/terms} \ \mathsf{andconditions:} \ \mathsf{rfid.averydennison.com/terms} \ \mathsf{andconditions:} \ \mathsf{averydennison.com/terms} \ \mathsf{averydennison.com/terms } \ \mathsf{averydennison.com/terms} \ \mathsf{averydennison.com/terms } \ \mathsf{avery$

Care and handling: RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics / RFID to keep environmental impact and static charge to a minimum.



Applications: This product should be tested by the customer / user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use. Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.