, Cable, Plug, 5.5 mm, 2-pole, DC Plug/Socket



#### See below:

## **Approvals and Compliances**

# Description - pre-assembled cable

- Low Voltage DC Plug and Socket
- DC Plug: 2-pole , straight

#### Weblinks

pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product

Technical Data		
Diameter	5.5 mm / 3.3 mm / 1.0 mm	
Number of Poles	2-pole	
Ratings DC	2A / 13.5VDC	
Dielectric Strength	500 VDC	
Insulation Resistance	> 100 MΩ @ 500 VDC	

Allowable Operation Temperature	-20°C to 70°C
Terminal	Cable
Cord Lenght	1.8 m
Cable Cross Section	2 x 0.3 mm <sup>2</sup>
Style	straight
Lifetime	5000 Insertions

## **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals


SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

## Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
RoHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
<b>50</b>	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

## Dimensions [mm]



# **All Variants**

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DC Plug/Socket	5.5	2-pole	Cable	4840.5220

kaging	

200 Pcs

## **Mating Outlets/Connectors**

Category / Description



DC Plugs / Sockets Overview complete

4840.2220 , solder terminal, Socket, 5.9 mm, 2-pole, DC Plug/Socket , PCB terminals, Socket, 6.0 mm, 2-pole, DC Plug/Socket 4840.2221

information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each

product selected for their own applications.