

# Han C axial module female 2,5-8mm<sup>2</sup>



Part number	09 14 003 2701
Specification	Han C axial module female 2,5-8mm <sup>2</sup>
HARTING eCatalogue	https://b2b.harting.com/09140032701

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Modules
Series	Han-Modular <sup>®</sup>
Type of module	Han <sup>®</sup> C module

#### Version

Termination method	Axial screw termination
Gender	Female
Number of contacts	3

### Technical characteristics

Conductor cross-section	2.5 8 mm²
Rated current	40 A
Rated voltage	690 V
Rated impulse voltage	8 kV
Pollution degree	3
Rated current acc. to UL	40 A
Rated voltage acc. to UL	600 V
Insulation resistance	>10 <sup>10</sup> Ω
Contact resistance	≤0.3 mΩ
Stripping length	5 mm @ 2.5 mm <sup>2</sup> 5 mm @ 4 mm <sup>2</sup> 8 mm @ 6 mm <sup>2</sup>



#### Technical characteristics

Tightening torque	1.5 Nm @ 2.5 mm <sup>2</sup> 1.5 Nm @ 4 mm <sup>2</sup> 2 Nm @ 6 mm <sup>2</sup>
Limiting temperature	-40 +125 °C
Mating cycles	≥500

#### Material properties

Colour (insert)  RAL 7032 (pebble grey)  Material (contacts)  Copper alloy  Surface (contacts)  Silver plated  Material flammability class acc. to UL 94  V-0  RoHS  RoHS exemptions  6(c): Copper alloy containing up to 4 % lead by weight  ELV status  compliant with exemption  China RoHS  50  REACH Annex XVII substances  Not contained  REACH ANNEX XIV substances  Not contained  REACH SVHC substances  Yes  REACH SVHC substances  Lead  ECHA SCIP number  5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances  Nickel Lead	Material (insert)	Polycarbonate (PC)
Surface (contacts)  Silver plated  Material flammability class acc. to UL 94  V-0  RoHS  compliant with exemption  RoHS exemptions  6(c): Copper alloy containing up to 4 % lead by weight  ELV status  compliant with exemption  China RoHS  50  REACH Annex XVII substances  Not contained  REACH ANNEX XIV substances  Not contained  REACH SVHC substances  Yes  REACH SVHC substances  Lead  ECHA SCIP number  5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances  Nickel	Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94  RoHS  compliant with exemption  RoHS exemptions  6(c): Copper alloy containing up to 4 % lead by weight  ELV status  compliant with exemption  China RoHS  50  REACH Annex XVII substances  Not contained  REACH ANNEX XIV substances  Not contained  REACH SVHC substances  Yes  REACH SVHC substances  Lead  ECHA SCIP number  5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances  Nickel	Material (contacts)	Copper alloy
RoHS compliant with exemption  RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight  ELV status compliant with exemption  China RoHS 50  REACH Annex XVII substances Not contained  REACH ANNEX XIV substances Not contained  REACH SVHC substances Yes  REACH SVHC substances Lead  ECHA SCIP number 5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances  Nickel	Surface (contacts)	Silver plated
RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight  ELV status compliant with exemption  China RoHS 50  REACH Annex XVII substances Not contained  REACH ANNEX XIV substances Not contained  REACH SVHC substances Yes  REACH SVHC substances Lead  ECHA SCIP number 5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances  Nickel	Material flammability class acc. to UL 94	V-0
ELV status compliant with exemption  China RoHS 50  REACH Annex XVII substances Not contained  REACH ANNEX XIV substances Not contained  REACH SVHC substances Yes  REACH SVHC substances Lead  ECHA SCIP number 5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances Yes  California Proposition 65 substances  Nickel	RoHS	compliant with exemption
China RoHS 50  REACH Annex XVII substances Not contained  REACH ANNEX XIV substances Not contained  REACH SVHC substances Yes  REACH SVHC substances Lead  ECHA SCIP number 5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances Yes  Nickel	RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
REACH Annex XVII substances  REACH ANNEX XIV substances  Not contained  REACH SVHC substances  Yes  REACH SVHC substances  Lead  ECHA SCIP number  5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances  Nickel	ELV status	compliant with exemption
REACH ANNEX XIV substances  REACH SVHC substances  REACH SVHC substances  Lead  ECHA SCIP number  5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances  Nickel	China RoHS	50
REACH SVHC substances  REACH SVHC substances  Lead  ECHA SCIP number  5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances  Nickel	REACH Annex XVII substances	Not contained
REACH SVHC substances  ECHA SCIP number  5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances  Nickel	REACH ANNEX XIV substances	Not contained
ECHA SCIP number 5dbb3851-b94e-4e88-97a1-571845975242  California Proposition 65 substances Yes  California Proposition 65 substances  Nickel	REACH SVHC substances	Yes
California Proposition 65 substances  Yes  Nickel	REACH SVHC substances	Lead
California Proposition 65 substances	ECHA SCIP number	5dbb3851-b94e-4e88-97a1-571845975242
California Proposition 65 substances	California Proposition 65 substances	Yes
	California Proposition 65 substances	· · · · · · · · · · · · · · · · · · ·

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 UL 2237 PVVA2.E318390 CSA-C22.2 No. 182.3 PVVA8.E318390

#### Commercial data

Packaging size	2
Net weight	31 g

Product data sheet 09 14 003 2701 Han C axial module female 2,5-8mm²



#### Commercial data

Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440217 Module for industrial connectors (power/signals)