

Power strips used within the patient care vicinity may be permanently attached so that it is only removable with a tool. Choose the PSCLAMP for a safe and secure mounting solution.

## Safe-IT UL 60601-1 Medical-Grade Power Strip for Patient-Care Vicinity, Surge Protection, 4x Hospital-Grade Outlets, 6 ft. Cord

MODEL NUMBER: **SPS406HGULTRA**



Full 60601-1 compliance and agency listing, surge protection, integrated locking safety covers and a 6 ft. cord make this medical-grade power strip ideal for standalone use in areas inside and outside patient-care vicinities.

### Features

**Power Distribution Anywhere in Any Medical Facility** Ideal for standalone use in all patient-care vicinities, therapy rooms, imaging environments, laboratories and administrative areas. 120V, 50/60 Hz power strip complies with UL 60601-1 and UL 60950-1 specifications. Automatic single-fault protection. Tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 Canadian standards. Patent # 7,375,939 & 8,339,759.

**Exclusive Antimicrobial Protection** Antimicrobial coating helps resist the growth of bacteria, viruses, fungi, mold and mildew. Coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

**Versatile Medical-Grade Solution** 4 NEMA 5-15R-HG hospital-grade outlets provide consistent power. 6 ft. power cord with NEMA 5-15P-HG plug provides ample reach to the power source. Rugged all-metal housing for long life in demanding environments.

**Premium Safety Features** 1410 joules of surge suppression protect against dangerous power spikes. Integrated locking outlet safety covers block access to unused outlets. Built-in 15A resettable circuit breaker protects against dangerous overloads. Switchless design prevents accidental shut-off. LED indicates power is present and surge-protected.

**Ready to Use Right Out of the Box** Built-in mounting slots and flanges for easy installation on a variety of surfaces.

### Highlights

- Antimicrobial protection helps prevent the growth of bacteria, viruses, fungi, mold and mildew
- Approved for standalone use in all patient-care vicinities
- Listed to UL 60601-1 and UL 60950-1 specifications
- 1410 joules of surge suppression
- Automatic single-fault detection for added patient protection

### Package Includes

- SPS406HGULTRA UL 60601-1 Medical-Grade Power Strip
- Owner's manual

## Specifications

<b>OVERVIEW</b>	
UPC Code	037332194091
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A 120V
Voltage Compatibility (VAC)	120
Maximum Surge Amps	60000
Input Plug Type	NEMA 5-15P-HG
Input Cord Length (ft.)	6
Right-Angle Plug	No
Input Cord Length (m)	1.83
Integrated Cord Clip	No
<b>OUTPUT</b>	
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(4) 5-15R-HG
Circuit Breaker (amps)	15
Overload Protection	15A resettable circuit breaker
Outlet Orientation	Single row of 4
Right-Angle Outlets	No
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Diagnostic LED(s)	Yes
LED Indicators	Proper wiring and surge protection working
<b>SURGE / NOISE SUPPRESSION</b>	
AC Suppression Joule Rating	1410
Automatic Shut-Off	No
<b>DATALINE SURGE SUPPRESSION</b>	
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
Telephone/DSL Protection	No
<b>PHYSICAL</b>	



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Material of Construction	Metal
Power Cord Color	White
Housing Color	White
Mounting Holes or Slots	Yes
Receptacle Color	White
Shipping Dimensions (hwd / cm)	6.10 x 14.73 x 36.58
Shipping Dimensions (hwd / in.)	2.40 x 5.80 x 14.40
Shipping Weight (kg)	1.18
Shipping Weight (lbs.)	2.60
Unit Dimensions (hwd / in.)	1.5 x 13.75 x 2.5
Unit Dimensions (hwd / cm)	3.8 x 34.9 x 6.4
Unit Weight (lbs.)	3.20
Unit Weight (kg)	1.45
Mounting Details	Includes flanges

#### FEATURES & SPECIFICATIONS

Antimicrobial	Yes
Rotatable Outlets	No
Antibacterial	No

#### STANDARDS & COMPLIANCE

Approvals	TUV tested and Listed to UL 60601-1 and UL 60950-1 (USA); TUV tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 (Canada)
Patented	Patent# 7,375,939; Patent# 8,339,759

#### WARRANTY

Product Warranty Period (Worldwide)	Lifetime limited warranty
-------------------------------------	---------------------------

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>