

1-Port Industrial USB over Cat6 Extender, ESD Protection, PoC - USB 2.0, Mountable, 150 ft. (45.72 m), TAA

MODEL NUMBER: **B203-101-IND**



Industrial-grade transmitter/receiver combo connects your office laptop or PC to a webcam or other USB peripheral up to 150 ft. away.

Features

Industrial-Grade Extender Connects Your Computer to a USB Device up to 150-ft. (45.72 m)

Away This plug-and-play extender kit with heavy-duty all-metal housings is ideal for connecting your office computer's USB-A port to a printer, 1080p webcam, external hard drive or other USB device located up to 150-ft. (45.72 m) (45 meters) away. The B203-101-IND includes a local transmitter and a remote receiver that extends USB 2.0 signals over user-supplied Cat5/6 cabling (such as Tripp Lite's N202-Series Cat6 Ethernet cables).

Protects Your Devices against Electrostatic Discharge (ESD) Machines on the shop floor can generate electrostatic discharges, wiping out data and damaging sensitive electronics. This extender kit provides ESD protection to ± 15 kV, reducing potential static damage to your connected USB peripherals. The durable metal transmitter and receiver units withstand harsh physical conditions in industrial and commercial applications, such as factories, construction sites, supply rooms and warehouses.

With Great Distance Comes Great Flexibility By extending the USB connection beyond the standard 16-foot distance limitation to 150-ft. (45.72 m), the B203-101-IND provides workstation flexibility to place your computer and the USB device where they are best suited. This extender kit supports USB 2.0 data transfer rates up to 480 Mbps and is backward compatible with USB 1.1 technology, allowing you to connect legacy devices. No network connectivity is needed.

Plug-and-Play Kit Offers Flexible Power and Installation Options With user-supplied USB cables, connect the transmitter to your computer and the receiver to your USB peripheral. Connect the transmitter and receiver with a user-supplied Cat5/6 cable (all cables sold separately). The extender kit requires no software to download and install. The metal chassis rest easily on any flat surface or mount to a wall or DIN rail using the included hardware. A power supply with international plug adapters as well as a RS-232 Phoenix adapter supporting a DC voltage range from 9-36V is included for connecting external power to the unit as needed.

TAA-Compliant for GSA Schedule Purchases The B203-101-IND is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Highlights

- Supports USB 2.0 speeds up to 480 Mbps to ensure reliable data transfers
- Power over Cable (PoC) provides power to the transmitter via Cat5/6 cable
- ESD protection to ± 15 kV cuts potential static damage to your connected peripherals
- Industrial-grade metal housings withstand harsh warehouse and factory environments
- Compatible with all major operating systems, including Windows, Mac OS and Chrome

Applications

- Connect an impact printer or 1080p webcam using existing in-wall Cat5/6 wiring to a computer, laptop or server located in another room
- Eliminate excessive cable clutter with the extender kit's PoC capability
- Place the computer or server in a locked cabinet or closet to protect against tampering
- Mount to a wall or DIN rail in a harsh environment, such as a factory, construction site, supply room or warehouse

System Requirements

- Computer, laptop or server with USB-A port
- Cat5/5e/6/6a cabling
- Any major operating system, including Windows, Mac OS and Chrome

Package Includes

- Transmitter
- Receiver
- (2) DIN rail mounts
- (4) M4 screws
- RS-232 Phoenix adapter
- International power supply (Input: 100–240V, 50/60 Hz, 0.35A; Output: 5V 2A)
- (4) Plug adapters (North America, Europe, U.K.,



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Australia)

- Owner's manual

Specifications

| OVERVIEW | |
|--|---|
| UPC Code | 037332256072 |
| Technology | USB 2.0 (High Speed) |
| VIDEO | |
| HDR Support | No |
| INPUT | |
| Product Length (in.) | 4.528 |
| Product Length (cm.) | 11.501 |
| Product Length (ft.) | 0.377 |
| Product Length (m.) | 0.115 |
| POWER | |
| Power Over Cable (PoC) Support | Yes |
| USB Power Delivery (PD) Charging Support | No |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Transmitter: 1x Green (Connection); 1x Orange (Signal) Receiver: 1x Green (Connection); 1x Orange (Activity) |
| PHYSICAL | |
| Material of Construction | Metal |
| Color | Black |
| Receiver Unit Dimensions (hwd / cm.) | 11.501 x 6.240 x 2.700 |
| Receiver Unit Dimensions (hwd / in.) | 4.528 x 2.457 x 1.063 |
| Receiver Unit Weight (lbs.) | 1 |
| Transmitter Unit Dimensions (hwd / cm.) | 11.501 x 6.240 x 2.700 |
| Transmitter Unit Dimensions (hwd / in.) | 4.528 x 2.457 x 1.063 |
| Transmitter Unit Weight (lbs.) | 1 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|--------------------------------------|---|
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 1 |
| Unit Weight (kg) | 0.45 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 - 122 °F (0 - 50 °C) |
| Storage Temperature Range | -4 - 158 °F (-20 - 70 °C) |
| Operating Humidity Range | 0 - 85% RH, NON-CONDENSING |
| Storage Humidity Range | 0 - 85% RH, NON-CONDENSING |
| ESD Protection | 15KV |
| COMMUNICATIONS | |
| Signal Range (ft.) | 150 |
| Signal Range (m) | 46 |
| Transmission Distance | 45m (150 ft) |
| IR Remote Extension Support | No |
| RS-232 Serial Extension Support | No |
| USB Extension Support | No |
| CONNECTIONS | |
| Number of Ports | 4 |
| Side A - Connector 1 | USB B (FEMALE) |
| Side A - Connector 2 | RJ45 (FEMALE) |
| Side B - Connector 1 | USB A (FEMALE) |
| Side B - Connector 2 | RJ45 (FEMALE) |
| Connector Plating | Nickel |
| FEATURES & SPECIFICATIONS | |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| Driver Required | No |
| Recommended Category Cable | Cat5e/Cat6 |
| STANDARDS & COMPLIANCE | |
| Certification & Compliance | CE (Europe); RoHS; REACH; FCC (USA); NOM (Mexico) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<https://www.tripplite.com/products/product-certification-agencies>