

Han F+B housing bulkhead mount-angled



Part number	09 15 503 0901
Specification	Han F+B housing bulkhead mount- angled
HARTING eCatalogue	https://b2b.harting.com/09155030901

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series	Han [®] F+B
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	Angled With three through holes for fixing screws

Version

Locking type	Screw locking
Field of application	Connector for food+beverage industry
	Cleaning: For cleaning with high pressure lances, a cleaning distance > 30 cm is recommended in order to avoid mechanical damage to the connector's exterior parts.
Details	Strain relief:A suitable strain relief is required to enable the F+B connectorto resist the stress caused e.g. by the daily cleaning of the machinery. DIN VDE 0100-520: 2013-06 defines the stress relief for a connector depending on the outer diameter of the cable.

Technical characteristics

Limiting temperature	-40 +125 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP67 locked condition IP6K9K acc. to ISO 20653

Material properties

Material (hood/housing)	Polypropylen
Roughness of the surface	≤1.12 µm



Material properties

Colour (hood/housing)	Black
Material (seal)	EPDM Silicone
Colour (seal)	Blue
Material flammability class acc. to UL 94	НВ
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
EG1935/2004	compliant
California Proposition 65 substances	Yes
California Proposition 65 substances	Naphthalene

Specifications and approvals

	Ecolab Topactive 200
	Ecolab Topactive 500
	Ecolab Topax 66
Approvals	Ecolab Topactive OKTO
	Ecolab Topax 990
	FDA 21 CFR 177.1520
	FDA 21 CFR 177.2600
CE	Yes
CE	165

Commercial data

Packaging size	1
Net weight	29.72 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors