



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

## 10Gb/100Gb Duplex Multimode 50/125 OM4 LSZH Fiber Patch Cable (LC/LC) - Aqua, 2M (6 ft.)

MODEL NUMBER: N820-02M-OM4



### Highlights

- Designed for 40/100-Gig Ethernet applications...OM4 Rated
- Backward compatible with existing 50/125 fiber
- Max 40/100Gb distance of 300 meters @850nm
- Low-Smoke, Zero Halogen (LSZH) Aqua jacket

### Package Includes

- 2 meter ( 6ft ) Duplex Multimode 50/125 Aqua OM4 Fiber Patch Cable, LC/LC

### Features

- 2 Meter ( 6ft ) LC/LC, OM4 Rated
- 40/100Gb Ethernet speed to 300 meters @850nm
- Use with VCSEL and LED laser light sources
- High-Speed, High-Bandwidth, Low-Cost
- Backward compatible with legacy LAN's
- Ideal for Fibre Channel (SAN) applications
- IEEE 802.3ae and TIA LOMMF compliant

## Specifications

| OVERVIEW                |              |
|-------------------------|--------------|
| UPC Code                | 037332165244 |
| Technology              | Multimode    |
| Optical Mode            | OM4          |
| PHYSICAL                |              |
| Cable Jacket Color      | Aqua         |
| Connector Color         | Aqua         |
| Cable Jacket Material   | LSZH         |
| Cable Jacket Rating     | OFNR         |
| Clad Diameter (microns) | 125          |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                      |                                                       |
|--------------------------------------|-------------------------------------------------------|
| Core Diameter (microns)              | 50                                                    |
| Number of Fibers                     | 2                                                     |
| Cable Length (ft.)                   | 6.6                                                   |
| Cable Length (m)                     | 2.01                                                  |
| Cable Length (in.)                   | 78.7                                                  |
| Minimum Bend Radius                  | 20MM (Dynamic); 10MM (Static)                         |
| Shipping Dimensions (hwd / cm)       | 22.86 x 17.78 x 1.27                                  |
| Shipping Dimensions (hwd / in.)      | 9.00 x 7.00 x 0.50                                    |
| Shipping Weight (kg)                 | 0.02                                                  |
| Shipping Weight (lbs.)               | 0.05                                                  |
| <b>ENVIRONMENTAL</b>                 |                                                       |
| Operating Temperature Range          | -4 to 140 °F (-20 to 60 °C)                           |
| Storage Temperature Range            | -4 to 140 °F (-20 to 60 °C)                           |
| Operating Humidity Range             | 5% to 85% RH, Non-Condensing                          |
| Storage Humidity Range               | 35% to 65% RH, Non-Condensing                         |
| <b>COMMUNICATIONS</b>                |                                                       |
| Network Compatibility                | 1 Gbps (Gigabit); 10 Gbps; 25 Gbps; 40 Gbps; 100 Gbps |
| Attenuation @ 850NM                  | 3.0dB/Km                                              |
| Insertion Loss                       | 0.20dB                                                |
| <b>CONNECTIONS</b>                   |                                                       |
| Side A - Connector 1                 | LC DUPLEX (MALE)                                      |
| Side B - Connector 1                 | LC DUPLEX (MALE)                                      |
| Endface Polish                       | PC                                                    |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                                       |
| Push/Pull Tabs                       | No                                                    |
| Breakout                             | No                                                    |
| Trunk                                | No                                                    |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                                       |
| Certification & Compliance           | RoHS; REACH                                           |
| <b>WARRANTY</b>                      |                                                       |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty                             |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:  
<https://www.tripplite.com/products/product-certification-agencies>