

The N052-P24 is designed specifically to be used in PoE applications. It does not add PoE power to a Cat5e signal not already transmitting both data and power.

## Cat5e 24-Port Patch Panel - PoE+ Compliant, 110/Krone, 568A/B, RJ45 Ethernet, 1U Rack-Mount, TAA

MODEL NUMBER: **N052-P24**



PoE+-compliant 24-port patch panel manages and organizes Cat5e data/power cable connections in your high-density network.

### Description

IEC 60512-99-002 Compliant  
PoE Certificate Number: 2019-248  
UTP Cat6 22-24 AWG solid cable (Requires PoE cable if used in PoE setting)

### Features

**24-Port Patch Panel Manages and Organizes High-Density Cat5e Network Cabling** This patch panel enables quick, easy cable patching. Just plug Cat5e cables into its 24 front RJ45 ports, and use a 110 or Krone punch-down tool (do not use a 4/5 pair 110 punch-down tool) to terminate color-coded connections in the rear. Both the front and rear connectors are clearly numbered, and the front ports have blank labels to help you identify individual cable runs. The N052-P24 supports EIA/TIA 568A and 568B wiring standards and is compatible with all network applications.

**Specifically Designed for Use in Power over Ethernet Plus (PoE+) Applications** This Power over Ethernet patch panel maximizes performance with PoE+ applications. It prevents spark-gap erosion that degrades the plug and jack contacts over time and can affect data and/or power transmission capabilities. The N052-P24 is designed to handle the frequent mating and unmating of surveillance cameras, VoIP phone systems, wireless access points and other PoE and PoE+ devices under electrical load.

**Mounts in 1U of Space in Your 19 in. Enclosure or Open Frame Rack** The high-density patch panel supports mounting in 1U of space in EIA-standard 19-inch racks. Included cable ties and a removable cable management bracket help organize your connections, cut down on cord clutter and maintain stable performance.

**TAA-Compliant for GSA Schedule Purchases** The N052-P24 is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

### Highlights

- Power over Ethernet patch panel prevents spark-gap erosion that can affect transmission
- 24 RJ45 and 110 ports numbered/labeled for immediate cable identification
- Mounts easily into 1U of space in your EIA-standard 19 in. rack for immediate use
- Supports EIA/TIA 568A/B wiring standards for either 110 or Krone-type terminations
- Ideal for managing Cat5e cable patching in high-density IT environments

### Applications

- Patch cables to PoE+ devices mounted in areas that are difficult to reach or have no electrical outlets
- Add routers, switches, wireless access points, security cameras, sensors and other PoE+ devices to an Ethernet network configuration

### Package Includes

- N052-P24 24-Port 1U Rack-Mount Cat5e Patch Panel - PoE+ Compliant
- Cable management bracket
- (8) Cable ties
- Quick Start Guide



**Lifetime Warranty** The N052-P24 is backed by a lifetime warranty, ensuring reliability and performance.

## Specifications

| OVERVIEW                            |                                       |
|-------------------------------------|---------------------------------------|
| UPC Code                            | 037332210418                          |
| Product Type                        | Punchdown                             |
| Technology                          | Cat5/5e                               |
| PHYSICAL                            |                                       |
| Color                               | Black                                 |
| Shipping Dimensions (hwd / cm)      | 6.86 x 49.02 x 7.62                   |
| Shipping Dimensions (hwd / in.)     | 2.70 x 19.30 x 3.00                   |
| Shipping Weight (kg)                | 0.73                                  |
| Shipping Weight (lbs.)              | 1.60                                  |
| Unit Dimensions (hwd / in.)         | 1.73 x 18.89 x 4.38                   |
| Unit Dimensions (hwd / cm)          | 4.4 x 47.98 x 11.13                   |
| ENVIRONMENTAL                       |                                       |
| Operating Temperature Range         | 14 TO 140 F (-10 TO 60 C)             |
| Storage Temperature Range           | -40 TO 154.4 F (-40 TO 68 C)          |
| Relative Humidity                   | 10% TO 90% RH, NON-CONDENSING         |
| CONNECTIONS                         |                                       |
| Number of Ports                     | 24                                    |
| PoE Power Budget (Watts)            | 90                                    |
| Side A - Connector 1                | 110 IDC                               |
| Side B - Connector 1                | RJ45 (FEMALE)                         |
| PoE Type                            | Type 3 PoE++/UPoE (60W, IEEE 802.3bt) |
| STANDARDS & COMPLIANCE              |                                       |
| Certification & Compliance          | RoHS; UL Listed; CE (Europe)          |
| WARRANTY                            |                                       |
| Product Warranty Period (Worldwide) | Lifetime limited warranty             |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>