

Han 10Ex UL-HTE-M25



Image is for illustration purposes only. Please refer to product description.

Identification

| | |
|--------------------------|----------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han® Ex |
| Type of hood/housing | Hood |

Version

| | |
|----------------------|--|
| Size | 10 B |
| Version | Top entry |
| Cable entry | 1x M25 |
| Locking type | Double locking lever |
| Field of application | Connectors for explosion hazardous environments |
| Details | for US purposes only |
| Details | ATTENTION! Only to be used with Han® Ex inserts! |

Technical characteristics

| | |
|--|-----------------------|
| Limiting temperature | -20 ... +40 °C |
| Degree of protection acc. to IEC 60529 | IP65 With cable gland |

Material properties

| | |
|-------------------------|---------------------|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 5015 (sky blue) |
| RoHS | compliant |
| ELV status | compliant |

Material properties

| | |
|--------------------------------------|----------------|
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Lead |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 293 g |
| Country of origin | China |
| European customs tariff number | 85389099 |
| eCl@ss | 27440202 Shell for industrial connectors |