

## Han-Eco Mod.6 Outd.-HCC-M32-glanded



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 19 41 306 0722  |
| Specification      | Han-Eco Mod.6 Outd.-HCC-M32-glanded   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19413060722">https://b2b.harting.com/19413060722</a> |

### Identification

|                             |                             |
|-----------------------------|-----------------------------|
| Category                    | Hoods/Housings              |
| Series of hoods/housings    | Han-Eco® Modular            |
| Type of hood/housing        | Cable to cable housing      |
| Description of hood/housing | With integrated cable gland |

### Version

|              |                      |
|--------------|----------------------|
| Size         | 6 B                  |
| Module slots | 3                    |
| Version      | Top entry            |
| Cable entry  | 1x M32               |
| Locking type | Double locking lever |

### Technical characteristics

|  |                 |
|--|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Number of relockings                   | ≥500            |
| Degree of protection acc. to IEC 60529 | IP65            |
| Clamping range                         | 13 ... 21 mm    |

### Material properties

|                         |  |
|-------------------------|--|
| Material (hood/housing) | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (hood/housing)   | RAL 9005 (jet black)                     |
| Material (seal)         | FPM                                      |

## Material properties

|  |  |
|--|--|
| Colour (seal)  | RAL 7001 (silver-grey)                   |
| Material (locking)   | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (locking)   | RAL 9005 (jet black)                     |
| Material flammability class acc. to UL 94                  | V-0                                      |
| Material flammability class acc. to UL 94 (locking levers) | V-0                                      |
| RoHS   | compliant                                |
| ELV status   | compliant                                |
| China RoHS   | e  |
| REACH Annex XVII substances                                | No                                       |
| REACH ANNEX XIV substances                                 | No                                       |
| REACH SVHC substances                                      | No                                       |

## Specifications and approvals

|                |  |
|----------------|--|
| Specifications | IEC 61984<br>EN 45545-2 R22: HL1, HL2, HL3<br>EN 45545-2 R23: HL1, HL2, HL3<br>EN 45545-2 R24: HL1, HL2, HL3 |
| UL / CSA       | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076   |
| CE             | Yes  |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 163.5 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |