

Han K 9/9/18-F-C



Image is for illustration purposes only. Please refer to product description.

Identification

Category	Inserts
Series	Han-Com®
Identification	Han® K 9/9/18

Version

Termination method	Crimp termination
Gender	Female
Size	16 B
Number of contacts	36
Number of signal contacts	18
Number of power contacts	9
PE contact	Yes
Details	<p>Please order crimp contacts separately.</p> <p>9x Han® C</p> <p>9x Han E®</p> <p>18x Han D®</p> <p>To ensure a preleading PE-contact under all conditions, it is necessary to use guide pins/bushes (09 33 000 9908 / 09 33 000 9909).</p>

Technical characteristics

Conductor cross-section	1.5 ... 6 mm ² Power 0.14 ... 4 mm ² Power 0.14 ... 2.5 mm ² Signal
Rated current (signal)	10 A

Technical characteristics

Rated voltage (signal)	250 V
Rated impulse voltage (signal)	4 kV
Pollution degree (signal)	3
Rated current (power)	40 A 16 A
Rated voltage (power)	830 V 830 V
Rated impulse voltage (power)	8 kV 8 kV
Pollution degree (power)	3 3
Insulation resistance	>10 ¹⁰ Ω
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500

Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead

Specifications and approvals

Specifications	EN 60664-1 IEC 61984
Approvals	DNV GL

Commercial data

Packaging size	1
----------------	---

Commercial data

Net weight	68 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440205 Contact insert for industrial connectors