




Pushing Performance

## Han-Eco 24B Outd-HCC-with DL-M40



|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 43 224 0738                                                                        |
| Specification      | Han-Eco 24B Outd-HCC-with DL-M40                                                      |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19432240738">https://b2b.harting.com/19432240738</a> |

### Identification

|                          |                        |
|--------------------------|------------------------|
| Category                 | Hoods/Housings         |
| Series of hoods/housings | Han-Eco <sup>®</sup> B |
| Type of hood/housing     | Cable to cable housing |

### Version

|              |                      |
|--------------|----------------------|
| Size         | 24 B                 |
| Version      | Top entry            |
| Cable entry  | 1x M40               |
| Locking type | Double locking lever |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Number of relockings                   | ≥500            |
| Degree of protection acc. to IEC 60529 | IP66            |

### Material properties

|                                           |                                          |
|-------------------------------------------|------------------------------------------|
| Material (hood/housing)                   | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (hood/housing)                     | RAL 9005 (jet black)                     |
| Material (seal)                           | FPM                                      |
| Colour (seal)                             | RAL 7001 (silver-grey)                   |
| Material (locking)                        | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (locking)                          | RAL 9005 (jet black)                     |
| Material flammability class acc. to UL 94 | V-0                                      |



Pushing Performance

## Material properties

Material flammability class acc. to UL 94  
 (locking levers)

V-0

RoHS

compliant with exemption

RoHS exemptions

6(c): Copper alloy containing up to 4 % lead by weight

ELV status

compliant with exemption

China RoHS

50

REACH Annex XVII substances

Not contained

REACH ANNEX XIV substances

Not contained

REACH SVHC substances

Yes

REACH SVHC substances

Lead

California Proposition 65 substances

Yes

California Proposition 65 substances

Lead

## Specifications and approvals

Specifications

IEC 61984

EN 45545-2 R22: HL1, HL2, HL3

EN 45545-2 R23: HL1, HL2, HL3

EN 45545-2 R24: HL1, HL2, HL3

CE

Yes

## Commercial data

Packaging size

1

Country of origin

Germany

European customs tariff number

85389099

eCl@ss

27440202 Shell for industrial connectors