

Specification Sheet

Part Number: TELS-H



Continuous strap and separate heads allow for any bundle diameter, eliminating waste.

Smooth strap prevents cable damage.

UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

Article Number	111-31000
----------------	-----------

Type	EL-TY (TELSH)
------	---------------

Color	Black (BK)
-------	------------

Quantity Per	bag
--------------	-----

Product Description	Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.
---------------------	--

Short Description	Extended-Length Tie Heads, POM, Black, 25/pkg
-------------------	---

Global Part Name	EL-TY (TELSH)-POM-BK
-------------------------	----------------------

Contents of pkg/kit	25 Heads
----------------------------	----------

Minimum Tensile Strength (Imperial)	250.0
--	-------

Minimum Tensile Strength (Metric)	1115.0
--	--------

Length L (Imperial)	0.62
----------------------------	------

Length L (Metric)	15.75
--------------------------	-------

Fixation Method	2 piece
------------------------	---------

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	No
---------------------------	----

Tie Closure	steel pawl
--------------------	------------

Variant	Extended Length
----------------	-----------------

Width W (Imperial)	0.8
---------------------------	-----

Width W (Metric)	20.3
-------------------------	------

Height H (Imperial)	.49
----------------------------	-----

Height H (Metric)	12.40
--------------------------	-------

Cable Tie Width Max (Metric)	12.7
-------------------------------------	------

Material	Polyacetal (POM)
Material Shortcut	POM
Material Cable Tie	Polyacetal (POM)
Material Head	Polyacetal (POM)
Flammability	UL 94 HB
Operating Temperature	-40°F to +194°F (-40°C to +90°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909988