



SUMMARY

Wires



Image is for illustrative purpose only

Series 0S

Termination type No contacts / Accessory

IP rating (

AWG wire size 0.00 - 0.00

Cable Ø 0.00 - 0.00 mm

Status active

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model GRA*: Insulating washer

Keying No keying

Housing Material Polyamide, red

Weight .07 g

Performance

Configuration

Insulator

Rated Current

Others

Temp (min / max): -50° C / $+90^{\circ}$ C


Humidity (max): $\leq 95\%$ [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Climatical Category: 50/175/21

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz)

DRAWINGS



No keying

Dimensions

	А	В	L	М	S	Т
mm.	12	10.8	1.8	1	8.3	9.9
in.	0,47	0,43	0,07	0,04	0,33	0,39

RECOMMENDED BY LEMO

Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.