



G3&4" Water Flow Sensor

SKU 314150003

Description

Water flow sensor consists of a plastic valve body, a water rotor, and a hall-effect sensor. When water flows through the rotor, rotor rolls. Its speed changes with different rate of flow. The hall-effect sensor outputs the corresponding pulse signal. This one is suitable to detect flow in water dispenser or coffee machine.

We have a comprehensive line of water flow sensors in different diameters. Check them out to find the one that meets your need most.

FEATURES

- Compact, Easy to Install
- High Sealing Performance
- High Quality Hall Effect Sensor
- RoHS Compliant

SPECIFICATIONS

- Mini. Working Voltage: DC 4.5V
- Max. Working Current: 15mA (DC 5V)
- Working Voltage: DC 5V~24V
- Flow Rate Range: 0~60L/min
- Load Capacity: ≤10mA (DC 5V)
- Operating Temperature: ≤80°C
- Liquid Temperature: ≤120°C
- Operating Humidity: 35%~90%RH
- Water Pressure: ≤2.0MPa
- Storage Temperature: -25~+ 80°C
- Storage Humidity: 25%~95%RH

Technical Details

| | |
|------------|---------------------|
| Dimensions | 100mm x 60mm x 38mm |
| Weight | G.W 65g |
| Battery | Exclude |

ECCN/HTS

| | |
|--------|------------|
| ECCN | ERA99 |
| HSCODE | 9026100000 |

Certification

| | |
|------|-----------|
| RoHS | Compliant |
|------|-----------|