


# TANTALUM SURFACE MOUNT CAPACITORS – LOW ESR –

**TC SERIES:** The TC Series is designed for hybrid circuit and low profile printed circuit board applications where inductance is to be minimized, or where substrate space is at a premium. They can be attached to substrates or circuit boards by dipsoldering, welding, re-flow soldering or other conventional methods.

These units have the further advantage of being compatible with automatic assembly equipment-minus the problems associated with flexible terminal lead wires. Our chip tantalums meet all EIA sizes.



## BENEFITS

- Meets or exceeds EIA Standard 535BAAC
- Tape & Reel standard packaging per EIA 481
- High surge current capability
- Optional gold-plated terminations
- High ripple current capability
- 100% surge current test on B, C, D, E, U, V, and X sizes
- 100% steady-state accelerated aging
- Capacitance values of 0.1 – 1,000  $\mu\text{F}$
- Tolerances of  $\pm 10\%$  and  $\pm 20\%$
- Voltage rating of 2.5 – 50 VDC
- Extended range values
- RoHS compliant and lead-free terminations
- Operating temperature range of  $-55^\circ\text{C}$  to  $+125^\circ\text{C}$

## APPLICATIONS

Typical applications include decoupling and filtering in automotive end applications, such as DC/DC converters, portable electronics, telecommunications, and control units requiring high ripple current capability.

## ENVIRONMENTAL COMPLIANCE

RoHS compliant (6/6) according to Directive 2002/95/EC when ordered with 100% Sn solder, Gold-plated or Non-magnetic 100% Sn solder.

## ORDERING INFORMATION

TC	K	IA	107	D	T	LSR 045	G
CAPACITOR CLASS	TOLERANCE	VOLTAGE (VDC)	CAPACITANCE CODE (P#)	CASE SIZE	TERMINATION FINISH	LOW ESR RATING	PACKAGING CODE
T = Tantalum	K = $\pm 10\%$ M = $\pm 20\%$	OB = 2.5 OG = 4 OJ = 6.3 IA = 10 IC = 16 ID = 20 IE = 25 IV = 35 1X = 50	First two digits represent significant figures. Third digit specifies number of zeros	A B C D H E M T U V W	T = 100% Matte tin (Sn)-plated B = Standard solder coated H = (SnPb 5% Pb minimum) G = Gold-plated (A, B, C, D, X only) N = Non-magnetic 100% tin (Sn) M = Non-magnetic (SnPb)	LSR = ESR last three digits specify ESR in $\text{m}\Omega$ (45 = 45 $\text{m}\Omega$ )	Blank: 7" reel G: 13" reel

## PERFORMANCE CHARACTERISTICS

ITEM	PERFORMANCE CHARACTERISTICS
Operating Temperature	$-55^\circ\text{C}$ to $125^\circ\text{C}$
Rated Capacitance Range	0.47 – 1,000 $\mu\text{F}$ at 120 Hz/25°C
Capacitance Tolerance	K tolerance (10%), M tolerance (20%)
Rated Voltage Range	2.5 – 50 V
DF (120 Hz)	Refer to Part Number Electrical Specification Table
ESR (100 kHz)	Refer to Part Number Electrical Specification Table
Leakage Current	$\leq 0.01 \text{ CV} (\mu\text{A})$ at rated voltage after 5 minutes





## QUALIFICATION


TEST	CONDITION	CHARACTERISTICS				
Endurance	85°C at rated voltage, 2,000 hours 125°C at 2/3 rated voltage, 2,000 hours	Δ C/C - DF - DCL - ESR -	Within ±10% of initial value Within initial limits Within 1.25 x initial limit Within initial limits			
Storage Life	125°C at 0 volts, 2,000 hours	Δ C/C - DF - DCL - ESR -	Within ±10% of initial value Within initial limits Within 1.25 x initial limit Within initial limits			
Thermal Shock	MIL-STD-202, Method 107, Condition B, mounted, -55°C to 125°C, 1,000 cycles	Δ C/C - DF - DCL - ESR -	Within ±10% of initial value Within initial limits Within 1.25 x initial limit Within initial limits			
Temperature Stability	Extreme temperature exposure at a succession of continuous steps at +25°C, -55°C, +25°C, +85°C, +125°C, +25°C.	Δ C/C DF DCL	+25°C IL* IL IL	-55°C ±10% IL N/A	+85°C ±10% 1.5 x IL 10 x IL	+125°C ±20% 1.5 x IL 12 x IL
Surge Voltage	85°C, 1.32 x rated voltage 1,000 cycles (125°C, 1.2 x rated voltage)	Δ C/C - DF - DCL - ESR -	Within ±5% of initial value Within initial limits Within initial limits Within initial limits			
Mechanical Shock/ Vibration	MIL-STD-202, Method 213, Condition I, 100 G peak MIL-STD-202, Method 204, Condition D, 10 Hz to 2,000 Hz, 20 G peak	Δ C/C - DF - DCL -	Within ±10% of initial value Within initial limits Within initial limits			

\*IL - Initial Limit





## ELECTRICAL CHARACTERISTICS

ESR VS. FREQUENCY



CAPACITANCE VS. FREQUENCY




TC SERIES

**Cal-Chip**  
Electronics Inc.



## DIMENSIONS – MILLIMETERS (INCHES)

Metric will govern



CASE SIZE		COMPONENT												TYPICAL WEIGHT	
CCE	EIA	L	W	H	F $\pm 0.1$ $\pm(0.004)$	S	B $\pm 0.15$ (Ref) $\pm 0.006$	X (Ref)	P (Ref)	R (Ref)	T (Ref)	A (Min)	G (Ref)	E (Ref)	(mg)
A	3216-18	3.2 $\pm 0.2$ (0.126 $\pm 0.008$ )	1.6 $\pm 0.2$ (0.063 $\pm 0.008$ )	1.6 $\pm 0.2$ (0.063 $\pm 0.008$ )	1.2 (0.047)	0.80 (0.032) $+0.2 (0.008)$ $-0.3 (0.011)$	0.4 (0.016)	0.10 $\pm 0.10$ (0.004 $\pm 0.004$ )	0.4 (0.016)	0.4 (0.016)	0.13 (0.005)	1.2 (0.047)	1.1 (0.043)	1.3 (0.051)	58.60
B	3528-21	3.5 $\pm 0.2$ (0.138 $\pm 0.008$ )	2.8 $\pm 0.2$ (0.110 $\pm 0.008$ )	1.9 $\pm 0.2$ (0.075 $\pm 0.008$ )	2.2 (0.087)	0.80 (0.032) $+0.1 (0.004)$ $-0.3 (0.011)$	0.4 (0.016)	0.10 $\pm 0.10$ (0.004 $\pm 0.004$ )	0.5 (0.020)	1.0 (0.039)	0.13 (0.005)	1.9 (0.075)	1.8 (0.071)	2.2 (0.087)	107.45
M	3528-15	3.5 $\pm 0.2$ (0.138 $\pm 0.008$ )	2.8 $\pm 0.2$ (0.110 $\pm 0.008$ )	1.5 (0.059)	2.2 (0.087)	0.8 (0.031) $\pm 0.3 (0.012)$	N/A	0.05 (0.002)	N/A	N/A	0.13 (0.005)	1.9 (0.075)	1.8 (0.071)	2.2 (0.087)	97.99
C	6032-28	6.0 $\pm 0.3$ (0.236 $\pm 0.012$ )	3.2 $\pm 0.3$ (0.126 $\pm 0.012$ )	2.5 $\pm 0.3$ (0.098 $\pm 0.012$ )	2.2 (0.087)	1.3 (0.051) $\pm 0.3 (0.012)$	0.5 (0.020)	0.10 $\pm 0.10$ (0.004 $\pm 0.004$ )	0.9 (0.035)	1.0 (0.039)	0.13 (0.005)	2.9 (0.114)	2.8 (0.110)	2.4 (0.094)	224.48
U	6032-15	6.0 $\pm 0.3$ (0.236 $\pm 0.012$ )	3.2 $\pm 0.2$ (0.110 $\pm 0.008$ )	1.5 (0.059)	2.2 (0.087)	1.3 (0.051) $\pm 0.3 (0.012)$	N/A	0.05 (0.002)	N/A	N/A	0.13 (0.005)	2.9 (0.114)	2.8 (0.110)	2.4 (0.094)	70.00
D	7343-31	7.3 $\pm 0.3$ (0.287 $\pm 0.012$ )	4.3 $\pm 0.3$ (0.169 $\pm 0.012$ )	2.8 $\pm 0.3$ (0.110 $\pm 0.012$ )	2.4 (0.094)	1.3 (0.051) $\pm 0.3 (0.012)$	0.5 (0.020)	0.10 $\pm 0.10$ (0.004 $\pm 0.004$ )	0.9 (0.035)	1.0 (0.039)	0.13 (0.005)	3.6 (0.142)	3.5 (0.138)	3.5 (0.138)	446.84
W	7343-15	7.3 $\pm 0.3$ (0.287 $\pm 0.012$ )	4.3 $\pm 0.3$ (0.169 $\pm 0.012$ )	1.5 (0.059)	2.4 (0.094)	1.3 (0.051) $\pm 0.3 (0.012)$	N/A	0.05 (0.002)	N/A	N/A	0.13 (0.005)	3.6 (0.142)	3.5 (0.138)	3.5 (0.138)	248.27
E	7343-43	7.3 $\pm 0.3$ (0.287 $\pm 0.012$ )	4.3 $\pm 0.3$ (0.169 $\pm 0.012$ )	4.0 $\pm 0.3$ (0.157 $\pm 0.012$ )	2.4 (0.094)	1.3 (0.051) $\pm 0.3 (0.012)$	0.5 (0.020)	0.10 $\pm 0.10$ (0.004 $\pm 0.004$ )	1.7 (0.067)	1.0 (0.039)	0.13 (0.005)	3.6 (0.142)	3.5 (0.138)	3.5 (0.138)	652.04
H	7360-38	7.3 $\pm 0.3$ (0.287 $\pm 0.012$ )	6.0 $\pm 0.3$ (0.236 $\pm 0.012$ )	3.6 $\pm 0.2$ (0.142 $\pm 0.008$ )	4.1 (0.161)	1.3 (0.051) $\pm 0.3 (0.012)$	0.5 (0.020)	0.10 $\pm 0.10$ (0.004 $\pm 0.004$ )	N/A	N/A	0.13 (0.005)	3.6 (0.142)	3.5 (0.138)	3.5 (0.138)	803.76
T	3528-12	3.5 $\pm 0.2$ (0.138 $\pm 0.008$ )	2.8 $\pm 0.2$ (0.110 $\pm 0.008$ )	1.2 (0.047)	2.2 (0.087)	0.80 (0.032) $+0.1 (0.004)$ $-0.3 (0.011)$	N/A	0.05 (0.002)	N/A	N/A	0.13 (0.005)	1.9 (0.075)	1.8 (0.071)	2.2 (0.087)	63.89
V	7343-20	7.3 $\pm 0.3$ (0.287 $\pm 0.012$ )	4.3 $\pm 0.3$ (0.169 $\pm 0.012$ )	2.0 (0.079)	2.4 (0.094)	1.3 (0.051) $\pm 0.3 (0.012)$	N/A	0.05 (0.002)	N/A	N/A	0.13 (0.005)	3.6 (0.142)	3.5 (0.138)	3.5 (0.138)	286.40

Notes: (Ref) – Dimensions provided for reference only. For low profile cases, no dimensions are provided for B, P, or R because these cases do not have a bevel or a notch. These weights are provided as reference.

## RATINGS &amp; PART NUMBER REFERENCE

Table 1

RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	µF	CCE/EIA	(See below for part options)	µA +20°C Max/5 Min	% at +20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at +25°C 100 kHz	mA at +85°C 100 kHz	mA at +125°C 100 kHz	°C	Reflow Temp ≤ 260°C
2.5	220	D/7343-31	TC(1)OB227D(2)LSR045	5.5	8.0	45	1826	1643	730	125	1
2.5	470	D/7343-31	TC(1)OG477D(2)LSR035	11.8	8.0	35	2070	1863	828	125	1
2.5	1000	E/7343-43	TC(1)OB108E(2)LSR030	25.0	15.0	30	2345	2111	938	125	1
2.5	1000	E/7343-43	TC(1)OB108E(2)LSR040	25.0	15.0	40	2031	1828	812	125	1
4	6.8	A/3216-18	TC(1)OG685A(2)LSR2K0	0.5	6.0	2,000	194	175	78	125	1
4	22	C/6032-28	TC(1)OG226C(2)LSR2K4	0.9	6.0	2,400	214	193	86	125	1
4	22	C/6032-28	TC(1)OG226C(2)LSR380	0.9	6.0	380	538	484	215	125	1
4	33	T/3528-12	TC(1)OG336T(2)LSR1K2	1.3	8.0	1,200	242	218	97	125	1
4	68	T/3528-12	TC(1)OG686T(2)LSR1K5	2.7	20.0	1,500	216	194	86	125	1
4	68	V/7343-20	TC(1)OG686V(2)LSR150	2.7	6.0	150	913	822	365	125	1
4	100	B/3528-21	TC(1)OG107B(2)LSR500	4.0	8.0	500	412	371	165	125	1
4	100	D/7343-31	TC(1)OG107D(2)LSR800	4.0	6.0	800	433	390	173	125	1
4	150	B/3528-21	TC(1)OG157B(2)LSR900	6.0	12.0	900	307	276	123	125	1
4	150	C/6032-28	TC(1)OG157C(2)LSR070	6.0	12.0	70	1254	1129	502	125	1
4	150	C/6032-28	TC(1)OG157C(2)LSR250	6.0	8.0	250	663	597	265	125	1
4	150	U/6032-15	TC(1)OG157U(2)LSR200	6.0	8.0	200	671	604	268	125	1
4	220	D/7343-31	TC(1)OG227D(2)LSR040	8.8	8.0	40	1936	1742	774	125	1
4	220	D/7343-31	TC(1)OG227D(2)LSR050	8.8	8.0	50	1732	1559	693	125	1
4	220	D/7343-31	TC(1)OG227D(2)LSR100	8.8	8.0	100	1225	1103	490	125	1
4	330	C/6032-28	TC(1)OG337C(2)LSR300	13.2	10.0	300	606	545	242	125	1
4	330	C/6032-28	TC(1)OG337C(2)LSR700	13.2	12.0	700	396	356	158	125	1
4	330	D/7343-31	TC(1)OG337D(2)LSR030	13.2	8.0	30	2236	2012	894	125	1
4	330	D/7343-31	TC(1)OG337D(2)LSR045	13.2	8.0	45	1826	1643	730	125	1
4	330	D/7343-31	TC(1)OG337D(2)LSR100	13.2	8.0	100	1225	1103	490	125	1
4	470	D/7343-31	TC(1)OG477D(2)LSR045	18.8	12.0	45	1826	1643	730	125	1
4	470	D/7343-31	TC(1)OG477D(2)LSR100	18.8	12.0	100	1225	1103	490	125	1
4	470	E/7343-43	TC(1)OG477E(2)LSR030	18.8	8.0	30	2345	2111	938	125	1
4	470	E/7343-43	TC(1)OG477E(2)LSR045	18.8	8.0	45	1915	1724	766	125	1
4	470	E/7343-43	TC(1)OG477E(2)LSR060	18.8	10.0	60	1658	1492	663	125	1
4	470	E/7343-43	TC(1)OG477E(2)LSR100	18.8	8.0	100	1285	1157	514	125	1
4	680	E/7343-43	TC(1)OG687E(2)LSR040	27.2	10.0	40	2031	1828	812	125	1
4	680	E/7343-43	TC(1)OG687E(2)LSR060	27.2	10.0	60	1658	1492	663	125	1
4	680	E/7343-43	TC(1)OG687E(2)LSR100	27.2	10.0	100	1258	1157	514	125	1
4	1000	E/7343-43	TC(1)OG108E(2)LSR030	40.0	10.0	30	2345	2111	938	125	1
4	1000	E/7343-43	TC(1)OG108E(2)LSR040	40.0	10.0	40	2031	1828	812	125	1
4	1000	E/7343-43	TC(1)OG108E(2)LSR060	40.0	10.0	60	1658	1492	663	125	1
4	1000	E/7343-43	TC(1)OG108E(2)LSR070	40.0	10.0	70	1535	1382	614	125	1
4	1000	E/7343-43	TC(1)OG108E(2)LSR090	40.0	10.0	90	1354	1219	542	125	1
4	1000	E/7343-43	TC(1)OG108E(2)LSR100	40.0	10.0	100	1285	1157	514	125	1
4	1000	H/7360-38	TC(1)OG108H(2)LSR035	40.0	15.0	35	2390	2151	956	125	1
4	1000	H/7360-38	TC(1)OG108H(2)LSR050	40.0	15.0	50	2000	1800	800	125	1
6.3	2.2	A/3216-18	TC(1)OG225A(2)LSR5K0	0.5	6.0	5,000	122	110	49	125	1
6.3	3.3	A/3216-18	TC(1)OG335A(2)LSR3K0	0.5	6.0	3,000	158	142	63	125	1
6.3	6.8	A/3216-18	TC(1)OG685A(2)LSR1K8	0.5	6.0	1,800	204	184	82	125	1
6.3	6.8	A/3216-18	TC(1)OG685A(2)LSR2K0	0.5	6.0	2,000	194	175	78	125	1
6.3	6.8	A/3216-18	TC(1)OG685A(2)LSR4K5	0.5	6.0	4,500	129	116	52	125	1
6.3	6.8	C/6032-28	TC(1)OG685C(2)LSR480	0.5	6.0	480	479	431	192	125	1
6.3	10	A/3216-18	TC(1)OG106A(2)LSR00	0.6	6.0	800	306	275	122	125	1
6.3	10	A/3216-18	TC(1)OG108E(2)LSR100	0.6	6.0	1,000	274	247	110	125	1
6.3	10	A/3216-18	TC(1)OG108H(2)LSR035	0.6	15.0	224	202	90	125	1	
6.3	10	A/3216-18	TC(1)OG108H(2)LSR050	0.6	15.0	2,000	194	175	78	125	1
6.3	10	B/3528-21	TC(1)OG106A(2)LSR2K0	0.6	6.0	2,000	194	175	78	125	1
6.3	10	B/3528-21	TC(1)OG106B(2)LSR1K0	0.6	6.0	1,000	292	263	117	125	1
6.3	10	T/3528-12	TC(1)OG106T(2)LSR1K2	0.6	6.0	1,200	242	218	97	125	1
6.3	15	A/3216-18	TC(1)OG156A(2)LSR2K0	0.9	6.0	2,000	194	175	78	125	1
6.3	15	T/3528-12	TC(1)OG156T(2)LSR1K0	0.9	6.0	1,000	265	239	106	125	1
6.3	10	A/3216-18	TC(1)OG106A(2)LSR2K0	0.6	6.0	2,000	194	175	78	125	1
6.3	10	B/3528-21	TC(1)OG106B(2)LSR1K0	0.6	6.0	1,000	292	263	117	125	1
6.3	10	T/3528-12	TC(1)OG106T(2)LSR1K2	0.6	6.0	1,200	242	218	97	125	1
6.3	15	A/3216-18	TC(1)OG156A(2)LSR2K0	0.9	6.0	2,000	194	175	78	125	1
6.3	15	T/3528-12	TC(1)OG156T(2)LSR1K0	0.9	6.0	1,000	265	239	106	125	1
6.3	22	A/3216-18	TC(1)OG226A(2)LSR500	1.4	6.0	500	387	348	155	125	1
6.3	22	A/3216-18	TC(1)OG226A(2)LSR900	1.4	8.0	900	289	260	116	125	1
6.3	22	A/3216-18	TC(1)OG226A(2)LSR1K5	1.4	8.0	1,500	224	202	90	125	1
6.3	22	B/3528-21	TC(1)OG226B(2)LSR500	1.4	6.0	500	412	371	165	125	1
6.3	22	C/6032-28	TC(1)OG226C(2)LSR380	1.4	6.0	380	538	484	215	125	1
6.3	33	A/3216-18	TC(1)OG336A(2)LSR600	2.1	12.0	600	354	319	142	125	1
6.3	33	B/3528-21	TC(1)OG336B(2)LSR600	2.1	6.0	600	376	338	150	125	1
6.3	33	T/3528-12	TC(1)OG336T(2)LSR800	2.1	6.0	800	296	266	118	125	1
6.3	33	C/6032-28	TC(1)OG336C(2)LSR350	2.1	6.0	350	561	505	224	125	1
6.3	47	B/3528-21	TC(1)OG476B(2)LSR250	3.0	6.0	250	583	525	233	125	1

## RATINGS &amp; PART NUMBER REFERENCE

Table 2

RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	μF	CCE/EIA	(See below for part options)	μA +20°C Max/5 Min	% at+20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at+25°C 100 kHz	mA at+85°C 100 kHz	mA at+125°C 100 kHz	°C	Reflow Temp ≤ 260°C
6.3	47	B/3528-21	TC(1)OJ476B(2)LSR400	3.0	6.0	400	461	415	184	125	1
6.3	47	B/3528-21	TC(1)OJ476B(2)LSR450	3.0	6.0	450	435	392	174	125	1
6.3	47	B/3528-21	TC(1)OJ476B(2)LSR500	3.0	6.0	500	583	525	233	125	1
6.3	47	C/6032-28	TC(1)OJ476C(2)LSR250	3.0	6.0	250	663	597	265	125	1
6.3	47	C/6032-28	TC(1)OJ476C(2)LSR300	3.0	6.0	300	606	545	242	125	1
6.3	47	C/6032-28	TC(1)OJ476C(2)LSR330	3.0	6.0	330	577	519	231	125	1
6.3	47	V/7343-20	TC(1)OJ476V(2)LSR150	3.0	6.0	150	913	822	365	125	1
6.3	68	B/3528-21	TC(1)OJ686B(2)LSR500	4.3	8.0	500	412	371	165	125	1
6.3	68	C/6032-28	TC(1)OJ686C(2)LSR400	4.3	6.0	400	524	472	210	125	1
6.3	68	U/6032-15	TC(1)OJ686U(2)LSR400	4.3	6.0	400	474	427	190	125	1
6.3	68	D/7343-31	TC(1)OJ686D(2)LSR175	4.3	4.0	175	926	833	370	125	1
6.3	68	D/7343-31	TC(1)OJ686D(2)LSR180	4.3	4.0	180	913	822	365	125	1
6.3	100	B/3528-21	TC(1)OJ107B(2)LSR400	6.3	15.0	400	461	415	184	125	1
6.3	100	B/3528-21	TC(M)OJ107B(2)LSR700	6.3	15.0	700	348	313	139	125	1
6.3	100	M/3528-15	TC(1)OJ107M(2)LSR500	6.3	20.0	500	490	441	196	125	1
6.3	100	M/3528-15	TC(1)OJ107M(2)SR1K0	6.3	20.0	1,000	346	311	138	125	1
6.3	100	C/6032-28	TC(1)OJ107C(2)LSR075	6.3	8.0	75	1211	1090	484	125	1
6.3	100	C/6032-28	TC(1)OJ107C(2)LSR150	6.3	8.0	150	856	770	342	125	1
6.3	100	D/7343-31	TC(1)OJ107D(2)LSR050	6.3	6.0	50	1732	1559	693	125	1
6.3	100	D/7343-31	TC(1)OJ107D(2)LSR0130	6.3	6.0	130	1074	967	430	125	1
6.3	100	D/7343-31	TC(1)OJ107D(2)LSR150	6.3	8.0	150	1000	900	400	125	1
6.3	100	D/7343-31	TC(1)OJ107D(2)LSR800	6.3	6.0	800	433	390	173	125	1
6.3	100	V/7343-20	TC(1)OJ107V(2)LSR090	6.3	8.0	90	1179	1061	472	125	1
6.3	100	V/7343-20	TC(1)OJ107V(2)LSR150	6.3	8.0	150	913	822	365	125	1
6.3	150	B/3528-21	TC(1)OJ157B(2)LSR800	9.5	6.0	800	326	293	130	125	1
6.3	150	C/6032-28	TC(1)OJ157C(2)LSR050	9.5	8.0	50	1483	1335	593	125	1
6.3	150	C/6032-28	TC(1)OJ157C(2)LSR200	9.5	8.0	200	742	668	297	125	1
6.3	150	U/6032-15	TC(1)OJ157U(2)LSR200	9.5	8.0	200	671	604	268	125	1
6.3	150	V/7343-20	TC(1)OJ157V(2)LSR040	9.5	8.0	40	1768	1591	707	125	1
6.3	150	V/7343-20	TC(1)OJ157V(2)LSR070	9.5	8.0	70	1336	1202	534	125	1
6.3	150	V/7343-20	TC(1)OJ157V(2)LSR150	9.5	8.0	150	913	822	365	125	1
6.3	150	D/7343-31	TC(1)OJ157D(2)LSR050	9.5	6.0	50	1732	1559	693	125	1
6.3	150	D/7343-31	TC(1)OJ157D(2)LSR200	9.5	6.0	200	671	604	268	125	1
6.3	150	D/7343-31	TC(1)OJ157D(2)LSR040	9.5	8.0	40	1768	1591	707	125	1
6.3	150	D/7343-31	TC(1)OJ157D(2)LSR070	9.5	8.0	70	1336	1202	534	125	1
6.3	150	V/7343-20	TC(1)OJ157V(2)LSR150	9.5	8.0	150	913	822	365	125	1
6.3	150	D/7343-31	TC(1)OJ157D(2)LSR050	9.5	6.0	50	1732	1559	693	125	1
6.3	150	D/7343-31	TC(1)OJ157D(2)LSR065	9.5	6.0	65	1519	1367	608	125	1
6.3	150	D/7343-31	TC(1)OJ157D(2)LSR080	9.5	6.0	80	1369	1232	548	125	1
6.3	150	D/7343-31	TC(1)OJ157D(2)LSR100	9.5	6.0	100	1225	1103	490	125	1
6.3	150	D/7343-31	TC(1)OJ157D(2)LSR125	9.5	6.0	125	1095	986	438	125	1
6.3	150	E/7343-43	TC(1)OJ157E(2)LSR100	9.5	6.0	100	1285	1157	514	125	1
6.3	220	C/6032-28	TC(1)OJ227C(2)LSR225	13.9	10.0	225	699	629	280	125	1
6.3	220	C/6032-28	TC(1)OJ227C(2)LSR200	13.9	10.0	200	742	668	297	125	1
6.3	220	C/6032-28	TC(1)OJ227C(2)LSR100	13.9	10.0	100	1049	944	420	125	1
6.3	220	D/7343-31	TC(1)OJ227D(2)LSR045	13.9	8.0	45	1826	1643	730	125	1
6.3	220	D/7343-31	TC(1)OJ227D(2)LSR050	13.9	8.0	50	1732	1559	693	125	1
6.3	220	D/7343-31	TC(1)OJ227D(2)LSR100	13.9	8.0	100	1225	1103	490	125	1
6.3	220	D/7343-31	TC(1)OJ227W(2)LSR250	13.9	8.0	250	849	764	340	125	1
6.3	220	E/7343-43	TC(1)OJ227E(2)LSR070	13.9	8.0	70	1535	1382	614	125	1
6.3	220	E/7343-43	TC(1)OJ227E(2)LSR080	13.9	8.0	80	1800	1436	574	125	1
6.3	220	E/7343-43	TC(1)OJ227E(2)LSR100	13.9	8.0	100	1285	1157	514	125	1
6.3	220	V/7343-20	TC(1)OJ227V(2)LSR150	13.9	8.0	150	913	822	365	125	1
6.3	330	C/6032-28	TC(1)OJ337C(2)LSR200	20.8	18.0	200	742	668	297	125	1
6.3	330	D/7343-31	TC(1)OJ337D(2)LSR040	20.8	8.0	40	1936	1742	774	125	1
6.3	330	D/7343-31	TC(1)OJ337D(2)LSR045	20.8	8.0	45	1826	1643	730	125	1
6.3	330	D/7343-31	TC(1)OJ337D(2)LSR050	20.8	8.0	50	1732	1559	693	125	1
6.3	330	D/7343-31	TC(1)OJ337D(2)LSR070	20.8	8.0	70	1464	1318	586	125	1
6.3	330	D/7343-31	TC(1)OJ337D(2)LSR100	20.8	8.0	100	1225	1103	490	125	1
6.3	330	D/7343-31	TC(1)OJ337V(2)LSR150	20.8	8.0	150	913	822	365	125	1
6.3	330	E/7343-43	TC(1)OJ337E(2)LSR045	20.8	8.0	45	1915	1724	766	125	1
6.3	330	E/7343-43	TC(1)OJ337E(2)LSR050	20.8	8.0	50	1817	1635	727	125	1
6.3	330	E/7343-43	TC(1)OJ337E(2)LSR065	20.8	8.0	65	1593	1434	637	125	1
6.3	330	E/7343-43	TC(1)OJ337E(2)LSR080	20.8	8.0	80	1436	1292	574	125	1
6.3	330	E/7343-43	TC(1)OJ337E(2)LSR100	20.8	8.0	100	1285	1157	514	125	1
6.3	330	H/7360-38	TC(1)OJ337H(2)LSR060	20.8	8.0	60	1826	1643	730	125	1
6.3	330	H/7360-38	TC(1)OJ337H(2)LSR100	20.8	8.0	100	1414	1273	566	125	1
6.3	470	D/7343-31	TC(1)OJ477D(2)LSR045	29.6	12.0	45	1826	1643	730	125	1
6.3	470	D/7343-31	TC(1)OJ477D(2)LSR100	29.6	12.0	100	1225	1103	490	125	1
6.3	470	D/7343-31	TC(1)OJ477D(2)LSR125	29.6	12.0	125	1095	986	438	125	1



Table 3

RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	µF	CCE/EIA	(See below for part options)	µA +20°C Max/5 Min	% at+20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at+25°C 100 kHz	mA at+85°C 100 kHz	mA at+125°C 100 kHz	°C	Reflow Temp ≤ 260°C
6.3	470	D/7343-31	TC(1)OJ477D(2)LSR150	29.6	12.0	150	1000	900	400	125	1
6.3	470	D/7343-20	TC(1)OJ477V(2)LSR150	29.6	15.0	150	913	822	365	125	1
6.3	470	E/7343-43	TC(1)OJ477E(2)LSR030	29.6	10.0	30	2345	2111	938	125	1
6.3	470	E/7343-43	TC(1)OJ477E(2)LSR045	29.6	10.0	45	1915	1724	766	125	1
6.3	470	E/7343-43	TC(1)OJ477E(2)LSR050	29.6	10.0	50	1817	1635	727	125	1
6.3	470	E/7343-43	TC(1)OJ477X(2)LSR060	29.6	10.0	60	1658	1492	663	125	1
6.3	470	E/7343-43	TC(1)OJ477X(2)LSR065	29.6	10.0	65	1593	1434	637	125	1
6.3	470	E/7343-43	TC(1)OJ477X(2)LSR100	29.6	10.0	100	1285	1157	514	125	1
6.3	470	E/7343-43	TC(1)OJ477X(2)LSR125	29.6	10.0	125	1149	1034	460	125	1
6.3	470	H/7360-38	TC(1)OJ477H(2)LSR040	29.6	12.0	40	2236	2012	894	125	1
6.3	470	H/7360-38	TC(1)OJ477H(2)LSR100	29.6	10.0	55	1907	1716	763	125	1
6.3	470	H/7360-38	TC(1)OJ477H(2)LSR105	29.6	10.0	100	1414	1273	566	125	1
6.3	680	E/7343-43	TC(1)OJ687E(2)LSR100	42.8	12.0	100	1285	1157	514	125	1
6.3	680	E/7343-43	TC(1)OJ687E(2)LSR060	42.8	12.0	60	1658	1492	663	125	1
6.3	680	E/7343-43	TC(1)OJ687E(2)LSR045	42.8	12.0	45	1915	1724	766	125	1
6.3	1,000	E/7343-43	TC(1)OJ108E(2)LSR100	63.0	20.0	100	1285	1157	514	125	1
6.3	1,000	H/7360-38	TC(1)OJ108H(2)LSR050	63.0	15.0	50	2000	1800	800	125	1
6.3	1,000	H/7360-38	TC(1)OJ108H(2)LSR040	63.0	15.0	40	2236	2012	894	125	1
10	2.2	A/3216-18	TC(1)IA225A(2)LSR1K8	0.5	6.0	1,800	204	184	82	125	1
10	2.2	A/3216-18	TC(1)IA225A(2)LSR7K0	0.5	6.0	7,000	104	94	42	125	1
10	2.2	A/3216-18	TC(1)IA335A(2)LSR2K0	0.5	6.0	2,000	194	175	78	125	1
10	4.7	A/3216-18	TC(1)IA475A(2)LSR1K2	0.5	6.0	1,200	250	225	100	125	1
10	4.7	A/3216-18	TC(1)IA475A(2)LSR1K3	0.5	6.0	1,300	240	216	96	125	1
10	4.7	A/3216-18	TC(1)IA475A(2)LSR1K4	0.5	6.0	1,400	231	208	92	125	1
10	4.7	A/3216-18	TC(1)IA475A(2)LSR1K8	0.5	6.0	1,800	204	184	82	125	1
10	4.7	A/3216-18	TC(1)IA475A(2)LSR1K2	0.5	6.0	2,000	194	175	78	125	1
10	4.7	B/3528-21	TC(1)IA475B(2)LSR1K3	0.5	15.0	1,300	256	230	102	125	1
10	4.7	B/3528-21	TC(1)IA475B(2)LSR1K5	0.5	6.0	1,500	238	214	95	125	1
10	6.8	A/3216-18	TC(1)IA685A(2)LSR1K8	0.7	6.0	1,800	204	184	82	125	1
10	6.8	B/3528-21	TC(1)IA685B(2)LSR900	0.7	6.0	900	307	276	123	125	1
10	6.8	B/3528-21	TC(1)IA685B(2)LSR1K1	0.7	6.0	1,100	278	250	111	125	1
10	6.8	B/3528-21	TC(1)IA685B(2)LSR1K2	0.7	6.0	1,200	266	239	106	125	1
10	10	A/3216-18	TC(1)IA106A(2)LSR1K8	1.0	6.0	1,800	204	184	82	125	1
10	10	A/3216-18	TC(1)IA106A(2)LSR2K0	1.0	6.0	2,000	194	175	78	125	1
10	10	A/3216-18	TC(1)IA106A(2)LSR2K5	1.0	6.0	2,500	173	156	69	125	1
10	10	A/3216-18	TC(1)IA106A(2)LSR3K8	1.0	6.0	3,800	140	126	56	125	1
10	10	B/3528-21	TC(1)IA106B(2)LSR600	1.0	6.0	600	376	338	150	125	1
10	10	B/3528-21	TC(1)IA106B(2)LSR750	1.0	6.0	750	337	303	135	125	1
10	10	B/3528-21	TC(1)IA106B(2)LSR1K2	1.0	6.0	1,200	266	239	106	125	1
10	10	B/3528-21	TC(1)IA106B(2)LSR3K0	1.0	6.0	3,000	168	151	67	125	1
10	10	C/6032-28	TC(1)IA106C(2)LSR400	1.0	6.0	400	524	472	210	125	1
10	10	T/3528-12	TC(1)IA106T(2)LSR1K5	1.0	6.0	1,500	216	194	86	125	1
10	15	A/3216-18	TC(1)IA156A(2)LSR1K0	1.5	6.0	1,000	274	247	110	125	1
10	15	A/3216-18	TC(1)IA156A(2)LSR1K8	1.5	6.0	1,800	204	184	82	125	1
10	15	B/3528-21	TC(1)IA156B(2)LSR600	1.5	6.0	600	376	338	150	125	1
10	15	B/3528-21	TC(1)IA156B(2)LSR900	1.5	6.0	900	307	276	123	125	1
10	15	B/3528-21	TC(1)IA156T(2)LSR1K2	1.5	6.0	1,200	242	218	97	125	1
10	15	B/3528-21	TC(1)IA156B(2)LSR500	1.5	6.0	500	412	371	165	125	1
10	15	C/6032-28	TC(1)IA156C(2)LSR375	1.5	6.0	375	542	488	217	125	1
10	15	C/6032-28	TC(1)IA156C(2)LSR400	1.5	6.0	400	524	472	210	125	1
10	15	C/6032-28	TC(1)IA156C(2)LSR3475	1.5	6.0	475	481	433	192	125	1
10	22	A/3216-18	TC(1)IA226A(2)LSR1K2	2.2	8.0	1,200	250	225	100	125	1
10	22	A/3216-18	TC(1)IA226A(2)LSR1K5	2.2	8.0	1,500	224	202	90	125	1
10	22	B/3528-21	TC(1)IA226B(2)LSR400	2.2	6.0	400	461	415	184	125	1
10	22	B/3528-21	TC(1)IA226B(2)LSR500	2.2	6.0	500	412	371	165	125	1
10	22	B/3528-21	TC(1)IA226B(2)LSR700	2.2	6.0	700	348	313	139	125	1
10	22	B/3528-21	TC(1)IA226B(2)LSR800	2.2	6.0	800	326	293	130	125	1
10	22	B/3528-21	TC(1)IA226B(2)LSR2K3	2.2	6.0	2,300	192	173	77	125	1
10	22	C/6032-28	TC(1)IA226C(2)LSR200	2.2	6.0	200	742	668	297	125	1
10	22	C/6032-28	TC(1)IA226C(2)LSR245	2.2	6.0	245	670	603	268	125	1
10	22	C/6032-28	TC(1)IA226C(2)LSR290	2.2	6.0	290	616	554	246	125	1
10	22	C/6032-28	TC(1)IA226C(2)LSR300	2.2	6.0	300	606	545	242	125	1
10	22	C/6032-28	TC(1)IA226C(2)LSR345	2.2	6.0	345	565	509	226	125	1
10	22	C/6032-28	TC(1)IA226C(2)LSR350	2.2	6.0	350	561	505	224	125	1
10	22	C/6032-28	TC(1)IA226C(2)LSR380	2.2	6.0	380	538	484	215	125	1

## RATINGS &amp; PART NUMBER REFERENCE

Table 4

RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	µF	CCE/EIA	(See below for part options)	µA +20°C Max/5 Min	% at+20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at+25°C 100 kHz	mA at+85°C 100 kHz	mA at+125°C 100 kHz	°C	Reflow Temp ≤ 260°C
10	33	B/3528-21	TC(1)IA336B(2)LSR450	3.3	6.0	450	435	392	174	125	1
10	33	B/3528-21	TC(1)IA336B(2)LSR550	3.3	6.0	550	393	354	157	125	1
10	33	B/3528-21	TC(1)IA336B(2)LSR650	3.3	6.0	650	362	326	145	125	1
10	33	V/7343-20	TC(1)IA336V(2)LSR100	3.3	6.0	100	1118	1006	447	125	1
10	33	V/7343-20	TC(1)IA336V(2)LSR150	3.3	6.0	150	913	822	365	125	1
10	47	B/3528-21	TC(1)IA476B(2)LSR500	4.7	6.0	500	412	371	165	125	1
10	47	B/3528-21	TC(1)IA476B(2)LSR650	4.7	6.0	650	362	326	145	125	1
10	47	C/6032-28	TC(1)IA476C(2)LSR300	4.7	6.0	300	606	545	242	125	1
10	47	U/6032-15	TC(1)IA476U(2)LSR400	4.7	6.0	400	474	427	190	125	1
10	47	D/7343-31	TC(1)IA476D(2)LSR080	4.7	4.0	80	1369	1232	548	125	1
10	47	D/7343-31	TC(1)IA476D(2)LSR090	4.7	6.0	90	1291	1162	516	125	1
10	47	D/7343-31	TC(1)IA476D(2)LSR100	4.7	6.0	100	1225	1103	490	125	1
10	47	D/7343-31	TC(1)IA476D(2)LSR200	4.7	4.0	200	866	779	346	125	1
10	47	V/7343-20	TC(1)IA476V(2)LSR200	4.7	6.0	200	791	712	316	125	1
10	68	B/3528-21	TC(1)IA686B(2)LSR600	6.8	8.0	600	376	338	150	125	1
10	68	B/3528-21	TC(1)IA686B(M)LSR900	6.8	8.0	750	337	303	135	125	1
10	68	C/6032-28	TC(1)IA686C(2)LSR080	6.8	6.0	80	307	276	123	125	1
10	68	C/6032-28	TC(1)IA686C(2)LSR200	6.8	6.0	200	1173	1056	469	125	1
10	68	C/6032-28	TC(1)IA686C(2)LSR225	6.8	6.0	225	742	668	297	125	1
10	68	C/6032-28	TC(1)IA686C(2)LSR250	6.8	6.0	250	663	597	265	125	1
10	68	V/7343-20	TC(1)IA686V(2)LSR070	6.8	6.0	70	1335	1202	534	125	1
10	68	V/7343-20	TC(1)IA686V(2)LSR100	6.8	6.0	100	1118	1006	447	125	1
10	68	V/7343-20	TC(1)IA686V(2)LSR140	6.8	6.0	140	945	851	378	125	1
10	68	V/7343-20	TC(1)IA686V(2)LSR200	6.8	6.0	200	791	712	316	125	1
10	68	D/7343-31	TC(1)IA686D(2)LSR070	6.8	6.0	70	1464	1318	586	125	1
10	68	D/7343-31	TC(1)IA686D(2)LSR090	6.8	6.0	90	1291	1162	516	125	1
10	68	D/7343-31	TC(1)IA686D(2)LSR100	6.8	6.0	100	1225	1103	490	125	1
10	68	D/7343-31	TC(1)IA686D(2)LSR150	6.8	6.0	150	1000	900	400	125	1
10	68	E/7343-43	TC(1)IA686E(2)LSR150	6.8	4.0	150	1049	944	420	125	1
10	100	B/3528-21	TC(M)IA107B(2)LSR350	10.0	12.0	350	493	444	197	125	1
10	100	B/3528-21	TC(M)IA107B(2)LSR500	10.0	30.0	500	412	371	165	125	1
10	100	B/3528-21	TC(M)IA107B(2)LSR700	10.0	30.0	700	348	313	139	125	1
10	100	C/6032-28	TC(1)IA107C(2)LSR100	10.0	8.0	100	1050	945	420	125	1
10	100	C/6032-28	TC(1)IA107C(2)LSR150	10.0	8.0	150	856	812	542	125	1
10	100	C/6032-28	TC(1)IA107C(2)LSR180	10.0	8.0	180	782	704	313	125	1
10	100	C/6032-28	TC(1)IA107C(2)LSR200	10.0	8.0	200	742	668	297	125	1
10	100	C/6032-28	TC(1)IA107C(2)LSR250	10.0	8.0	250	663	597	265	125	1
10	100	U/6032-15	TC(1)IA107U(2)LSR150	10.0	8.0	150	775	698	310	125	1
10	100	W/7343-15	TC(1)IA107W(2)LSR200	10.0	8.0	200	949	854	380	125	1
10	100	V/7343-20	TC(1)IA107V(2)LSR100	10.0	8.0	100	1118	1006	447	125	1
10	100	V/7343-20	TC(1)IA107V(2)LSR150	10.0	8.0	150	913	822	365	125	1
10	100	V/7343-20	TC(1)IA107V(2)LSR200	10.0	8.0	200	791	712	316	125	1
10	100	D/7343-31	TC(1)IA107D(2)LSR050	10.0	8.0	50	1732	1559	693	125	1
10	100	D/7343-31	TC(1)IA107D(2)LSR065	10.0	8.0	65	1519	1367	608	125	1
10	100	D/7343-31	TC(1)IA107D(2)LSR080	10.0	8.0	80	1369	1232	548	125	1
10	100	D/7343-31	TC(1)IA107D(2)LSR100	10.0	8.0	100	1225	1103	490	125	1
10	100	D/7343-31	TC(1)IA107D(2)LSR120	10.0	8.0	120	1118	1006	447	125	1
10	100	D/7343-31	TC(1)IA107D(2)LSR125	10.0	8.0	125	1095	986	438	125	1
10	100	E/7343-43	TC(1)IA107E(2)LSR100	10.0	6.0	100	1285	1157	514	125	1
10	150	C/6032-28	TC(1)IA157C(2)LSR200	15.0	10.0	200	742	668	297	125	1
10	150	V/7343-20	TC(1)IA157C(2)LSR100	15.0	8.0	100	1118	1006	447	125	1
10	150	V/7343-20	TC(1)IA157C(2)LSR150	15.0	8.0	150	913	822	365	125	1
10	150	V/7343-20	TC(1)IA157C(2)LSR200	15.0	8.0	200	791	712	316	125	1
10	150	D/7343-31	TC(1)IA157D(2)LSR050	15.0	8.0	50	1732	1559	693	125	1
10	150	D/7343-31	TC(1)IA157D(2)LSR060	15.0	8.0	60	1581	1423	632	125	1
10	150	D/7343-31	TC(1)IA157D(2)LSR080	15.0	8.0	80	1369	1232	548	125	1
10	150	D/7343-31	TC(1)IA157D(2)LSR100	15.0	8.0	100	1225	1103	490	125	1
10	150	E/7343-43	TC(1)IA157E(2)LSR070	15.0	8.0	70	1535	1382	614	125	1
10	150	E/7343-43	TC(1)IA157E(2)LSR080	15.0	8.0	80	1436	1292	574	125	1
10	150	E/7343-43	TC(1)IA157E(2)LSR085	15.0	8.0	85	1393	1254	557	125	1
10	150	E/7343-43	TC(1)IA157E(2)LSR100	15.0	8.0	100	1285	1157	514	125	1
10	220	D/7343-31	TC(1)IA227D(2)LSR045	22.0	8.0	45	1826	1643	730	125	1
10	220	D/7343-31	TC(1)IA227D(2)LSR050	22.0	9.0	50	1732	1559	693	125	1
10	220	D/7343-31	TC(1)IA227D(2)LSR075	22.0	8.0	75	1414	1273	566	125	1



## RATINGS &amp; PART NUMBER REFERENCE

Table 5

RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	µF	CCE/EIA	(See below for part options)	µA +20°C Max/5 Min	% at+20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at+25°C 100 kHz	mA at+85°C 100 kHz	mA at+125°C 100 kHz	°C	Reflow Temp ≤ 260°C
10	220	D/7343-31	TC(1)IA227D(2)LSR100	22.0	8.0	100	1225	1103	490	125	1
10	220	D/7343-31	TC(1)IA227D(2)LSR125	22.0	8.0	125	1095	986	438	125	1
10	220	V/7343-20	TC(1)IA227V(2)LSR150	22.0	10.0	150	913	822	365	125	1
10	220	V/7343-20	TC(1)IA227V(2)LSR200	22.0	10.0	200	791	712	316	125	1
10	220	E/7343-43	TC(1)IA227E(2)LSR045	22.0	8.0	45	1915	1724	766	125	1
10	220	E/7343-43	TC(1)IA227E(2)LSR050	22.0	8.0	50	1817	1635	727	125	1
10	220	E/7343-43	TC(1)IA227E(2)LSR060	22.0	8.0	60	1658	1492	663	125	1
10	220	E/7343-43	TC(1)IA227E(2)LSR070	22.0	8.0	70	1535	1382	614	125	1
10	220	E/7343-43	TC(1)IA227E(2)LSR080	22.0	8.0	80	1436	1292	574	125	1
10	220	E/7343-43	TC(1)IA227E(2)LSR100	22.0	8.0	100	1285	1157	514	125	1
10	330	D/7343-31	TC(1)IA337D(2)LSR100	33.0	8.0	100	1225	1103	490	125	1
10	330	D/7343-31	TC(1)IA337D(2)LSR125	33.0	10.0	125	1095	986	438	125	1
10	330	D/7343-31	TC(1)IA337D(2)LSR150	33.0	10.0	150	1000	900	400	125	1
10	330	E/7343-43	TC(1)IA337E(2)LSR035	33.0	10.0	35	2171	1954	868	125	1
10	330	E/7343-43	TC(1)IA337E(2)LSR040	33.0	10.0	40	2031	1828	812	125	1
10	330	E/7343-43	TC(1)IA337E(2)LSR050	33.0	10.0	50	1817	1635	727	125	1
10	330	E/7343-43	TC(1)IA337E(2)LSR060	33.0	10.0	60	1658	1492	663	125	1
10	330	E/7343-43	TC(1)IA337E(2)LSR080	33.0	10.0	80	1436	1292	574	125	1
10	330	E/7343-43	TC(1)IA337E(2)LSR100	33.0	10.0	100	1285	1157	514	125	1
10	330	H/7360-38	TC(1)IA337H(2)LSR040	33.0	8.0	40	2236	2012	894	125	1
10	330	H/7360-38	TC(1)IA337H(2)LSR060	33.0	10.0	60	1826	1643	730	125	1
10	330	H/7360-38	TC(1)IA337H(2)LSR100	33.0	10.0	100	1414	1273	566	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR045	47.0	10.0	45	1915	1724	766	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR050	47.0	10.0	50	1817	1635	727	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR060	47.0	10.0	60	1658	1492	663	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR080	47.0	10.0	80	1436	1292	574	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR100	47.0	10.0	100	1285	1157	514	125	1
10	470	H/7360-38	TC(1)IA477H(2)LSR040	47.0	10.0	40	2236	2012	894	125	1
10	470	H/7360-38	TC(1)IA477H(2)LSR060	47.0	10.0	60	1826	1643	730	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR100	47.0	10.0	100	1414	1273	566	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR100	47.0	10.0	100	1285	1157	514	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR200	47.0	10.0	200	908	817	363	125	1
10	470	H/7360-38	TC(1)IA477H(2)LSR040	47.0	10.0	40	2236	2012	894	125	1
10	470	H/7360-38	TC(1)IA477H(2)LSR060	47.0	10.0	60	1826	1643	730	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR080	47.0	10.0	80	1436	1292	574	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR100	47.0	10.0	100	1285	1157	514	125	1
10	470	E/7343-43	TC(1)IA477E(2)LSR200	47.0	10.0	200	908	817	363	125	1
10	470	H/7360-38	TC(1)IA477H(2)LSR040	47.0	10.0	40	2236	2012	894	125	1
10	470	H/7360-38	TC(1)IA477H(2)LSR060	47.0	10.0	60	1826	1643	730	125	1
16	1	A/3216-18	TC(1)IA105A(2)LSR500	0.5	6.0	5,000	1414	1273	566	125	1
16	1.5	A/3216-18	TC(1)IC155A(2)LST5K0	0.5	6.0	5,000	122	110	49	125	1
16	2.2	A/3216-18	TC(1)IC225A(2)LSR5K	0.5	6.0	2,500	173	156	69	125	1
16	2.2	A/3216-18	TC(1)IC225A(2)LSR1K8	0.5	6.0	1,800	204	184	82	125	1
16	3.3	A/3216-18	TC(1)IC335A(2)LSR3K0	0.5	6.0	3,000	158	142	63	125	1
16	3.3	B/3528-21	TC(1)IC335B(2)LSR2K0	0.5	6.0	2,000	206	185	82	125	1
16	4.7	A/3216-18	TC(1)IC475A(2)LSR2K0	0.8	6.0	2,000	194	175	78	125	1
16	4.7	B/3528-21	TC(1)IC475B(2)LSR700	0.8	6.0	700	348	313	139	125	1
16	4.7	B/3528-21	TC(1)IC475B(2)LSR800	0.8	6.0	800	326	293	130	125	1
16	4.7	B/3528-21	TC(1)IC475B(2)LSR1K0	0.8	6.0	1,000	292	263	117	125	1
16	4.7	B/3528-21	TC(1)IC475B(2)LSR1K5	0.8	6.0	1,500	238	214	95	125	1
16	6.8	B/3528-21	TC(1)IC685B(2)LSR1K2	1.1	6.0	1,200	266	239	106	125	1
16	6.8	C/6032-28	TC(1)IC685C(2)LSR750	1.1	6.0	750	383	345	153	125	1
16	10	A/3216-18	TC(1)IC106A(2)LSR1K7	1.6	6.0	1,700	210	189	84	125	1
16	10	B/3528-21	TC(1)IC106B(2)LSR500	1.6	6.0	500	412	371	165	125	1
16	10	B/3528-21	TC(1)IC106B(2)LSR650	1.6	6.0	650	362	326	145	125	1
16	10	B/3528-21	TC(1)IC106B(2)LSR800	1.6	6.0	800	326	293	130	125	1
16	10	B/3528-21	TC(1)IC106B(2)LSR2K5	1.6	6.0	2,500	184	166	74	125	1
16	10	T/3528-12	TC(1)IC106T(2)LSR4K0	1.6	8.0	4,000	132	119	53	125	1
16	15	A/3216-18	TC(1)IC156A(2)LSR2K5	2.4	8.0	2,500	173	156	69	125	1
16	15	B/3528-21	TC(1)IC156B(2)LSR500	2.4	6.0	412	371	313	165	125	1
16	15	B/3528-21	TC(1)IC156B(2)LSR650	2.4	6.0	650	362	326	145	125	1
16	15	B/3528-21	TC(1)IC156B(2)LSR800	2.4	6.0	800	326	293	130	125	1
16	15	C/6032-28	TC(1)IC156C(2)LSR400	2.4	6.0	400	524	472	210	125	1
16	22	B/3528-21	TC(1)IC226B(2)LSR600	3.5	6.0	600	376	338	150	125	1
16	22	B/3528-21	TC(1)IC226B(2)LSR700	3.5	6.0	700	348	313	139	125	1
16	22	C/6032-28	TC(1)IC226C(2)LSR300	3.5	6.0	300	606	545	242	125	1
16	22	C/6032-28	TC(1)IC226C(2)LSR350	3.5	6.0	350	561	505	224	125	1
16	22	C/6032-28	TC(1)IC226C(2)LSR500	3.5	6.0	500	469	422	188	125	1
16	33	C/6032-28	TC(1)IC336C(2)LSR200	5.3	6.0	200	742	668	297	125	1
16	33	C/6032-28	TC(1)IC336C(2)LSR225	5.3	6.0	225	699	629	280	125	1
16	33	C/6032-28	TC(1)IC336C(2)LSR230	5.3	6.0	230	692	623	277	125	1
16	33	C/6032-28	TC(1)IC336C(2)LSR275	5.3	6.0	275	632	569	253	125	1
16	33	C/6032-28	TC(1)IC336C(2)LSR300	5.3	6.0	300	606	545	242	125	1

## RATINGS &amp; PART NUMBER REFERENCE

Table 6

RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	µF	CCE/EIA	(See below for part options)	µA +20°C Max/5 Min	% at+20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at+25°C 100 kHz	mA at+85°C 100 kHz	mA at+125°C 100 kHz	°C	Reflow Temp ≤ 260°C
16	33	U/6032-15	TC(1)IC336U(2)LSR200	5.3	6.0	200	671	604	268	125	1
16	33	U/6032-15	TC(1)IC336U(2)LSR400	5.3	6.0	400	474	427	190	125	1
16	33	B/3528-21	TC(1)IC336B(2)LSR350	5.3	6.0	350	493	444	197	125	1
16	33	D/7343-31	TC(1)IC336D(2)LSR150	5.3	6.0	150	1000	900	400	125	1
16	33	D/7343-31	TC(1)IC336D(2)LSR175	5.3	6.0	175	926	833	370	125	1
16	33	D/7343-31	TC(1)IC336D(2)LSR200	5.3	6.0	200	866	779	346	125	1
16	33	D/7343-31	TC(1)IC336D(2)LSR225	5.3	4.0	225	816	734	326	125	1
16	33	D/7343-31	TC(1)IC336D(2)LSR250	5.3	6.0	250	775	698	310	125	1
16	47	C/6032-28	TC(1)IC476C(2)LSR300	7.5	6.0	300	606	545	242	125	1
16	47	C/6032-28	TC(1)IC476C(2)LSR350	7.5	6.0	350	561	505	224	125	1
16	47	D/7343-31	TC(1)IC476D(2)LSR080	7.5	6.0	80	1369	1232	548	125	1
16	47	D/7343-31	TC(1)IC476D(2)LSR100	7.5	6.0	100	1225	1103	490	125	1
16	47	D/7343-31	TC(1)IC476D(2)LSR150	7.5	6.0	150	1000	900	400	125	1
16	47	D/7343-31	TC(1)IC476D(2)LSR180	7.5	6.0	180	913	822	365	125	1
16	47	D/7343-31	TC(1)IC476D(2)LSR800	7.5	6.0	800	433	390	173	125	1
16	68	C/6032-28	TC(1)IC686C(2)LSR250	10.9	6.0	250	663	597	265	125	1
16	68	C/6032-28	TC(1)IC686C(2)LSR200	10.9	6.0	200	742	668	297	125	1
16	68	C/6032-28	TC(1)IC686C(2)LSR180	10.9	6.0	180	782	704	313	125	1
16	68	V/7343-20	TC(1)IC686V(2)LSR180	10.9	6.0	180	833	750	333	125	1
16	68	V/7343-20	TC(1)IC686V(2)LSR250	10.9	6.0	250	707	636	283	125	1
16	68	V/7343-20	TC(1)IC686E(2)LSR180	10.9	6.0	300	645	581	258	125	1
16	68	D/7343-31	TC(1)IC686D(2)LSR070	10.9	6.0	70	1464	1318	586	125	1
16	68	D/7343-31	TC(1)IC686D(2)LSR100	10.9	6.0	100	1225	1103	490	125	1
16	68	D/7343-31	TC(1)IC686D(2)LSR150	10.9	6.0	150	1000	900	400	125	1
16	68	E/7343-43	TC(1)IC686E(2)LSR150	10.9	5.0	150	1049	944	420	125	1
16	100	C/6032-28	TC(1)IC107C(2)LSR200	16.0	10.0	200	742	668	297	125	1
16	100	D/7343-31	TC(1)IC107D(2)LSR060	16.0	8.0	60	1581	1423	632	125	1
16	100	D/7343-31	TC(1)IC107D(2)LSR100	16.0	8.0	100	1225	1103	490	125	1
16	100	D/7343-31	TC(1)IC107D(2)LSR125	16.0	8.0	125	1095	986	438	125	1
16	100	D/7343-31	TC(1)IC107D(2)LSR130	16.0	8.0	130	1074	967	430	125	1
16	100	D/7343-31	TC(1)IC107D(2)LSR150	16.0	8.0	150	1000	900	400	125	1
16	100	D/7343-31	TC(1)IC107D(2)LSR800	16.0	8.0	800	433	390	173	125	1
16	100	E/7343-43	TC(1)IC107E(2)LSR080	16.0	8.0	80	1436	1292	574	125	1
16	100	E/7343-43	TC(1)IC107E(2)LSR100	16.0	8.0	100	1285	1157	514	125	1
16	150	D/7343-31	TC(1)IC157D(2)LSR060	24.0	12.0	60	1581	1423	632	125	1
16	150	D/7343-31	TC(1)IC157D(2)LSR085	24.0	8.0	85	1328	1195	531	125	1
16	150	D/7343-31	TC(1)IC157D(2)LSR100	24.0	8.0	100	1225	1103	490	125	1
16	150	D/7343-31	TC(1)IC157D(2)LSR125	24.0	8.0	125	1095	986	438	125	1
16	150	D/7343-31	TC(1)IC157D(2)LSR130	24.0	8.0	130	1074	967	430	125	1
16	150	D/7343-31	TC(1)IC157D(2)LSR150	24.0	8.0	150	1000	900	400	125	1
16	150	E/7343-43	TC(1)IC157E(2)LSR075	24.0	8.0	75	1483	1335	593	125	1
16	150	E/7343-43	TC(1)IC157E(2)LSR100	24.0	8.0	100	1285	1157	514	125	1
16	220	D/7343-31	TC(1)IC227D(2)LSR150	35.2	12.0	150	1000	900	400	125	1
16	220	D/7343-31	TC(1)IC227D(2)LSR200	35.2	12.0	200	866	779	346	125	1
16	220	D/7343-31	TC(1)IC227D(2)LSR220	35.2	12.0	220	826	743	330	125	1
16	220	E/7343-43	TC(1)IC227E(2)LSR100	35.2	8.0	100	1285	1157	514	125	1
16	220	H/7360-38	TC(1)IC227H(2)LSR050	35.2	12.0	50	2000	1800	800	125	1
16	220	H/7360-38	TC(1)IC227H(2)LSR075	35.2	8.0	75	1633	1470	653	125	1
16	220	H/7360-38	TC(1)IC227H(2)LSR100	35.2	7.2	100	1414	1273	566	125	1
16	220	H/7360-38	TC(1)IC227H(2)LSR150	35.2	7.2	150	1155	1040	462	125	1
20	1	A/3216-18	TC(1)ID105A(2)LSR3K0	0.5	4.0	3,000	158	142	63	125	1
20	1	A/3216-18	TC(1)ID105A(2)LSR5K0	0.5	4.0	5,000	122	110	49	125	1
20	2.2	A/3216-18	TC(1)ID225A(2)LSR3K0	0.5	6.0	3,000	158	142	63	125	1
20	4.7	A/3216-18	TC(1)ID475A(2)LSR1K8	0.9	6.0	1,800	204	184	82	125	1
20	4.7	A/3216-18	TC(1)ID475A(2)LSR1K0	0.9	6.0	2,000	194	175	78	125	1
20	4.7	B/3528-21	TC(1)ID475B(2)LSR750	0.9	6.0	750	337	303	135	125	1
20	4.7	B/3528-21	TC(1)ID475B(2)LSR1K0	0.9	6.0	1,000	292	263	117	125	1
20	6.8	C/6032-28	TC(1)ID685C(2)LSR480	1.4	6.0	480	479	431	192	125	1
20	10	C/6032-28	TC(1)ID106B(2)LSR1K0	2.0	6.0	1,000	292	263	117	125	1
20	10	C/6032-28	TC(1)ID106B(2)LSR800	2.0	6.0	800	326	293	130	125	1
20	10	C/6032-28	TC(1)ID106C(2)LSR300	2.0	6.0	300	606	545	242	125	1
20	10	C/6032-28	TC(1)ID106C(2)LSR350	2.0	6.0	350	561	505	224	125	1
20	10	C/6032-28	TC(1)ID106C(2)LSR400	2.0	6.0	400	524	472	210	125	1
20	10	C/6032-28	TC(1)ID106C(2)LSR450	2.0	6.0	450	494	445	198	125	1
20	10	C/6032-28	TC(1)ID106C(2)LSR475	2.0	6.0	475	481	433	192	125	1

## RATINGS &amp; PART NUMBER REFERENCE

Table 7

RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	µF	CCE/EIA	(See below for part options)	µA +20°C Max/5 Min	% at+20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at+25°C 100 kHz	mA at+85°C 100 kHz	mA at+125°C 100 kHz	°C	Reflow Temp ≤ 260°C
20	15	C/6032-28	TC(1)ID156C(2)LSR375	3.0	6.0	375	542	488	217	125	1
20	15	C/6032-28	TC(1)ID156C(2)LSR400	3.0	6.0	400	524	472	210	125	1
20	15	D/7343-31	TC(1)ID156D(2)LSR1K2	3.0	4.0	275	739	665	296	125	1
20	15	D/7343-31	TC(1)ID156D(2)LSR1K2	3.0	4.0	1,200	354	319	142	125	1
20	22	D/7343-31	TC(1)ID226D(2)LSR180	4.4	4.0	180	913	822	365	125	1
20	22	D/7343-31	TC(1)ID226D(2)LSR200	4.4	4.0	200	866	779	346	125	1
20	22	D/7343-31	TC(1)ID226D(2)LSR225	4.4	4.0	225	816	734	326	125	1
20	22	V/7343-20	TC(1)ID226V(2)LSR400	4.4	6.0	400	559	503	224	125	1
20	33	C/6032-28	TC(1)ID336C(2)LSR200	6.6	6.0	200	742	668	297	125	1
20	33	D/7343-31	TC(1)ID336D(2)LSR100	6.6	6.0	100	1225	1103	490	125	1
20	33	D/7343-31	TC(1)ID336D(2)LSR150	6.6	6.0	150	1000	900	400	125	1
20	33	D/7343-31	TC(1)ID336D(2)LSR200	6.6	6.0	200	866	779	346	125	1
20	33	E/7343-43	TC(1)ID336E(2)LSR200	6.6	6.0	200	908	817	363	125	1
20	47	D/7343-31	TC(1)ID476D(2)LSR075	9.4	6.0	75	1414	1273	566	125	1
20	47	D/7343-31	TC(1)ID476D(2)LSR100	9.4	6.0	100	1225	1103	490	125	1
20	47	D/7343-31	TC(1)ID476D(2)LSR150	9.4	6.0	150	1000	900	400	125	1
20	47	D/7343-31	TC(1)ID476D(2)LSR175	9.4	6.0	175	926	833	370	125	1
20	47	D/7343-31	TC(1)ID476D(2)LSR200	9.4	6.0	200	866	779	346	125	1
20	47	D/7343-31	TC(1)ID476D(2)LSR250	9.4	6.0	250	775	698	310	125	1
20	47	E/7343-43	TC(1)ID476E(2)LSR065	9.4	8.0	65	1593	1434	637	125	1
20	47	E/7343-43	TC(1)ID476E(2)LSR070	9.4	6.0	70	1535	1382	614	125	1
20	47	E/7343-43	TC(1)ID476E(2)LSR100	9.4	6.0	100	1285	1157	514	125	1
20	47	E/7343-43	TC(1)ID476E(2)LSR125	9.4	6.0	125	1149	1034	460	125	1
20	47	E/7343-43	TC(1)ID476E(2)LSR130	9.4	6.0	130	1127	1014	451	125	1
20	47	E/7343-43	TC(1)ID476E(2)LSR150	9.4	40	150	1049	944	420	125	1
20	68	C/6032-28	TC(1)ID686C(2)LSR250	13.6	8.0	250	663	597	265	125	1
20	68	D/7343-31	TC(1)ID686D(2)LSR070	13.6	6.0	70	1464	1318	586	125	1
20	68	D/7343-31	TC(1)ID686D(2)LSR100	13.6	6.0	100	1225	1103	490	125	1
20	68	D/7343-31	TC(1)ID686D(2)LSR150	13.6	6.0	150	1000	900	400	125	1
20	68	D/7343-31	TC(1)ID686D(2)LSR200	13.6	6.0	200	866	779	346	125	1
20	68	D/7343-31	TC(1)ID686D(2)LSR300	13.6	6.0	300	707	636	283	125	1
20	68	E/7343-43	TC(1)ID686E(2)LSR120	13.6	6.0	120	1173	1056	469	125	1
20	68	E/7343-43	TC(1)ID686E(2)LSR130	13.6	6.0	130	1127	1014	451	125	1
20	68	E/7343-43	TC(1)ID686E(2)LSR150	13.6	6.0	150	1049	944	420	125	1
20	68	E/7343-43	TC(1)ID686E(2)LSR200	13.6	6.0	200	908	817	363	125	1
20	100	D/7343-31	TC(1)ID107D(2)LSR200	20.0	6.0	200	866	779	346	125	1
20	100	E/7343-43	TC(1)ID107E(2)LSR100	20.0	6.0	100	1285	1157	514	125	1
20	100	E/7343-43	TC(1)ID107E(2)LSR150	20.0	8.0	150	1049	944	420	125	1
20	100	H/7360-38	TC(1)ID107H(2)LSR080	20.0	8.0	60	1826	1643	730	125	1
20	100	H/7360-38	TC(1)ID107H(2)LSR085	20.0	8.0	85	1534	1381	614	125	1
20	100	H/7360-38	TC(1)ID107H(2)LSR100	20.0	8.0	100	1414	1273	566	125	1
20	100	H/7360-38	TC(1)ID107H(2)LSR200	20.0	8.0	200	1000	900	400	125	1
20	150	H/7360-38	TC(1)ID157H(2)LSR080	30.0	8.0	80	1581	1423	632	125	1
25	0.47	A/3216-18	TC(1)IE474A(2)LSR4K5	0.5	4.0	4,500	129	116	52	125	1
25	0.47	A/3216-18	TC(1)IE474A(2)LSR7K0	0.5	4.0	7,000	104	94	42	125	1
25	1	A/3216-18	TC(1)IE105A(2)LSR2K5	0.5	4.0	2,500	173	156	69	125	1
25	1	A/3216-18	TC(1)IE105A(2)LSR3K0	0.5	4.0	3,000	158	142	63	125	1
25	1	A/3216-18	TC(1)IE105A(2)LSR4K0	0.5	4.0	4,000	137	123	55	125	1
25	1	A/3216-18	TC(1)IE105A(2)LSR5K0	0.5	4.0	5,000	122	110	49	125	1
25	1.5	A/3216-18	TC(1)IE155A(2)LSR3K0	0.5	6.0	3,000	158	142	63	125	1
25	2.2	B/3528-21	TC(1)IE225B(2)LSR1K2	0.6	4.0	1,200	266	239	106	125	1
25	2.2	C/6032-28	TC(1)IE225C(2)LSR1K3	0.6	6.0	1,300	291	262	116	125	1
25	3.3	B/3528-21	TC(1)IE335B(2)LSR1K2	0.8	6.0	1,200	266	239	106	125	1
25	3.3	C/6032-28	TC(1)IE335C(2)LSR750	0.8	6.0	750	383	345	153	125	1
25	4.7	C/6032-28	TC(1)IE475C(2)LSR530	1.2	6.0	530	456	410	182	125	1
25	4.7	C/6032-28	TC(1)IE475C(2)LSR575	1.2	6.0	575	437	393	175	125	1
25	4.7	B/3528-21	TC(1)IE475B(2)LSR700	1.2	6.0	700	348	313	139	125	1
25	4.7	B/3528-21	TC(1)IE475B(2)LSR750	1.2	6.0	750	337	303	135	125	1
25	4.7	B/3528-21	TC(1)IE475B(2)LSR800	1.2	6.0	800	326	293	130	125	1
25	4.7	B/3528-21	TC(1)IE475B(2)LSR900	1.2	6.0	900	307	276	123	125	1
25	4.7	B/3528-21	TC(1)IE475B(2)LSR1K0	1.2	6.0	1,000	292	263	117	125	1
25	6.8	B/3528-21	TC(1)IE685B(2)LSR1K0	1.7	6.0	1,000	292	263	117	125	1
25	6.8	B/3528-21	TC(1)IE685B(2)LSR1K5	1.7	6.0	1,500	238	214	95	125	1
25	6.8	C/6032-28	TC(1)IE685C(2)LSR400	1.7	6.0	400	524	472	210	125	1
25	6.8	C/6032-28	TC(1)IE685C(2)LSR490	1.7	6.0	490	474	427	190	125	1

## RATINGS &amp; PART NUMBER REFERENCE

Table 8

RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	µF	CCE/EIA	(See below for part options)	µA +20°C Max/5 Min	% at+20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at+25°C 100 kHz	mA at+85°C 100 kHz	mA at+125°C 100 kHz	°C	Reflow Temp ≤ 260°C
25	6.8	C/6032-28	TC(1)IE685C(2)LSR500	1.7	6.0	500	469	422	188	125	1
25	10	B/3528-21	TC(1)IE106B(2)LSR750	2.5	6.0	750	337	303	135	125	1
25	10	C/6032-28	TC(1)IE106C(2)LSR275	2.5	6.0	275	632	569	253	125	1
25	10	C/6032-28	TC(1)IE106C(2)LSR300	2.5	6.0	300	606	545	242	125	1
25	10	C/6032-28	TC(1)IE106C(2)LSR450	2.5	6.0	450	494	445	198	125	1
25	10	D/7343-31	TC(1)IE106D(2)LSR1K2	2.5	6.0	1,200	354	319	142	125	1
25	15	C/6032-28	TC(1)IE156C(2)LSR300	3.8	6.0	300	606	545	242	125	1
25	15	D/7343-31	TC(1)IE156D(2)LSR100	3.8	6.0	100	1225	1103	490	125	1
25	15	D/7343-31	TC(1)IE156D(2)LSR230	3.8	4.0	230	808	727	323	125	1
25	15	D/7343-31	TC(1)IE156D(2)LSR275	3.8	6.0	275	739	665	296	125	1
25	15	V/7343-20	TC(1)IE156V(2)LSR500	3.8	6.0	500	500	450	200	125	1
25	15	E/7343-43	TC(1)IE156E(2)LSR200	3.8	4.0	200	908	817	363	125	1
25	22	C/6032-28	TC(1)IE226C(2)LSR275	5.5	6.0	275	632	569	253	125	1
25	22	C/6032-28	TC(1)IE226C(2)LSR280	5.5	6.0	280	627	564	251	125	1
25	22	C/6032-28	TC(1)IE226C(2)LSR300	5.5	8.0	300	606	545	242	125	1
25	22	C/6032-28	TC(1)IE226C(2)LSR900	5.5	6.0	900	350	315	140	125	1
25	22	D/7343-31	TC(1)IE226D(2)LSR200	5.5	6.0	200	866	779	346	125	1
25	22	D/7343-31	TC(1)IE226D(2)LSR230	5.5	6.0	230	808	727	323	125	1
25	22	E/7343-43	TC(1)IE226E(2)LSR225	5.5	4.0	225	856	770	342	125	1
25	33	D/7343-31	TC(1)IE336D(2)LSR090	8.3	6.0	90	1291	1162	516	125	1
25	33	D/7343-31	TC(1)IE336D(2)LSR100	8.3	6.0	100	1225	1103	490	125	1
25	33	D/7343-31	TC(1)IE336D(2)LSR150	8.3	6.0	150	1000	900	400	125	1
25	33	D/7343-31	TC(1)IE336D(2)LSR200	8.3	6.0	200	866	779	346	125	1
25	33	D/7343-31	TC(1)IE336D(2)LSR225	8.3	6.0	225	816	734	326	125	1
25	33	D/7343-31	TC(1)IE336D(2)LSR230	8.3	6.0	230	808	727	323	125	1
25	33	D/7343-31	TC(1)IE336D(2)LSR300	8.3	6.0	300	707	636	283	125	1
25	33	E/7343-43	TC(1)IE336E(2)LSR100	8.3	4.0	100	1285	1157	514	125	1
25	33	E/7343-43	TC(1)IE336E(2)LSR175	8.3	4.0	175	971	874	388	125	1
25	33	E/7343-43	TC(1)IE336E(2)LSR180	8.3	4.0	180	957	861	383	125	1
25	33	E/7343-43	TC(1)IE336E(2)LSR200	8.3	4.0	200	908	817	363	125	1
25	47	E/7343-43	TC(1)IE476E(2)LSR080	11.8	6.0	80	1436	1292	574	125	1
25	47	E/7343-43	TC(1)IE476E(2)LSR100	11.8	6.0	100	1285	1157	514	125	1
25	47	E/7343-43	TC(1)IE476E(2)LSR120	11.8	6.0	120	1173	1056	469	125	1
25	47	E/7343-43	TC(1)IE476E(2)LSR150	11.8	6.0	150	1049	944	420	125	1
25	47	E/7343-43	TC(1)IE476E(2)LSR185	11.8	6.0	185	944	850	378	125	1
25	47	E/7343-43	TC(1)IE476E(2)LSR200	11.8	6.0	200	908	817	363	125	1
25	47	D/7343-31	TC(1)IE476D(2)LSR100	11.8	6.0	100	1225	1103	490	125	1
25	47	D/7343-31	TC(1)IE476D(2)LSR120	11.8	6.0	120	1118	1006	447	125	1
25	47	D/7343-31	TC(1)IE476D(2)LSR130	11.8	6.0	130	1074	967	430	125	1
25	47	D/7343-31	TC(1)IE476D(2)LSR150	11.8	6.0	150	1000	900	400	125	1
25	47	D/7343-31	TC(1)IE476D(2)LSR250	11.8	6.0	250	775	698	310	125	1
25	68	D/7343-31	TC(1)IE686D(2)LSR150	17.0	10.0	150	1000	900	400	125	1
25	68	D/7343-31	TC(1)IE686D(2)LSR1200	17.0	10.0	200	866	779	346	125	1
25	68	E/7343-43	TC(1)IE686E(2)LSR125	17.0	6.0	125	1149	1034	460	125	1
25	68	E/7343-43	TC(1)IE686E(2)LSR130	17.0	6.0	130	1127	1014	451	125	1
25	68	E/7343-43	TC(1)IE686E(2)LSR150	17.0	6.0	250	775	698	310	125	1
25	68	E/7343-43	TC(1)IE686E(2)LSR200	17.0	6.0	200	908	817	363	125	1
25	68	E/7343-43	TC(1)IE686E(2)LSR120	17.0	6.0	120	1118	1006	447	125	1
25	68	E/7343-43	TC(1)IE686E(2)LSR130	17.0	6.0	130	1074	967	430	125	1
25	68	E/7343-43	TC(1)IE686E(2)LSR150	17.0	6.0	150	1000	900	400	125	1
25	68	E/7343-43	TC(1)IE686E(2)LSR200	17.0	6.0	200	908	817	363	125	1
25	100	E/7343-43	TC(1)IE107E(2)LSR150	25.0	10.0	150	1049	944	420	125	1
25	100	H/7360-38	TC(1)IE107H(2)LSR100	25.0	8.0	100	1414	1273	566	125	1
35	0.33	A/3216-18	TC(1)IV334A(2)LSR6K0	0.5	4.0	6,000	112	101	45	125	1
35	0.47	A/3216-18	TC(1)IV474A(2)LSR4K0	0.5	4.0	4,000	137	123	55	125	1
35	0.47	B/3528-21	TC(1)IV474B(2)LSR1K5	0.5	4.0	1,500	238	214	95	125	1
35	0.47	B/3528-21	TC(1)IV474B(2)LSR2K2	0.5	4.0	2,200	197	177	79	125	1
35	0.47	B/3528-21	TC(1)IV474B(2)LSR2K5	0.5	4.0	2,500	184	166	74	125	1
35	0.47	B/3528-21	TC(1)IV474B(2)LSR11K	0.5	4.0	11,000	88	79	35	125	1
35	1	A/3216-18	TC(1)IV105A(2)LSR3K0	0.5	4.0	3,000	158	142	63	125	1
35	1	B/3528-21	TC(1)IV105B(2)LSR1K5	0.5	4.0	1,500	238	214	95	125	1
35	1	B/3528-21	TC(1)IV105B(2)LSR1K7	0.5	4.0	1,700	224	202	90	125	1
35	1	B/3528-21	TC(1)IV105B(2)LSR2K0	0.5	4.0	2,000	206	185	82	125	1
35	1	B/3528-21	TC(1)IV105B(2)LSR7K0	0.5	4.0	7,000	110	99	44	125	1
35	2.2	B/3528-21	TC(1)IV225B(2)LSR1K5	0.8	6.0	1,500	238	214	95	125	1
35	2.2	B/3528-21	TC(1)IV225B(2)LSR2K0	0.8	6.0	2,000	206	185	82	125	1
35	2.2	B/3528-21	TC(1)IV225B(2)LSR4K0	0.8	6.0	4,000	146	131	58	125	1
35	2.2	C/6032-28	TC(1)IV225C(2)LSR750	0.8	6.0	750	383	345	153	125	1
35	3.3	B/3528-21	TC(1)IV335B(2)LSR1K0	1.2	6.0	1,000	292	263	117	125	1

## RATINGS &amp; PART NUMBER REFERENCE


Table 9

RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	µF	CCE/EIA	(See below for part options)	µA +20°C Max/5 Min	% at +20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at +25°C 100 kHz	mA at +85°C 100 kHz	mA at +125°C 100 kHz	°C	Reflow Temp ≤ 260°C
35	3.3	B/3528-21	TC(1)IV335B(2)LSR900	1.2	6.0	900	307	276	123	125	1
35	3.3	C/6032-28	TC(1)IV335C(2)LSR525	1.2	6.0	525	458	412	183	125	1
35	3.3	C/6032-28	TC(1)IV335C(2)LSR550	1.2	6.0	550	447	402	179	125	1
35	3.3	C/6032-28	TC(1)IV335C(2)LSR600	1.2	6.0	600	428	385	171	125	1
35	4.7	B/3528-21	TC(1)IV475B(2)LSR850	1.6	6.0	850	316	284	126	125	1
35	4.7	B/3528-21	TC(1)IV475B(2)LSR1K0	1.6	6.0	1,000	292	263	117	125	1
35	4.7	C/6032-28	TC(1)IV475C(2)LSR450	1.6	6.0	450	494	445	198	125	1
35	4.7	C/6032-28	TC(1)IV475C(2)LSR500	1.6	6.0	500	469	422	188	125	1
35	4.7	C/6032-28	TC(1)IV475C(2)LSR600	1.6	6.0	600	428	385	171	125	1
35	4.7	D/7343-31	TC(1)IV475D(2)LSR300	1.6	6.0	300	707	636	283	125	1
35	6.8	C/6032-28	TC(1)IV685C(2)LSR1K8	2.4	6.0	1,800	247	222	99	125	1
35	6.8	D/7343-31	TC(1)IV685D(2)LSR150	2.4	6.0	150	1000	900	400	125	1
35	6.8	D/7343-31	TC(1)IV685D(2)LSR300	2.4	6.0	300	707	636	283	125	1
35	6.8	D/7343-31	TC(1)IV685D(2)LSR400	2.4	6.0	400	612	551	245	125	1
35	6.8	V/7343-20	TC(1)IV685V(2)LSR600	2.4	6.0	600	456	410	182	125	1
35	6.8	E/7343-43	TC(1)IV685E(2)LSR300	2.4	4.0	300	742	668	297	125	1
35	10	C/6032-28	TC(1)IV106C(2)LSR400	3.5	6.0	400	524	472	210	125	1
35	10	D/7343-31	TC(1)IV106C(2)LSR120	3.5	4.0	120	1118	1006	447	125	1
35	10	D/7343-31	TC(1)IV106D(2)LSR125	3.5	6.0	125	1095	986	438	125	1
35	10	D/7343-31	TC(1)IV106D(2)LSR130	3.5	6.0	130	1074	967	430	125	1
35	10	D/7343-31	TC(1)IV106D(2)LSR250	3.5	6.0	250	775	698	310	125	1
35	10	D/7343-31	TC(1)IV106D(2)LSR260	3.5	6.0	260	760	684	304	125	1
35	10	D/7343-31	TC(1)IV106D(2)LSR300	3.5	6.0	300	707	636	283	125	1
35	10	D/7343-31	TC(1)IV106D(2)LSR1K0	3.5	6.0	1,000	387	348	155	125	1
35	10	V/7343-20	TC(1)IV106D(2)LSR600	3.5	6.0	600	456	410	182	125	1
35	10	E/7343-43	TC(1)IV106E(2)LSR175	3.5	6.0	175	971	874	388	125	1
35	10	E/7343-43	TC(1)IV106E(2)LSR200	3.5	6.0	200	908	817	363	125	1
35	10	E/7343-43	TC(1)IV106E(2)LSR250	3.5	4.0	250	812	731	325	125	1
35	10	E/7343-43	TC(1)IV106E(2)LSR260	3.5	4.0	260	797	717	319	125	1
35	15	C/6032-28	TC(1)IV156C(2)LSR350	5.3	6.0	350	561	505	224	125	1
35	15	D/7343-31	TC(1)IV156D(2)LSR225	5.3	6.0	225	816	734	326	125	1
35	15	D/7343-31	TC(1)IV156D(2)LSR260	5.3	6.0	260	760	684	304	125	1
35	15	D/7343-31	TC(1)IV156D(2)LSR300	5.3	6.0	300	707	636	283	125	1
35	15	E/7343-43	TC(1)IV156E(2)LSR200	5.3	6.0	200	908	817	363	125	1
35	15	E/7343-43	TC(1)IV156E(2)LSR225	5.3	6.0	225	856	770	342	125	1
35	15	E/7343-43	TC(1)IV156E(2)LSR250	5.3	6.0	250	812	731	325	125	1
35	15	E/7343-43	TC(1)IV156E(2)LSR260	5.3	6.0	260	797	717	319	125	1
35	15	E/7343-43	TC(1)IV156E(2)LSR275	5.3	6.0	275	775	698	310	125	1
35	15	E/7343-43	TC(1)IV156E(2)LSR300	5.3	6.0	300	742	668	297	125	1
35	22	D/7343-31	TC(1)IV226D(2)LSR200	7.7	6.0	200	908	817	363	125	1
35	22	D/7343-31	TC(1)IV226D(2)LSR200	7.7	6.0	200	866	779	346	125	1
35	22	D/7343-31	TC(1)IV226D(2)LSR250	7.7	6.0	250	775	698	310	125	1
35	22	D/7343-31	TC(1)IV226D(2)LSR260	7.7	6.0	260	797	717	319	125	1
35	22	D/7343-31	TC(1)IV226D(2)LSR275	7.7	6.0	275	775	698	310	125	1
35	22	D/7343-31	TC(1)IV226D(2)LSR300	7.7	6.0	300	742	668	297	125	1
35	33	D/7343-31	TC(1)IV336D(2)LSR200	11.6	6.0	200	866	779	346	125	1
35	33	D/7343-31	TC(1)IV336D(2)LSR300	11.6	6.0	300	707	636	283	125	1
35	33	E/7343-43	TC(1)IV336E(2)LSR100	11.6	6.0	100	1285	1157	514	125	1
35	33	E/7343-43	TC(1)IV336E(2)LSR125	11.6	6.0	125	1149	1034	460	125	1
35	33	E/7343-43	TC(1)IV336E(2)LSR130	11.6	6.0	130	1127	1014	451	125	1
35	33	E/7343-43	TC(1)IV336E(2)LSR180	11.6	6.0	180	957	861	383	125	1
35	22	E/7343-43	TC(1)IV226E(2)LSR260	7.7	6.0	260	760	684	304	125	1
35	22	E/7343-43	TC(1)IV226E(2)LSR300	7.7	6.0	300	707	636	283	125	1
35	22	E/7343-43	TC(1)IV226E(2)LSR125	7.7	6.0	125	1149	1034	460	125	1
35	22	E/7343-43	TC(1)IV226E(2)LSR200	7.7	6.0	200	908	817	363	125	1
35	22	E/7343-43	TC(1)IV226E(2)LSR250	7.7	6.0	250	866	779	346	125	1
35	22	E/7343-43	TC(1)IV226E(2)LSR300	7.7	6.0	300	742	668	297	125	1
35	33	D/7343-31	TC(1)IV336D(2)LSR200	11.6	6.0	200	866	779	346	125	1
35	33	D/7343-31	TC(1)IV336D(2)LSR300	11.6	6.0	300	707	636	283	125	1
35	33	E/7343-43	TC(1)IV336E(2)LSR100	11.6	6.0	100	1285	1157	514	125	1
35	33	E/7343-43	TC(1)IV336E(2)LSR125	11.6	6.0	125	1149	1034	460	125	1
35	33	E/7343-43	TC(1)IV336E(2)LSR130	11.6	6.0	130	1127	1014	451	125	1
35	33	E/7343-43	TC(1)IV336E(2)LSR180	11.6	6.0	180	957	861	383	125	1
35	33	H/7360-38	TC(1)IV336H(2)LSR200	11.6	6.0	200	1000	900	400	125	1
35	47	E/7343-43	TC(1)IV476E(2)LSR185	16.5	8.0	185	944	850	378	125	1
35	47	E/7343-43	TC(1)IV476E(2)LSR200	16.5	8.0	200	908	817	363	125	1
35	47	E/7343-43	TC(1)IV476E(2)LSR230	16.5	8.0	230	847	762	339	125	1
35	47	E/7343-43	TC(1)IV476E(2)LSR300	16.5	8.0	300	742	668	297	125	1
50	1	C/6032-28	TC(1)IX105C(2)LSR1K3	0.5	4.0	1,300	291	262	116	125	1
50	1	C/6032-28	TC(1)IX105C(2)LSR1K6	0.5	4.0	1,600	262	236	105	125	1
50	2.2	D/7343-31	TC(1)IX225D(2)LSR600	1.1	6.0	600	500	450	200	125	1
50	3.3	D/7343-31	TC(1)IX335D(2)LSR700	1.7	6.0	700	463	417	185	125	1
50	4.7	D/7343-31	TC(1)IX475D(2)LSR275	2.4	6.0	275	739	665	296	125	1



Table 10


RATED VOLTAGE	RATED CAP	CASE CODE/ CASE SIZE	CCE PART NUMBER	DC LEAKAGE	DF	ESR	MAXIMUM ALLOWABLE RIPPLE CURRENT (RMS)			MAXIMUM OPERATING TEMP	MSL
VDC at 85°C	µF	CCE/EIA	(See below for part options)	µA +20°C Max/5 Min	% at+20°C 120 Hz Max	mΩ at 20°C 100 kHz Max	mA at+25°C 100 kHz	mA at+85°C 100 kHz	mA at+125°C 100 kHz	°C	Reflow Temp ≤ 260°C
50	4.7	D/7343-31	TC(1)IX475D(2)LSR300	2.4	6.0	300	707	636	283	125	1
50	4.7	E/7343-43	TC(1)IX475E(2)LSR300	2.4	4.0	300	742	668	297	125	1
50	6.8	D/7343-31	TC(1)IX685D(2)LSR190	3.4	6.0	190	889	800	356	125	1
50	6.8	D/7343-31	TC(1)IX685D(2)LSR200	3.4	6.0	200	866	779	346	125	1
50	6.8	D/7343-31	TC(1)IX685D(2)LSR275	3.4	6.0	275	739	665	296	125	1
50	6.8	D/7343-31	TC(1)IX685D(2)LSR300	3.4	6.0	300	707	636	283	125	1
50	6.8	D/7343-31	TC(1)IX685D(2)LSR400	3.4	6.0	400	612	551	245	125	1
50	6.8	E/7343-43	TC(1)IX685E(2)LSR300	3.4	6.0	300	742	668	297	125	1
50	10	E/7343-43	TC(1)IX106E(2)LSR250	5.0	8.0	250	812	731	325	125	1
50	10	E/7343-43	TC(1)IX106E(2)LSR260	5.0	6.0	260	797	717	319	125	1
50	10	E/7343-43	TC(1)IX106E(2)LSR300	5.0	6.0	300	742	668	297	125	1
50	15	E/7343-43	TC(1)IX156E(2)LSR200	7.5	6.0	200	908	817	363	125	1
50	15	E/7343-43	TC(1)IX156E(2)LSR250	7.5	6.0	250	812	731	325	125	1
50	15	E/7343-43	TC(1)IX156E(2)LSR300	7.5	6.0	300	742	668	297	125	1



TC Series

## RECOMMENDED VOLTAGE DERATING GUIDELINES

	−55°C to 85°C	85°C to 125°C
% Change in working DC voltage with temperature	$V_r$	67% of $V_r$
Recommended maximum application voltage	50% of $V_r$	50% of $V_r$



## RIPPLE CURRENT/RIPPLE VOLTAGE

Permissible AC ripple voltage and current are related to equivalent series resistance (ESR) and the power dissipation capabilities of the device. Permissible AC ripple voltage which may be applied is limited by two criteria:

1. The positive peak AC voltage plus the DC bias voltage, if any, must not exceed the DC voltage rating of the capacitor.
2. The negative peak AC voltage in combination with bias voltage, if any, must not exceed the allowable limits specified for reverse voltage. See the Reverse Voltage section for allowable limits.

The maximum power dissipation by case size can be determined using the table at right. The maximum power dissipation rating stated in the table must be reduced with increasing environmental operating temperatures. Refer to the table below for temperature compensation requirements.

### TEMPERATURE COMPENSATION MULTIPLIERS FOR MAXIMUM RIPPLE CURRENT

$T \leq 25^\circ\text{C}$	$T \leq 85^\circ\text{C}$	$T \leq 125^\circ\text{C}$
1.00	0.90	0.40

$T$  - Environmental Temperature

The maximum power dissipation rating must be reduced with increasing environmental operating temperatures. Refer to the Temperature Compensation Multiplier table for details.

CCE Case Code	EIA Case Code	Maximum Power Dissipation (P <sub>max</sub> ) mWatts at 25°C w/+20°C Rise
A	3216-18	75
B	3528-21	85
C	6032-28	110
D	7343-31	150
E	7343-43	165
H	7360-38	200
S	3216-12	60
T	3528-12	70
U	6032-15	90
V	7343-20	125

Using the P<sub>max</sub> of the device, the maximum allowable rms ripple current or voltage may be determined.

$$I_{(max)} = \sqrt{P_{max}/R}$$

$$E_{(max)} = Z \sqrt{P_{max}/R}$$

$I$  - rms ripple current (amperes)

$E$  - rms ripple voltage (volts)

$P_{max}$  - maximum power dissipation (watts)

$R$  - ESR at specified frequency (ohms)


$Z$  - Impedance at specified frequency (ohms)



## REVERSE VOLTAGE

Solid tantalum capacitors are polar devices and may be permanently damaged or destroyed if connected with the wrong polarity. The positive terminal is identified on the capacitor body by a stripe plus in some cases a beveled edge. A small degree of transient reverse voltage is permissible for short periods per the table. The capacitors should not be operated continuously in reverse mode, even within these limits.

TEMPERATURE	PERMISSIBLE TRANSIENT REVERSE VOLTAGE
25°C	15% of Rated Voltage
85°C	5% of Rated Voltage
125°C	1% of Rated Voltage




## LAND DIMENSIONS/COURTYARD

CCE	METRIC SIZE CODE	DENSITY LEVEL A: MAXIMUM (MOST) LAND PROTRUSION (MM)						DENSITY LEVEL B: MEDIAN (NOMINAL) LAND PROTRUSION						DENSITY LEVEL C: MINIMUM (LEAST) LAND PROTRUSION (MM)					
		CASE	EIA	W	L	S	V1	V2	W	L	S	V1	V2	W	L	S	V1	V2	
A	3216-18	1.35	2.20	0.62	6.02	2.80	1.23	1.80	0.82	4.92	2.30	1.13	1.42	0.98	4.06	2.04			
B	3528-21	2.35	2.21	0.92	6.32	4.00	2.23	1.80	1.12	5.22	3.50	2.13	1.42	1.28	4.36	3.24			
M	3528-15	2.35	2.20	0.92	6.32	4.00	2.23	1.80	1.12	5.22	3.50	2.13	1.42	1.28	4.36	3.24			
C	6032-28	2.35	2.77	2.37	8.92	4.50	2.23	2.37	2.57	7.82	4.00	2.13	1.99	2.73	6.96	3.74			
U	6032-15	2.35	2.77	2.67	8.92	4.50	2.23	2.37	2.57	7.82	4.00	2.13	1.99	2.73	6.96	3.74			
D	7343-31	2.55	2.77	3.67	10.22	5.60	2.43	2.37	3.87	9.12	5.10	2.33	1.99	4.03	8.26	4.84			
H <sup>1</sup>	7360-38	4.25	2.77	3.67	10.22	7.30	4.13	2.37	3.87	9.12	6.80	4.03	1.99	4.03	8.26	6.54			
T	3528-12	2.35	2.20	0.92	6.32	4.00	2.23	1.80	1.12	5.22	3.50	2.13	1.42	1.28	4.36	3.24			
V	7343-21	2.55	2.77	3.67	10.22	5.60	2.43	2.37	3.87	9.12	5.10	2.33	1.99	4.03	8.26	4.84			
E <sup>1</sup>	7343-43	2.55	2.77	3.67	10.22	5.60	2.43	2.37	3.87	9.12	5.10	2.33	1.99	4.03	8.26	4.84			

**Density Level A:** For low-density product applications. Recommended for wave solder applications and provides a wider process window for reflow solder processes.

**Density Level B:** For products with a moderate level of component density. Provides a robust solder attachment condition for reflow solder processes. **Density Level C:** For high component density product applications. Before adapting the minimum land pattern variations the user should perform qualification testing based on the conditions outlined in IPC standard 7351 (IPC-7351).

<sup>1</sup>Height of these chips may create problems in wave soldering. <sup>2</sup>Land pattern geometry is too small for silkscreen outline.



## SOLDERING PROCESS

The CCE families of surface mount capacitors are compatible with wave (single or dual), convection, IR, or vapor phase reflow techniques. Preheating of these components is recommended to avoid extreme thermal stress.

CCE's recommended profile conditions for convection and IR reflow reflect the profile conditions of the IPC/J-STD-020D standard for moisture sensitivity testing. The devices can safely withstand a maximum of three reflow passes at these conditions.

Please note that although the E/7343-43 case size can withstand wave soldering, the tall profile (4.3 mm maximum) dictates care in wave process development.


Hand soldering should be performed with care due to the difficulty in process control. If performed, care should be taken to avoid contact of the soldering iron to the molded case. The iron should be used to heat the solder pad, applying solder between the pad and the termination, until reflow occurs. Once reflow occurs, the iron should be removed immediately. "Wiping" the edges of a chip and heating the top surface is not recommended.

During typical reflow operations, a slight darkening of the gold-colored epoxy may be observed. This slight darkening is normal and not harmful to the product. Marking permanency is not affected by this change.

PROFILE FEATURE	SNPB ASSEMBLY	PB-FREE ASSEMBLY
PREHEAT/SOAK		
Temperature Minimum ( $T_{smin}$ )	100°C	150°C
Temperature Maximum ( $T_{smax}$ )	150°C	200°C
Time ( $t_s$ ) from $T_{smin}$ to $T_{smax}$ )	60 – 120 seconds	60 – 120 seconds
Ramp-up Rate ( $T_L$ to $T_P$ )	3°C/second maximum	3°C/second maximum
Liquidous Temperature ( $T_L$ )	183°C	217°C
Time Above Liquidous ( $t_L$ )	60 – 150 seconds	60 – 150 seconds
Peak Temperature ( $T_P$ )	220°C* 235°C**	220°C* 235°C**
Time within 5°C of Maximum Peak Temperature ( $t_P$ )	20 seconds maximum	30 seconds maximum
Ramp-down Rate ( $T_P$ to $T_L$ )	6°C/second maximum	6°C/second maximum
Time 25°C to Peak Temperature	6 minutes maximum	8 minutes maximum

Note: All temperatures refer to the center of the package, measured on the package body surface that is facing up during assembly reflow.



\* For Case Size height > 2.5 mm | \*\* For Case Size height ≤ 2.5 mm




## STORAGE

Tantalum chip capacitors should be stored in normal working environments. While the chips themselves are quite robust in other environments, solderability will be degraded by exposure to high temperatures, high humidity, corrosive atmospheres, and long term storage. In addition, packaging materials will be degraded by high temperature – reels may soften or warp and tape peel force may increase. CCE recommends that maximum storage temperature not exceed 40°C and maximum storage humidity not exceed 60% relative humidity. Temperature fluctuations should be minimized to avoid condensation on the parts and atmospheres should be free of chlorine and sulphur bearing compounds. For optimized solderability, chip stock should be used promptly, preferably within three years of receipt.

## CONSTRUCTION




## CAPACITOR MARKING



## ■ TAPE & REEL PACKAGING INFORMATION


CCE's molded chip capacitor families are packaged in 8 and 12 mm plastic tape on 7" and 13" reels in accordance with EIA Standard 481: Embossed Carrier Taping of Surface Mount Components for Automatic Handling. This packaging system is compatible with all tape-fed automatic pick-and-place systems.



## ■ PACKAGING QUANTITY

CASE CODE		TAPE WIDTH (MM)	7" REEL*	13" REEL*
CASE	EIA			
T	3528-12	8	3,000	10,000
M	3528-15	8	2,500	8,000
U	6032-15	12	1,000	5,000
W	7343-15	12	1,000	3,000
V	7343-20	12	1,000	3,000
A	3216-18	8	2,000	9,000
B	3528-21	8	2,000	8,000
C	6032-28	12	500	3,000
D	7343-31	12	500	2,500
E	7343-43	12	500	2,000
H	7360-38	12	500	2,000

## ■ EMBORESSED (PLASTIC) CARRIER TAPE DIMENSIONS 8 mm (0.315") or 12 mm



## ■ EMBORESSED (PLASTIC) CARRIER TAPE DIMENSIONS 8 mm (0.315") or 12 mm

Metric will govern

### CONSTANT DIMENSIONS — MILLIMETERS (INCHES)

TAPE SIZE	D <sub>0</sub>	D <sub>1</sub> MINIMUM NOTE 1	E <sub>1</sub>	P <sub>0</sub>	P <sub>2</sub>	R Reference Note 2	S <sub>1</sub> Minimum Note 3	T Maximum	T <sub>1</sub> Maximum
8MM	1.5 +0.10/-0.0 (0.059 +0.004/-0.0)	1.0 (0.039)	1.75 ±0.10 (0.069 ±0.004)	4.0 ±0.10 (0.157 ±0.004)	2.0 ±0.05 (0.079 ±0.002)	25.0 (0.984)	0.600 (0.024)	0.600 (0.024)	0.100 (0.004)
12MM		1.5 (0.059)				30 (1.181)			

### VARIABLE DIMENSIONS — MILLIMETERS (INCHES)

TAPE SIZE	PITCH	B <sub>1</sub> MAXIMUM NOTE 4	E <sub>2</sub> MINIMUM	F	P <sub>1</sub>	T <sub>2</sub> MAXIMUM	W MAXIMUM	A <sub>0</sub> , B <sub>0</sub> & K <sub>0</sub>
8MM	SINGLE (4 MM)	4.35 (0.171)	6.25 (0.246)	3.5 ±0.05 (0.138 ±0.002)	2.0 ±0.05 or 4.0 ±0.10 (0.079 ±0.002 or 0.157 ±0.004)	2.5 (0.098)	8.3 (0.327)	NOTE 5
12MM	SINGLE (4 MM) AND DOUBLE (8 MM)	8.2 (0.323)	10.25 (0.404)	5.5 ±0.05 (0.217 ±0.002)	2.0 ±0.05 (0.079 ±0.002) or 4.0 ±0.10 (0.157 ±0.004) or 8.0 ±0.10 (0.315 ±0.004)	4.6 (0.181)	12.3 (0.484)	

- The embossment hole location shall be measured from the sprocket hole controlling the location of the embossment. Dimensions of embossment location and hole location shall be applied independent of each other.
- The tape, with or without components, shall pass around R without damage (see Figure 4).
- If S<sub>1</sub> < 1.0 mm, there may not be enough area for cover tape to be properly applied (see EIA Standard 481-D, paragraph 4.3, section b).
- B<sub>1</sub> dimension is a reference dimension for tape feeder clearance only.
- The cavity defined by A<sub>0</sub>, B<sub>0</sub> and K<sub>0</sub> shall surround the component with sufficient clearance that:
  - the component does not protrude above the top surface of the carrier tape.
  - the component can be removed from the cavity in a vertical direction without mechanical restriction, after the top cover tape has been removed.
  - rotation of the component is limited to 20° maximum for 8 and 12 mm tapes (see Figure 2).
  - lateral movement of the component is restricted to 0.5 mm maximum for 8 mm and 12 mm wide tape (see Figure 3).
  - see Addendum in EIA Standard 481-D for standards relating to more precise taping requirements.

**Cal-Chip**  
Electronics Inc.



## PACKAGING INFORMATION PERFORMANCE NOTES

1. Cover tape break force: 1.0 kg minimum.
2. Cover tape peel strength: The total peel strength of the cover tape from the carrier tape shall be:


TAPE WIDTH	PEEL STRENGTH
8MM	0.1 to 1.0 newton (10 to 100 gf)
12 MM	0.1 to 1.3 newton (10 to 130 gf)

The direction of the pull shall be opposite the direction of the carrier tape travel. The pull angle of the carrier tape shall be 165° to 180° from the plane of the carrier tape. During peeling, the carrier and/or cover tape shall be pulled at a velocity of 300 ±10 mm/minute.


3. Labeling: Bar code labeling (standard or custom) shall be on the side of the reel opposite the sprocket holes. Refer to EIA Standards 556 and 624.




## MAXIMUM COMPONENT ROTATION




## MAXIMUM LATERAL MOVEMENT



## BENDING RADIUS



## ■ REEL DIMENSIONS




NOTE: DRIVE SPOKES OPTIONAL; IF USED, DIMENSIONS B AND D SHALL APPLY.

## ■ REEL DIMENSIONS


Metric will govern

CONSTANT DIMENSIONS — MILLIMETERS (INCHES)					VARIABLE DIMENSIONS — MILLIMETERS (INCHES)				
TAPE SIZE	A	B MINIMUM	C	D MINIMUM	TAPE SIZE	N Minimum	W <sub>1</sub>	W <sub>2</sub> MAXIMUM	W <sub>3</sub>
8MM	$178 \pm 0.20$ (7.008±0.008) or $330 \pm 0.20$ (13.000±0.008)	1.5 (0.059)	$13.0 +0.5/-0.2$ (0.521 +0.02/-0.008)	20.2 (0.795)	8MM	50 (1.969)	8.4 +1.5/-0.0 (0.331 +0.059/-0.0)	14.4 (0.567)	Shall accommodate tape width without interference
12MM					12MM		12.4 +2.0/-0.0 (0.488 +0.078/-0.0)	18.4 (0.724)	

## ■ TAPE LEADER & TRAILER DIMENSIONS



## ■ MAXIMUM CAMBER



## ■ DISCLAIMER

All product specifications, statements, information and data (collectively, the "Information") in this datasheet are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Statements of suitability for certain applications are based on CCE ("Cal-Chip Electronics, Inc") knowledge of typical operating conditions for such applications, but are not intended to constitute – and CCE specifically disclaims – any warranty concerning suitability for a specific customer application or use. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by CCEs with reference to the use of CCE's products is given gratis, and CCE assumes no obligation or liability for the advice given or results obtained.

Although CCE designs and manufactures its products to the most stringent quality and safety standards, given the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required.