

LAIRD NICKEL-PLATED HOLE SAW - REPLACEMENT BLADES & DRILL BIT

The Laird Hole Saw features a replaceable self-centering pilot bit (HS34DB) that prevents dangerous "walking" of the saw and a replaceable hardened saw blade (HS34RB). It also features a 1/8" depth limit that will prevent damage to the underlying headliner, yet it is deep enough to cut through thicker aluminum surfaces encountered on utility vehicles and ambulances. It is designed for a 3/8" drill chuck and is nickel-plated to guard the tool against corrosion.



HS34



HS34RB



HS34DB

SPECIFICATIONS

Description	X-ACT hole saw cuts a 3/4" hole x Depth 1/8". Repl blades: HS34R; repl pilot bit: HS34DB
Teeth per Inch	6
Item Height	1-1/2 in
Item Length	3/4 in
Item Width	3/4 in

Americas: +1.847 839.6925
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-H34 0915

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.