

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [2077820003](#)
Status: **Active**
Overview: [Squba Sealed Wire-to-Wire Connectors](#)
Description: Squba 3.6 Sealed Receptacle Assembly, 3.60mm Pitch, 3 Circuits, Single Row, Glow-Wire Capable

Documents:
[3D Model](#)
[Drawing \(PDF\)](#)
[3D Model \(PDF\)](#)
[Product Specification 2077760000-PS-000 \(PDF\)](#)
[Application Specification 2077760000-AS-000 \(PDF\)](#)
[Packaging Specification 2077820000-PK-000 \(PDF\)](#)
[Test Summary 2077760000-TS-000 \(PDF\)](#)
[Datasheet \(PDF\)](#)
[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification
UL E29179

General
Product Family Crimp Housings
Series [207782](#)
Application Power, Signal, Wire-to-Wire
Overview [Squba Sealed Wire-to-Wire Connectors](#)
Product Name Squba
UPC 191130533466

Physical
Circuits (maximum) 3
Color - Resin Black
Flammability 94V-0
Gender Receptacle
Glow-Wire Capable Yes
Keying to Mating Part None
Lock to Mating Part Yes
Material - Resin Nylon
Net Weight 3.923/g
Number of Rows 1
Packaging Type Tray
Panel Mount No
Pitch - Mating Interface 3.60mm
Pitch - Termination Interface 3.60mm
Polarized to Mating Part Yes
Temperature Range - Operating -40° to +105°C

Material Info

Reference - Drawing Numbers
Application Specification 2077760000-AS-000
Packaging Specification 2077820000-PK-000
Product Specification 2077760000-PS-000
Sales Drawing 2077820000-SD-000
Test Summary 2077760000-TS-000



Series image - Reference only

EU ELV
Not Relevant

EU RoHS	China RoHS
Compliant	
REACH SVHC	
Not Contained Per - D(2021)4569-DC (8 July 2021)	
Halogen-Free	
Status	
Not Low-Halogen	
For more information, please visit Contact US	
China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series
[207782](#) Series

Mates With
Squba 3.6 Plug Assembly [2077780003](#)

Use With
Squba 3.6 Crimp Terminal [207777](#)