



INTEGRA ENCLOSURES

STRONGBOX SERIES STANDARD ENCLOSURES




Bolted Tabs



Removable Pinge™



Rivet Nuts



FIP Urethane Gasket



1/4 Turn Latch



Panel Standoffs

Our High-Quality Stainless Steel Enclosures, available for *QuickShip!*

Ideal for indoor or outdoor applications that require protection against water, oil and dirt. Our Strongbox Series enclosures come in multiple standard sizes and feature an attractive brushed finish and NEMA 4X corrosion protection.

CERTIFICATIONS

NEMA Type 1, 2, 3, 3R, 4, 4X CSA Type 1, 2, 3, 3R, 4, 4X
UL 508A Listed File No. E162786
IEC 60529, IP66



STANDARD FEATURES - SINGLE DOOR WALL MOUNT ENCLOSURE

304 Stainless Steel with Grade #4 Finish

Seams Continuously Welded and Ground Smooth

Removable Pin Hinge (Pinge™)

Door Opens 180+ Degrees

Standoffs Provided for Mounting Optional Subpanels

Mounting Tabs Included

Chemical, Corrosion & Hosedown Resistant

Stainless Steel 1/4 Turn Latch

Water & Oil Resistant Foam-In-Place Urethane Gasket

Flange Collar Around All Sides of Door Opening

Grounding Stud on Door and Body

Multiple Sizes Available

*Standard QuickShip lead time is 1-2 business days and is based on available quantities of unmodified enclosures. Call sales department for details.



INTEGRA

ENCLOSURES

STRONGBOX SERIES

STANDARD ENCLOSURES

STANDARD ENCLOSURE SIZES

Part Number	Height	Width	Depth	Material Thickness Cover & Base	Enclosure Weight (lbs.)	Optional Subpanel Part #	Subpanel Dimensions
W100804-4PQ-BT	10"	8"	4"	16 Gauge (.060 in.)*	6.0	PNLB1008GVN	8.25x6
W100806-4PQ-BT	10"	8"	6"	16 Gauge (.060 in.)*	7.2	PNLB1008GVN	8.25x6
W121004-4PQ-BT	12"	10"	4"	16 Gauge (.060 in.)*	8.1	PNLB1210GVN	10.25x8
W121006-4PQ-BT	12"	10"	6"	16 Gauge (.060 in.)*	9.6	PNLB1210GVN	10.25x8
W141206-4PQ-BT	14"	12"	6"	16 Gauge (.060 in.)*	12.3	PNLB1412GVN	12.25x10
W201608-4PQ-BT	20"	16"	8"	16 Gauge (.060 in.)*	22.6	PNLB2016GVN	18.25x14
W202008-4PQ-BT	20"	20"	8"	16 Gauge (.060 in.)*	26.6	PNLB2020GVN	18x18
W202010-4PQ-BT	20"	20"	10"	14 Gauge (.075 in.)*	36.8	PNLB2020GVN	18x18
W242008-4PQ-BT	24"	20"	8"	16 Gauge (.060 in.)*	30.7	PNLB2420GVN	22.25x18
W242010-4PQ-BT	24"	20"	10"	14 Gauge (.075 in.)*	42.2	PNLB2420GVN	22.25x18
W242408-4PQ-BT	24"	24"	8"	16 Gauge (.060 in.)*	35.3	PNLB2424GVN	22x22
W242410-4PQ-BT	24"	24"	10"	14 Gauge (.075 in.)*	48.4	PNLB2424GVN	22x22
W302410-4PQ-BT	30"	24"	10"	14 Gauge (.075 in.)*	57.6	PNLB3024GVN	28.25x22
W302412-4PQ-BT	30"	24"	12"	14 Gauge (.075 in.)*	62.3	PNLB3024GVN	28.25x22
W363012-4PQ-BT	36"	30"	12"	14 Gauge (.075 in.)*	84.9	PNLB3630GVN	34.25x28

SINGLE DOOR, WALL MOUNT ENCLOSURES IN 304 STAINLESS STEEL
NEMA/CSA Type 1, 2, 3, 3R, 4, 4X

Looking for Something Different?
Contact Us About Custom Sizing & Accessories

Multiple Latch & Hinge Options to Fit your Application

Quarter Turn Latch - standard

Removable Pin Hinge (Pinge™) - standard

Integra Locking Latch

Continuous Piano Hinge

Pad Lockable 3-Point Latch

Lift Off Hinge

Multiple Non-Standard Mounting Options

Welded or Bolted Mounting Tabs - bolted tabs standard

Welded or Bolted Mounting Flange

Rivet Nuts or Through Holes

Multiple Sizes of Legs

Custom Laser Cut Machining

Precision laser cut machining available for cable connectors and more!

Email plans to sales@integraenclosures.com to request a quote.

316 Stainless Steel and Aluminum also available



INTEGRA ENCLOSURES

STRONGBOX SERIES STANDARD ENCLOSURES

STANDARD DESIGN & CONSTRUCTION SPECIFICATIONS:

1. 304 STAINLESS STEEL
2. #4 BRUSHED FINISH
3. CONTINUOUSLY WELDED SEAMS
4. EXTERNAL WELDS GROUND & FINISHED
5. NO SHARP EDGES/CORNERS
6. "C" CHANNEL BODY FLANGE WITH MINIMUM .34" WIDE SEALING FACE
7. MINIMUM 180° DOOR SWING
8. RIVET NUTS FOR MOUNTING
9. BONDING & GROUNDING STUDS ON DOOR AND BASE
10. COLLAR STUDS FOR BACK PANEL MOUNTING
11. 316 STAINLESS STEEL PIN HINGES (PINGE™)
12. IP66 RATED 304 STAINLESS STEEL QUARTER TURN LATCHES
13. HYDROPHOBIC POLYURETHANE FORMED-IN-PLACE FOAM GASKET

