

Serial ATA (SATA) Right-Angle Signal Cable (7Pin/7Pin-Up), 12-in. (30.48 cm)

MODEL NUMBER: **P941-12I**



Features

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Features 7Pin Straight and 7Pin Right-Angle Up connectors
- Angled connector ideal for situations in which space is at a premium, and reduces stress / excessive bending on the cable
- SATA III (6Gbps) / SATA II (3Gbps) / SATA I (1.5Gbps) Compliant
- Cable is shielded to protect against EMI/RFI

Highlights

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Features 7Pin Straight and 7Pin Right-Angle Up connectors
- Angled connector ideal for situations in which space is at a premium, and reduces stress / excessive bending on the cable
- SATA III (6Gbps) / SATA II (3Gbps) / SATA I (1.5Gbps) Compliant
- Cable is shielded to protect against EMI/RFI

Applications

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Compatible with Serial ATA Hard Drives, Blu-ray/DVD/CD Drives and other Serial ATA devices

System Requirements

- SATA device
- SATA controller
- Data transfer rates are dependent upon the version of SATA supported by your device and controller

Package Includes

- Serial ATA (SATA) Right Angle Signal Cable (7Pin/7Pin-Up) 12-in.

Specifications

| OVERVIEW | |
|---------------------------|-----------------|
| UPC Code | 037332184399 |
| Technology | SATA/eSATA |
| PHYSICAL | |
| Color | Red |
| Cable Jacket Color | Red |
| Cable Outer Diameter (OD) | 2.2 +/- 0.10 mm |

| | |
|-------------------------------------|------------------------------------|
| Cable Length (ft.) | 1 |
| Cable Length (m) | 0.30 |
| Cable Length (in.) | 12 |
| Cable Length (cm) | 30.48 |
| Shipping Dimensions (hwd / cm) | 22.86 x 17.78 x 1.27 |
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.50 |
| Shipping Weight (kg) | 0.02 |
| Shipping Weight (lbs.) | 0.04 |
| CONNECTIONS | |
| Side A - Connector 1 | 7 PIN SATA STRAIGHT (MALE) |
| Side B - Connector 1 | 7 PIN SATA (MALE) - RIGHT ANGLE UP |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>