

## Cat6 Gigabit Snagless Molded (UTP) Ethernet Cable (RJ45 M/M), Blue, 12 ft. (3.66 m)

MODEL NUMBER: N201-012-BL



### Features

- Meets category 6 cabling standards
- Premium cabling for category 6, category 5e and category 5 applications
- Length: 12 ft./Color: Blue/Connectors: RJ45 male
- Drastically reduce impedance & structural return loss compared to standard 100MHz wire
- High-quality copper wire and a staggered-pin plug design to keep near-end crosstalk levels to a minimum
- Feature molded connectors with integral strain relief
- Snagless design protects the locking tabs on the RJ45 connectors from being damaged or snapped off during installation
- PVC 4-pair stranded UTP

## Specifications

| OVERVIEW              |              |
|-----------------------|--------------|
| UPC Code              | 037332172877 |
| Technology            | Cat6         |
| PHYSICAL              |              |
| Cable Jacket Color    | Blue         |
| Cable Jacket Material | PVC          |
| Cable Jacket Rating   | CM           |
| Cable Shielding       | UTP          |

### Highlights

- Meets Category 6 cabling standards
- Meets most current industry standards including IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC 11801, and ETL (Category 6, draft 11)
- Drastically reduce impedance & structural return loss compared to standard 100Mhz wire
- Snagless boots protect the locking tabs on the RJ45 connectors from being damaged during installation
- Feature molded connectors with integral strain relief. Rated for 550 MHz/1 Gbps communication

### Package Includes

12-ft. Cat6 Blue Gigabit Patch Cord  
Snagless Molded



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                      |                              |
|--------------------------------------|------------------------------|
| Cable Outer Diameter (OD)            | 6.0mm                        |
| Number of Conductors                 | 4 Pair                       |
| Conductor Material                   | Stranded Copper              |
| Conductor Gauge                      | 24 AWG                       |
| Cable Length (ft.)                   | 12                           |
| Cable Length (m)                     | 3.66                         |
| Cable Length (in.)                   | 144                          |
| Cable Length (cm)                    | 365.8                        |
| Shipping Dimensions (hwd / cm)       | 25.40 x 20.32 x 1.27         |
| Shipping Dimensions (hwd / in.)      | 10.00 x 8.00 x 0.50          |
| Shipping Weight (kg)                 | 0.13                         |
| Shipping Weight (lbs.)               | 0.28                         |
| <b>ENVIRONMENTAL</b>                 |                              |
| Operating Temperature Range          | 14 to 122 F (-10 to 50 C)    |
| Storage Temperature Range            | 5 to 140 F (-15 to 60 C)     |
| Operating Humidity Range             | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range               | 0% to 90% RH, Non-Condensing |
| <b>COMMUNICATIONS</b>                |                              |
| Bandwidth per TIA Standard           | 250 MHz                      |
| Maximum Bandwidth as Tested          | 500 MHz                      |
| Network Compatibility                | 1 Gbps (Gigabit)             |
| IEEE Standards Supported             | 802.3an                      |
| <b>CONNECTIONS</b>                   |                              |
| Side A - Connector 1                 | RJ45 (MALE)                  |
| Side B - Connector 1                 | RJ45 (MALE)                  |
| Crossover Wiring                     | No                           |
| Contact Plating                      | Gold                         |
| Connector Type                       | Snagless                     |
| Wiring Configuration                 | EIA/TIA 568B                 |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                              |
| IP68 Rated                           | No                           |
| Snagless Connector                   | Yes                          |
| Antibacterial                        | No                           |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| STANDARDS & COMPLIANCE              |                                     |
|-------------------------------------|-------------------------------------|
| Certification & Compliance          | RoHS; REACH; IEEE 802.3an 10GBASE-T |
| WARRANTY                            |                                     |
| Product Warranty Period (Worldwide) | Lifetime limited warranty           |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>