

SmartRack Exhaust Duct Kit for SRCOOL7KRM

MODEL NUMBER: SRCOOL7KDUCT



Exhaust duct accessory for Tripp Lite SRCOOL7KRM. Directs and disperses heat from the air conditioning unit through an upper vent into your facility's ventilation system.

Description

The SRCOOL7KDUCT SmartRack Exhaust Duct Kit is a venting system accessory for Tripp Lite's SRCOOL7KRM Rack-Mounted Air Conditioning Unit. It directs and disperses heat from the SRCOOL7KRM through an upper vent into your facility's dropped ceiling plenum, return air duct or other standard ventilation system. By keeping your rack equipment cool and performing at its peak, the SRCOOL7KDUCT helps the SRCOOL7KRM reduce your cooling and energy costs.

Ideal for small-space applications where heat is unlikely to disperse on its own, such as an IT closet, the SRCOOL7KDUCT installs using the included hardware. Two magnetic tube adapters attach to the rack's vented rear door to make the kit compatible with EIA-standard rack enclosures and open frame racks that accommodate the SRCOOL7KRM.

Features

Reduces Your Cooling and Energy Costs

- Exhaust duct accessory for Tripp Lite SRCOOL7KRM
- Directs and disperses heat through your facility's ventilation system
- Ideal for small IT closets where heat is unlikely to disperse on its own
- Helps keep rack equipment cool and performing at its peak
- Installs using included hardware
- Compatible with EIA-standard rack enclosures and open frame racks that accommodate SRCOOL7KRM

Specifications

OVERVIEW	
UPC Code	037332190697
Accessory Type	Duct Kit
Accessory Class	Rack Accessories

Highlights

- Helps the SRCOOL7KRM reduce cooling and energy costs
- Ideal for small spaces, such as IT closets
- Compatible with most EIA-standard racks and rack enclosures
- Installs using included hardware
- Keeps rack equipment performing at its peak

Package Includes

- Manifold assembly
- Short exhaust tube
- Long exhaust tube (D 5.7" x L 3m)
- (2) Magnetic tube adapters
- Ceiling adapter
- Ceiling tile insert
- (4) M4 x 12 mm screws
- (4) Self-tapping screws
- Owner's manual



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

COOLING	
Cooling Type	Passive
PHYSICAL	
Housing Color	Black
Shipping Dimensions (hwd / cm)	37.49 x 31.50 x 62.99
Shipping Dimensions (hwd / in.)	14.76 x 12.40 x 24.80
Shipping Weight (kg)	6.05
Shipping Weight (lbs.)	13.33
FEATURES & SPECIFICATIONS	
IP68 Rated	No
IP20 Rated	No
STANDARDS & COMPLIANCE	
Certification & Compliance	RoHS; REACH; EIA/ECA-310-E
WARRANTY	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>