

4-Port USB 2.0 Hub

MODEL NUMBER: U225-004-R









Highlights

- Supports Hi-Speed data transfer rates up to 480 Mbps
- Meets or Exceeds USB 2.0 Specifications
- Supports USB 2.0 spec up to 500mA per port
- Hot Pluggable
- Includes 4ft USB 2.0 Computer to Hub cable

System Requirements

 A Windows, Mac or Linux computer with an available USB port

Package Includes

- U225-004-R
- 4ft USB Mini-B 5-Pin Male to USB A Male device cable

Description

Tripp Lite's U225-004-R 4-port USB 2.0 Hub allows you to attach multiple USB devices to a single USB port on your computer. The hub supports all three data transfer speeds: low speed (1.5 Mbps), full speed (12 Mbps) and Hi-Speed (480 Mbps). Includes 4 ft USB 2.0 Computer to Hub cable (A-B).

Features

- USB 2.0 and 1.1 compliant
- Compact desktop design (4"W x 2.5"D x .625"H)
- Does not require external power, software, or complicated set-up procedures
- Supports USB 2.0 spec up to 500mA per port
- On bus-power, 500mA from the USB 2.0 computer port is shared between the hub ports
- Plug & Play and Hot Swap capability
- Compatible with Windows, Mac and Linux

Specifications

OVERVIEW		
UPC Code	037332116505	
Product Type	Hub	
Over Current Protection	Yes	
Technology	USB; USB 2.0 (High Speed)	
Host Connector	USB A (MALE)	
VIDEO		
Number of Monitors Supported	0	



Extended Mode	No	
Mirror Mode	No	
DATA		
DATA Porto	(4) LISD A (FFMALE)	
Data Ports	(4) USB A (FEMALE)	
Data Ports Details	(4) USB-A - USB 2.0	
INPUT		
Voltage Compatibility (VAC)	100; 110; 120; 127; 200; 208; 220; 230; 240	
Bus Powered	Yes	
PHYSICAL		
Color	Black; Silver	
Material of Construction	PVC	
Shipping Dimensions (hwd / in.)	5.00 x 2.00 x 5.20	
Shipping Weight (kg)	0.14	
Shipping Weight (lbs.)	0.30	
Unit Dimensions (hwd / in.)	0.6 x 4 x 2.5	
Unit Packaging Type	Clamshell	
Unit Weight (kg)	0.11	
Unit Weight (lbs.)	0.24	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104 F (0 to 40 C)	
Storage Temperature Range	14 to 131 F (-10 to 55 C)	
Relative Humidity	5% to 90% RH, Non-Condensing	
BTUs	51.2 BTU/Hr	
Power Provided to Connected Device(s)	5V 0.5A (2.5W) Output per USB port	
CONNECTIONS		
Ports	4	
Side A - Connector 1	USB MINI-B 5-PIN (FEMALE)	
Side B - Connector 1	(4) USB A (FEMALE)	
FEATURES & SPECIFICATIONS		
USB Specification	USB 2.0 (up to 480 Mbps)	
Driver Required	No	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

STANDARDS & COMPLIANCE		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies