



12-Outlet Vertical Power Strip, 120V, 15A, 15 ft. (4.57 m) Cord, 5-15P, 36 in.

MODEL NUMBER: PS3612











Highlights

- 12 outlets
- Convenient and safe covered, on/off switch
- 15-amp circuit breaker
- 15-ft. cord
- 36" length

Package Includes

- PS3612
- Mounting hardware
- Instruction manual

Features

- Sturdy all-metal 36 inch corded strip format with 2.638 inch center-to-center outlet spacing
- Includes 12 NEMA 5-15R output receptacles
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- · Lighted power switch with locking transparent cover prevents accidental shutoff
- 15 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

Specifications

OVERVIEW		
UPC Code	037332011459	
INDUT		
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	15	
Input Cord Length (m)	4.57	



Integrated Cord Clip	No	
OUTPUT		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(12) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(6) Yes	
Right-Angle Outlets	No	
Outlet Spacing	2.638 in.	
USER INTERFACE, ALERTS & CO	NTROLS	
Switches	Lighted 2 position switch controls power to all outlets	
Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off	
PHYSICAL		
Material of Construction	Aluminum	
Color	Silver	
Power Cord Color	Black	
Form Factors Supported	Supports horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications	
Housing Color	Silver	
Included Mounting Accessories	Includes mounting clips	
Mounting Holes or Slots	No	
Outlets Measurement (Center to Center)	67mm	
Receptacle Color	Black	
Shipping Dimensions (hwd / cm)	100.33 x 8.38 x 5.08	
Shipping Dimensions (hwd / in.)	39.50 x 3.30 x 2.00	
Shipping Weight (kg)	1.76	
Shipping Weight (lbs.)	3.88	
Unit Dimensions (hwd / in.)	36 x 1.5 x 1.5	
Unit Dimensions (hwd / cm)	91.5 x 3.8 x 3.8	
Unit Weight (lbs.)	3.8	
Unit Weight (kg)	1.72	
FEATURES & SPECIFICATIONS		
Antimicrobial	No	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Built-In Circuit Breaker	Yes	
STANDARDS & COMPLIANCE		
STANDARDS & COMPLIANCE		
Canada	cUL	
UL1363 (Power Tap)	UL1363	
Certification & Compliance	RoHS; UL 1363; cUL Listed	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies