

2-Port VGA over Cat5/6 Splitter/Extender, Box-Style Transmitter for Video, Up to 1000 ft. (305 m), TAA

MODEL NUMBER: B132-002-2





Features

- Splits a single VGA signal into 2
- A B132-100-1 or B132-100-WP-1 remote receiver unit is required for each connected monitor
- Extends a 1920 x 1440 (60Hz) signal up to 500 ft., or a 1024 x 768 (60Hz) signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's N022-01K-GY (Cat5) and N222-01K-GY (Cat6)
- Can further expand the range and number of monitors by adding B132-110A repeaters
- EDID copy feature ensures optimal display compatibility
- Connect up to 4 remote units in a repeater chain (3 repeaters and 1 receiver), with a monitor at each location
- A 1920 x 1440 (60Hz) signal can be extended up to 500 ft. from the first repeater in the chain to the last receiver. A 1024 x 768 (60Hz) signal can be extended up to 1,000 ft. from the first repeater in the chain to the last receiver.
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite P524-01K
- Includes mounting hardware that allows unit to be wall mounted, rack mounted or pole mounted.
- Ideal for digital signage situations, such as retail, schools, churches, etc.
- · Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW

OVERVIEW	
UPC Code	037332178404
Product Type	Transceiver
Technology	VGA/SVGA; Cat5/5e; Cat6

Highlights

- Splits a single VGA signal into 2
- EDID copy feature ensures optimal display compatibility
- Extends a 1920 x 1440 (60Hz) signal up to 500 ft., or a 1024 x 768 (60Hz) signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's N022-01K-GY (Cat5) and N222-01K-GY (Cat6)
- Can further expand the range and number of monitors by adding B132-110A repeaters
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite P524-01K
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

Package Includes

- 2 Port Extender/Splitter local (Transmitter) unit
- Mounting hardware
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 5 ft.)
- · Owner's Manual



VIDEO		
Max 720P Range (ft)	500	
Max 1080P Range (ft)	500	
HDR Support	No	
3D Video Supported	No	
Maximum Signal Range (ft)	1000	
Maximum Signal Range (m)	305	
INPUT		
Bus Powered	No	
POWER		
Power Over Cable (PoC) Support	No	
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 5 ft.	
PHYSICAL		
Color	Black	
Number of Displays	2	
Form Factor/Mounting Options	Box	
Shipping Dimensions (hwd / cm)	5.08 x 15.75 x 18.29	
Shipping Dimensions (hwd / in.)	2.00 x 6.20 x 7.20	
Shipping Weight (kg)	0.50	
Shipping Weight (lbs.)	1.10	
Unit Dimensions (hwd / in.)	1 x 2.5 x 3.7	
Unit Dimensions (hwd / cm)	2.54 x 6.35 x 9.40	
Unit Weight (lbs.)	0.45	
Unit Weight (kg)	0.20	
COMMUNICATIONS		
Max 1024 x 768 Range (ft)	1000	
Max 480P Range (ft)	1000	
Max 1440 x 900 Range (ft)	500	
Max 1080i Range (ft)	500	
Max 1920 x 1440 Range (ft)	500	
Max 480i Range (ft)	1000	
Max 640 x 480 Range (ft)	1000	



Max 800 x 600 Range (ft)	1000	
Max 1600 x 1200 Range (ft)	500	
EDID Compatible	No	
IR Remote Extension Support	No	
RS-232 Serial Extension Support	No	
Consumer Electronics Control (CEC) Supported	No	
USB Extension Support	No	
CONNECTIONS		
Number of Ports	2	
Side A - Connector 1	HD15 (FEMALE)	
Side B - Connector 1	(2) RJ45 (FEMALE)	
FEATURES & SPECIFICATIONS		
Driver Required	No	
10/100 Ethernet Extension Support	No	
Built-In Equalizer	No	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies