

## Data sheet

## 6GK5795-6MN10-0AA6

### product type designation



### Antenna ANT795-6MN

ANT795-6MN IWLAN antenna with omnidirectional Characteristic; incl. N-Female connector: 6/8 dBi; IP65 (-40-+70°C), 2.4/5 GHz; Wi-Fi compliance and Observe national approvals mounting on roof and vehicles; compact instructions as hard copy English/German; scope of delivery: 1x ANT795-6MN, 1x terminating resistor TI795-1R for mounting, the mounting aid 6GK5795-6MN01-0AA6 is available

### radio frequencies

type of wireless network / is supported	WLAN
operating frequency	
• for WLAN in 2.4 GHz frequency band	2.4 ... 2.7 GHz
• for WLAN in 5 GHz frequency band 2	4.9 ... 5.935 GHz

### electrical data

impedance	50 Ω
polarization	linear vertical
radiation characteristic	omnidirectional
antenna gain compared to spherical radiator	
• of the WLAN antenna / in the 2.4 GHz frequency band	6 dB
• of the WLAN antenna / in the 5 GHz frequency band	8 dB
standing wave ratio (VSWR) / maximum	1.8
radiating angle of the antenna	
• in the 2.4 GHz frequency band / horizontal	360°
• in the 5 GHz frequency band / horizontal	150°
• in the 5 GHz frequency band / vertical	take the antenna diagram into account regarding the horizontal beam angle
number of electrical connections / of the antenna	1
type of electrical connection / of the antenna	N-Connector
design of plug-in connection	female
angle of inclination / downward / maximum	0°

### mechanical data

material	
• of outer shell	Polycarbonate

### ambient conditions

ambient temperature	
• during operation	-40 ... +80 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
protection class IP	IP65
wind load / maximum	10 N; at 160 km/h

### design, dimensions and weights

width	86 mm
height	43 mm
depth	86 mm

net weight	300 g
fastening method	
• mast mounting	No
• wall mounting	Yes
• roof mounting	Yes
• directly on the device	No
<b>product features, product functions, product components / general</b>	
product feature / silicon-free	Yes
<b>standards, specifications, approvals</b>	
certificate of suitability	Railway application in accordance with NF-F-16-101, NF-F-16-102
certificate of suitability	
• RoHS conformity	Yes
• railway application in accordance with EN 50155	Yes
• fire protection in accordance with EN 45545-2	Yes
Marine classification association / Korean Register of Shipping (KRS)	Yes
product conformity	UL 94-V0
wireless approval	Current national approvals can be found on the Internet under <a href="http://www.siemens.com/funkzulassungen">www.siemens.com/funkzulassungen</a>
<b>further information / internet-Links</b>	
Internet-Link	<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul> <a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

**last modified:**

12/16/2020 