

SITOP PSE200U/4X0.5-3A/CSC



Figure similar

SITOP PSE200U 3 A Selectivity module  
 4-channel input: DC 24 V/12 A  
 output: 24 V DC/4x 3 A  
 Level adjustable 0.5-3 A with common signaling contact

Input	
type of the power supply network	Controlled DC voltage
supply voltage / at DC / rated value	24 V
input voltage / at DC	22 ... 30 V
overvoltage overload capability	35 V
input current / at rated input voltage 24 V / rated value	12 A
Output	
voltage curve / at output	controlled DC voltage
formula for output voltage	$V_{in} - \text{approx. } 0.2 \text{ V}$
relative overall tolerance / of the voltage / note	In accordance with the supplying input voltage
number of outputs	4
output current / up to 60 °C / per output / rated value	3 A
adjustable current response value current / of the current-dependent overload release	0.5 ... 3 A
type of response value setting	via potentiometer
product feature	
• parallel switching of outputs	No
• bridging of equipment	Yes
type of outputs connection	Simultaneous connection of all outputs after power up of the supply voltage > 20 V, delay time of 25 ms, 100 ms or adjustable "load optimised" via DIP switch for sequential connection
Efficiency	
efficiency in percent	97 %
power loss [W] / at rated output voltage / for rated value of the output current / typical	9 W
Switch-off characteristic per output	
switching characteristic	
• of the excess current	$I_{out} = 1.0 \dots 1.5 \times \text{set value}$ , switch-off after approx. 5 s
• of the current limitation	$I_{out} = 1.5 \times \text{set value}$ , switch-off after typ. 100 ms
• of the immediate switch-off	$I_{out} > \text{set value}$ and $V_{in} < 20 \text{ V}$ , switch-off after approx. 0.5 ms
residual current at switch-off / typical	1 mA
design of the reset device/resetting mechanism	via sensor per output
remote reset function	Non-electrically isolated 24 V input (signal level "high" at > 15 V)

<b>Protection and monitoring</b>	
fuse protection type / at input	5 A per output (not accessible)
display version / for normal operation	Three-color LED per output: green LED for "Output switched through"; yellow LED for "Output switched off manually"; red LED for "Output switched off due to overcurrent"
design of the switching contact / for signaling function	Common signal contact (changeover contact, rating 0.1 A/24 V DC)
<b>Safety</b>	
galvanic isolation / between input and output at switch-off	No
standard / for safety	according to EN 60950-1 and EN 50178
operating resource protection class	Class III
protection class IP	IP20
<b>Approvals</b>	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes; UL-Recognized (UL 2367) File E328600; cULus-Listed (UL 508, CSA C22.2 No. 107.1) File E197259
• ATEX	Yes; IECEx Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cULus Class I, Div. 2, Group ABCD, T4
standard / for explosion protection	IECEx (IEC 60079-0, -15); ATEX (EN 60079-0, -15); cCSAus (CSA C22.2 No. 213, No. 60079, ANSI/ISA 12.12.01, UL 60079)
certificate of suitability	
• IECEx	Yes
• shipbuilding approval	Yes
shipbuilding approval	DNV GL, ABS
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• DNV GL	Yes
<b>EMC</b>	
standard	
• for emitted interference	EN 55022 Class B
• for interference immunity	EN 61000-6-2
<b>environmental conditions</b>	
ambient temperature	
• during operation	-25 ... +60 °C; with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
environmental category / acc. to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
<b>Mechanics</b>	
type of electrical connection	screw-type terminals
• at input	+24 V: 2 screw terminals for 0.5 ... 16 mm <sup>2</sup> ; 0 V: 2 screw terminals for 0.5 ... 4 mm <sup>2</sup>
• at output	Output 1 ... 4: 1 screw terminal each for 0.5 ... 4 mm <sup>2</sup>
• for signaling contact	3 screw terminals for 0.5 ... 4 mm <sup>2</sup>
• for auxiliary contacts	Remote reset: 1 screw terminal for 0.5 ... 4 mm <sup>2</sup>
width / of the enclosure	72 mm
height / of the enclosure	80 mm
depth / of the enclosure	72 mm
installation width	72 mm
mounting height	180 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
net weight	0.2 kg
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
mechanical accessories	Device identification label 20 mm x 7 mm, TI-grey 3RT2900-1SB20
MTBF / at 40 °C	755 915 h
other information	Specifications at rated input voltage and ambient temperature +25 °C

