

Specification Sheet

Part Number: TAG5L-105



Laser printable self-laminating polyester has a smooth surface, allowing for the highest resolution and print contrast.

The material is 1.0 mil thick, allowing it to conform around wires and cable.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.

Laser Print Label, Self-Laminating, .8" x .5" x 1.43", 56 Per Sheet, PET, White, 5000/pkg

|                     |                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 594-05105                                                                                                                                                                                                                                                                                                                                                                    |
| Type                | TAG5L                                                                                                                                                                                                                                                                                                                                                                        |
| Color               | White (WH)                                                                                                                                                                                                                                                                                                                                                                   |
| Quantity Per        | pack                                                                                                                                                                                                                                                                                                                                                                         |
| Product Description | <p>HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using a laser printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification.</p> |

|                                        |                                                                                           |
|----------------------------------------|-------------------------------------------------------------------------------------------|
| <b>Short Description</b>               | Laser Print Label, Self-Laminating, .8" x .5" x 1.43", 56 Per Sheet, PET, White, 5000/pkg |
| <b>Global Part Name</b>                | TAG5L-105-WH                                                                              |
| <b>Width W (Imperial)</b>              | 0.8                                                                                       |
| <b>Width W (Metric)</b>                | 20.3                                                                                      |
| <b>Bundle Diameter Min (Imperial)</b>  | 0.149                                                                                     |
| <b>Bundle Diameter Min (Metric)</b>    | 3.80                                                                                      |
| <b>Bundle Diameter Max (Imperial)</b>  | 0.29                                                                                      |
| <b>Bundle Diameter Max (Metric)</b>    | 7.60                                                                                      |
| <b>Thickness T (Metric)</b>            | 35.0                                                                                      |
| <b>Width of Liner (Metric)</b>         | 215.00                                                                                    |
| <b>Width of Liner (Imperial)</b>       | 8.5                                                                                       |
| <b>Outside Diameter Max (Imperial)</b> | 0.29                                                                                      |
| <b>Outside Diameter Min (Metric)</b>   | 3.8                                                                                       |
| <b>Outside Diameter Min (Imperial)</b> | 0.15                                                                                      |
| <b>Outside Diameter Max (Metric)</b>   | 7.60                                                                                      |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Material</b>                       | Type 105, Polyester, white (105)  |
| <b>Material Shortcut</b>              | 105                               |
| <b>Adhesive</b>                       | Acrylic                           |
| <b>Halogen Free</b>                   | No                                |
| <b>Adhesive Operating Temperature</b> | -40°F to +302°F (-40°C to +150°C) |
| <b>Operating Temperature</b>          | -40°F to +300°F (-40°C to +149°C) |
| <b>Reach Compliant (Article 33)</b>   | Yes                               |
| <b>ROHS Compliant</b>                 | Yes                               |
| <b>Package Quantity (Imperial)</b>    | 5000                              |
| <b>Package Quantity (Metric)</b>      | 5000                              |
| <b>Customs Number</b>                 | 3919905060                        |
| <b>Labels per Column</b>              | 7                                 |
| <b>Labels per Row</b>                 | 8                                 |

