

## Specification Sheet

Part Number: TELS-13



Continuous strap and separate heads allow for any bundle diameter, eliminating waste.

Smooth strap prevents cable damage.

UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

Extended-Length Tie, POM, Black, 10-13.5" straps and 10 heads/Kit

|                |           |
|----------------|-----------|
| Article Number | 111-32108 |
|----------------|-----------|

|      |         |
|------|---------|
| Type | TELS-13 |
|------|---------|

|       |            |
|-------|------------|
| Color | Black (BK) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications. |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                   |
|-------------------|-------------------------------------------------------------------|
| Short Description | Extended-Length Tie, POM, Black, 10-13.5" straps and 10 heads/Kit |
|-------------------|-------------------------------------------------------------------|

|                                            |                              |
|--------------------------------------------|------------------------------|
| <b>Global Part Name</b>                    | TELS-13-POM-BK               |
| <b>Contents of pkg/kit</b>                 | 10 straps (340 mm), 10 heads |
| <b>Minimum Tensile Strength (Imperial)</b> | 250.0                        |
| <b>Minimum Tensile Strength (Metric)</b>   | 1115.0                       |
| <b>Length L (Imperial)</b>                 | 13.5                         |
| <b>Length L (Metric)</b>                   | 343.0                        |
| <b>Fixation Method</b>                     | 2 piece                      |
| <b>Identification Plate Position</b>       | none                         |
| <b>Releasable Closure</b>                  | No                           |
| <b>Tie Closure</b>                         | steel pawl                   |
| <b>Variant</b>                             | Extended Length              |
| <b>Width W (Imperial)</b>                  | 0.5                          |
| <b>Width W (Metric)</b>                    | 12.7                         |
| <b>Thickness T (Imperial)</b>              | 0.06                         |
| <b>Thickness T (Metric)</b>                | 1.52                         |
| <b>Height H (Imperial)</b>                 | .49                          |

|                                    |                                  |
|------------------------------------|----------------------------------|
| <b>Height H (Metric)</b>           | 12.40                            |
| <b>Material</b>                    | Polyacetal (POM)                 |
| <b>Material Shortcut</b>           | POM                              |
| <b>Material Cable Tie</b>          | Polyacetal (POM)                 |
| <b>Material Head</b>               | Polyacetal (POM)                 |
| <b>Flammability</b>                | UL 94 HB                         |
| <b>Operating Temperature</b>       | -40°F to +194°F (-40°C to +90°C) |
| <b>ROHS Compliant</b>              | Yes                              |
| <b>Package Quantity (Imperial)</b> | 10                               |
| <b>Package Quantity (Metric)</b>   | 10                               |
| <b>Customs Number</b>              | 3926909988                       |