

1

2

3

4

5

6

7

A

B

C

D

E

F

A

B

C

D

E

F

TEST CONDITION:
 1.100% OPEN, SHORT, MISWIRE TEST
 2.CONDUCT RESISTANCE : 3 Ω Max
 3.INSULATION RESISTANCE: 20M Ω Min
 4.Dielectric test:300V DC

PIN ASSIGNMENT

P1		P2
1	Red	1
6		6
2	GREEN	2
7		7
3	Blue	3
8		8
4	Brown	4
5	Black	5
13	ORANGE	13
14	WHITE	14
Shell	Braid	Shell

NO.	NAME	Q'TY	SPECIFICATION
△14	TUBE	14	HEAT SHRINK TUBE BLACK OD1.5*L=15MM*2PCS,OD1.5*L=10MM*6PCS,OD3.0*L=8MM*6PCS,
△1/5	PE BAG	1/5	CLEAR SIZE:360*380*0.05mm PRINT BLACK"MADE IN CHINA"+"5PCS".
△2	TIE	2	WHITE L=120mm
△1	PE BAG	1	CLEAR SIZE:150*280*0.05mm PRINT BLACK"MADE IN CHINA"+"1PC"
△2	COPPER FOIL	2	DOUBLE-SIDED CONDUCTIVE COPPER FOIL 18U" W25mm*L55mm
△4	SCREW	4	SCREW:#4-40UNC D-E L32.5mm,NICKEL PLATED,INSULATION COLOR BEIGE(V-29)
△43.5g	OUT JACKET	43.5g	BEIGE(V-29) 40P PVC(MOULD NO:WM-113)
△8g	IN JACKET	8g	CLEAR LDPE(MOULD NO:NM-049)
△1	CONN	1	HDD15P FEMALE,PIN G/F.SHELL-NICKEL,INSULATION COLOR:BLUE. SOLDER TYPE.
△1	CONN	1	HDD15P MALE,PIN G/F.SHELL-NICKEL,INSULATION COLOR:BLUE. MISSING 9PIN SOLDER TYPE.
△1	CABLE	1	UL2919 28AWG(1C+S)*3COAX(75 OHMS)+28AWG(7/0.125TC)+4C+AL/MY+D.W(7/0.16TC)+B(24/6/0.12)+OUTER JACKET COROL:BEIGE(V-29) OD:8.1±0.15mm. L=1800±10mm.

RoHS compliant

Unit: mm

Scale	Free	Date	Name	Customer-No.			
TOLERANCE		Drawn	29.11.2018	Xavier			
		Approved	29.11.2018	Xavier			
DIM	TOL			Drawing-No.			
				ASS 8425 CA	rev00		
Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet
							1/1

1

2

3

4

5

6

7

H