



# Male Disconnects - Nylon Fully Insulated Butted Seam




| Product Number† | UPC (054007-) | Wire Range (AWG) | Male Tab Width(W) x Thickness | L    | W    | D    | Barrel Length | Barrel I.D. | Maximum Insulation Diameter | Terminals per: Carton Case |
|-----------------|---------------|------------------|-------------------------------|------|------|------|---------------|-------------|-----------------------------|----------------------------|
| MNU18-187DMIX   | 02354         | 22-18            | 0.187 x 0.020                 | 0.87 | 0.37 | 0.30 | 0.24          | 0.080       | 0.145                       | 100 500                    |
| MNU18-187DMIK   | 02379         | 22-18            | 0.187 x 0.020                 | 0.87 | 0.37 | 0.30 | 0.24          | 0.080       | 0.145                       | — 1000                     |
| MNU18-250DMIX   | 02289         | 22-18            | 0.250 x 0.032                 | 0.95 | 0.44 | 0.30 | 0.25          | 0.065       | 0.145                       | 100 500                    |
| MNU18-250DMIK   | 02299         | 22-18            | 0.250 x 0.032                 | 0.95 | 0.44 | 0.30 | 0.25          | 0.065       | 0.145                       | — 1000                     |
| MNU14-187DMIX   | 02381         | 16-14            | 0.187 x 0.020                 | 0.87 | 0.37 | 0.30 | 0.24          | 0.080       | 0.145                       | 100 500                    |
| MNU14-187DMIK   | 02385         | 16-14            | 0.187 x 0.020                 | 0.87 | 0.37 | 0.30 | 0.24          | 0.080       | 0.145                       | — 1000                     |
| MNU14-250DMIX   | 02306         | 16-14            | 0.250 x 0.032                 | 0.95 | 0.44 | 0.30 | 0.25          | 0.085       | 0.170                       | 50 500                     |
| MNU14-250DMIK   | 02306         | 16-14            | 0.250 x 0.032                 | 0.95 | 0.44 | 0.30 | 0.25          | 0.085       | 0.170                       | — 1000                     |
| MNU10-250DMIX   | 02307         | 12-10            | 0.250 x 0.032                 | 1.05 | 0.47 | 0.39 | 0.25          | 0.150       | 0.250                       | 50 500                     |
| MNU10-250DMIK   | 02301         | 12-10            | 0.250 x 0.032                 | 1.05 | 0.47 | 0.39 | 0.25          | 0.150       | 0.250                       | — 500                      |




**MNU18-187DMI**  
22-18  
Suggested Mate MNU18-187DFI




**MNU18-250DMI**  
22-18  
Suggested Mate MNU18-250DFI



**MNU14-187DMI**  
16-14  
Suggested Mate MNU14-187DFI



**MNU14-250DMI**  
16-14  
Suggested Mate MNU14-250DFI



**MNU10-250DMI**  
12-10  
Suggested Mate MNI10-250DFI

Wire Range  
Suggested Mate