



Miniature circuit breaker 240 V 14kA, 1-pole, C, 0.5A, D=70 mm according to UL 489, equal polarity

| Model | |
|---|--|
| product brand name | SENTRON |
| product designation | Miniature circuit breakers |
| design of the product | Miniature circuit-breaker 5SJ4 |
| General technical data | |
| number of poles | 1 |
| number of poles / note | 1P |
| tripping characteristic class | C |
| mechanical service life (switching cycles) / typical | 20 000 |
| installation environment regarding EMC | Suitable for environment B (immunity to interference not applicable) |
| reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750 | F |
| overvoltage category | 3 |
| degree of pollution | 3 |
| Voltage | |
| insulation voltage / at AC / rated value | 440 V |
| Supply voltage | |
| type of voltage | AC/DC |
| operational current / at AC / rated value | 0.5 A |
| supply voltage / at AC / rated value | 400 V |
| operating voltage | |
| • at AC / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum | 120 V |
| • at DC / rated value / maximum | 60 V |
| • at DC / single channel / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum | 60 V |
| supply voltage frequency | |
| • rated value | 50 Hz |
| Protection class | |
| protection class IP | IP20, with connected conductors, IP 40 in the handle range |
| Switching capacity | |
| switching capacity current | |
| • acc. to EN 60898 / rated value | 10 kA |
| • acc. to IEC 60947-2 / rated value | 15 kA |
| Dissipation | |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 1.2 W |
| Main circuit | |

| | |
|---|--|
| type of voltage supply / at AC / acc. to UL 489 and CSA C22.2 No. 5-02 | 240/120 |
| suitability for operation | Mechanical engineering / industry |
| Product details | |
| product function / neutral conductor switching | No |
| product feature / touch protection | Yes |
| product component | |
| • tunnel terminals top | No |
| • tunnel terminals bottom | No |
| • combined terminal top | Yes |
| • combined terminal bottom | Yes |
| product feature | |
| • halogen-free | Yes |
| • sealable | Yes |
| • silicon-free | Yes |
| product extension / installable / supplementary devices | Yes |
| Product function | |
| product function / note | Terminal tightening torque for Cu, 60/75°C; 3.5Nm/31lb.in |
| Short circuit | |
| breaking capacity short-circuit current (I _{cn}) / at AC / acc. to UL 1077 and CSA C22.2 No.235 | 14 kA |
| Connections | |
| connectable conductor cross-section / finely stranded / with core end processing | |
| • minimum | 1.5 mm ² |
| • maximum | 25 mm ² |
| position / of power supply cord | Any |
| Mechanical Design | |
| height | 90 mm |
| width | 18 mm |
| depth | 70 mm |
| installation depth | 70 mm |
| number of modular width units | 1 |
| fastening method | on standard mounting rail |
| mounting position | any |
| net weight | 166 g |
| Environmental conditions | |
| influence of the surrounding temperature | max. 95% humidity |
| vibration resistance | 50 m/s ² at 25 to 150Hz and 60m/s ² at 35Hz (4sec) |
| vibration resistance / acc. to IEC 60068-2-6 | 50 m/s ² at 25 to 150Hz and 60m/s ² at 35Hz (4sec) |
| ambient temperature | |
| • minimum | -25 °C |
| • maximum | 55 °C |
| ambient temperature / during storage | |
| • minimum | -40 °C |
| • maximum | 75 °C |
| Certificates | |
| reference code | |
| • acc. to DIN EN 61346-2 | F |
| • acc. to IEC 81346-2 | F |
| General Product Approval | |
| Declaration of Conformity | |



Test Certificates

[Miscellaneous](#)

[Special Test
Certificate](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SJ4105-7HG40>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SJ4105-7HG40>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SJ4105-7HG40

Tender specifications

<http://www.siemens.com/specifications>



