

Specification Sheet

Part Number: T150R0X2



Engineered and manufactured for maximum performance and quality.
Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Bent tail allows for simpler insertion.

Heavy Duty Cable Tie, 15" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg

Article Number	111-15200
----------------	-----------

Type	T150R(U)
------	----------

Color	Black (BK)
-------	------------

Quantity Per	bag
--------------	-----

Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
---------------------	---

Short Description	Heavy Duty Cable Tie, 15" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg
-------------------	---

Global Part Name	T150R(U)-PA66-BK
-------------------------	------------------

Minimum Tensile Strength (Imperial)	175.0
--	-------

Minimum Tensile Strength (Metric)	780.0
--	-------

Length L (Imperial)	15.0
----------------------------	------

Length L (Metric)	391.16
--------------------------	--------

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	No
---------------------------	----

Variant	Inside Serrated
----------------	-----------------

Width W (Imperial)	0.35
---------------------------	------

Width W (Metric)	8.9
-------------------------	-----

Bundle Diameter Min (Imperial)	0.31
---------------------------------------	------

Bundle Diameter Min (Metric)	8.0
-------------------------------------	-----

Bundle Diameter Max (Imperial)	4.13
---------------------------------------	------

Bundle Diameter Max (Metric)	105.0
-------------------------------------	-------

Thickness T (Imperial)	0.07
-------------------------------	------

Thickness T (Metric)	1.9
-----------------------------	-----

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL-ZODZ2.E64139
UL Recognized (US)	Yes
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25

Customs Number

3926909988

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)